

Ratings (Cont.)

Spectra™ RMS Main Circuit Breakers with Micro EntelliGuard Trip (MET) Units

BREAKER CAT NO.	MAX. RATING AMPS	REQ. BUS SPACE*	CIRCUIT BREAKER TYPE	SHORT CIRCUIT RATINGS, KA		
				240V	480V	600V
EZSEPA36AT0030	30	3X	SEP, 030A, 3P, 600VAC	200KA	100KA	25KA
EZSELA36AT0030	30	3X	SEL, 030A, 3P, 600VAC	100KA	65KA	25KA
EZSEHA36AT0030	30	3X	SEH, 030A, 3P, 600VAC	65KA	25KA	18KA
EZSEDA36AT0030	30	3X	SED, 030A, 3P, 600VAC	18KA	18KA	14KA
EZSKLC3612 [†]	1200	6X	SKL, 1200A, 3P, 600VAC	100ka	65ka	42ka
EZSKHC3612 [†]	1200	6X	SKH, 1200A, 3P, 600VAC	65ka	50ka	25ka
EZSKTC3412 [†]	1200	6X	SKT, 1200A, 3P, 480VAC	100ka	65ka	42ka
EZSKLL3610 [†]	1000	6X	SKL, 1000A, 3P, 600VAC	100ka	65ka	42ka
EZSKHH3610 [†]	1000	6X	SKH, 1000A, 3P, 600VAC	65ka	50ka	25ka
EZSKTT3410 [†]	1000	6X	SKT, 1000A, 3P, 480VAC	100ka	65ka	42ka
EZSKLC3608 [†]	800	6X	SKL, 800A, 3P, 600VAC	100ka	65ka	42ka
EZSKHC3608 [†]	800	6X	SKH, 800A, 3P, 600VAC	65ka	50ka	25ka
EZSKTC3408 [†]	800	6X	SKT, 800A, 3P, 480VAC	100ka	65ka	42ka
EZSGPC3606 [†]	600	4X	SGP, 600A, 3P, 600VAC	200ka	100ka	65ka
EZSGLC3606 [†]	600	4X	SGL, 600A, 3P, 600VAC	100ka	65ka	65ka
EZSGHC3606 [†]	600	4X	SGH, 600A, 3P, 600VAC	65ka	35ka	25ka
EZSGPC3604 [†]	400	4X	SGP, 400A, 3P, 600VAC	200ka	100ka	65ka
EZSGPP3604 [†]	400	4X	SGP, 400A, 3P, 600VAC	200ka	100ka	65ka
EZSGLC3604 [†]	400	4X	SGL, 400A, 3P, 600VAC	100ka	65ka	65ka
EZSGLL3604 [†]	400	4X	SGL, 400A, 3P, 600VAC	100ka	65ka	65ka
EZSGHC3604 [†]	400	4X	SGH, 400A, 3P, 600VAC	65ka	35ka	25ka
EZSGHH3604 [†]	400	4X	SGH, 400A, 3P, 600VAC	65ka	35ka	25ka

* Circuit breaker kits described above can only be used as main disconnects, and can be installed in the panelboard in any available position, assuming adequate space.

[†] Catalog numbers listed above have suffixes "L3" or "L4" or "L5" followed by either "X" or "R". See Catalog Number Structure for details.