


Hazardous Location Push Buttons

Product Selection

Complete Assembled Stations (Supplied with 3/4 in. Dead End Conduit Entry — Cat. No. 800H-1HZX7)

	Operator	Contact Symbol	Contact Action	Legend Marking	Lever Type Actuator*†	Component Type Buttons*‡
					Cat. No.	Cat. No.
 Cat. No. 800H-1HA7	One Push Button	 1 N.O. 1 N.C.	Momentary	STOP	800H-1HA7	800H-1HA7P
				START	800H-1HB7	800H-1HB7P
				JOG	800H-1HJ7	800H-1HJ7P
				No Legends	800H-1HX7	800H-1HX7P
 Cat. No. 800H-2HA7P	Two Push Buttons	 1 N.O. 1 N.C. Each Button	Momentary	START STOP	800H-2HA7	800H-2HA7P
				FOR REV	800H-2HB7	800H-2HB7P
				RAISE LOWER	800H-2HD7	800H-2HD7P
				OPEN CLOSE	800H-2HF7	800H-2HF7P
				No Legends	800H-2HX7	800H-2HX7P
 Cat. No. 800H-2HAM7	2-Position Selector Switch	 1 N.O. 1 N.C.	Maintained	START STOP	800H-2HAM7	—
				ON OFF	800H-2HCM7	800H-R2HC7
				OPEN CLOSE	800H-2HGM7	800H-R2HG7
				RUN STOP	800H-2HJM7	—
				HAND AUTO	800H-2HLM7	800H-R2HA7
				No Legends	800H-2HXM7	800H-R2HX7
 Cat. No. 800H-R3HA7	3-Position Selector Switch	 1 N.O. 1 N.C.	—	HAND OFF AUTO	—	800H-R3HA7
				No Legends	—	800H-R3HX7
 Cat. No. 800H-2HAD10R7	One Pilot Light, Dual Push Buttons	 120V AC/DC Full Volt./Red  1 N.O. 1 N.C.	—	No Legend START STOP	—	800H-2HAD10R7
				Marking other than listed - consult your local Allen-Bradley distributor	—	800H-2HDX10R7

* Operators have integral padlocking attachment.

* STOP is extended red, START is flush green, all others are flush black.

† Supplied with standard shallow contact blocks. For stations with sealed switch contacts, change Bulletin number from 800H to 800R. A deep enclosure is required.