



Representative Image

Catalog No. 9T21S1250**Description: "1A,25kVA,480-120/240,115C,N3R,SC20,QMS"****UPC No 783173030578****Home > Transformers > Dry Type Vented > Servicenter**

ABB's Single phase integrated main breaker load center with encapsulated dry type transformer ranging from 5 kVA to 25 kVA. Includes breakers for primary input and secondary output.

Descriptors

Category	Servicenter
GO Schedule	TF

Specifications

TransType	QMS
Phase	1
PriVoltage	480
SecVoltage	120/240
KVA	25.0 KVA
Coil Material	AL
TempRise	115.0 °C
ElecShield	N
Sub Type	Servicenter (NEMA 3R)
Frequency	60 Hz
Impedance	2.8 %
TempClass	180.0 °C
AmbTemp	40.0 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	NEMA 3R
Net Weight	388
Outline	303B915AAP025

Classifications

UL	Yes
cUL	No
CE	No


by ABB

Publications

Title	Publication No.	Publication Type
9T21S1250 LABEL		
AL 1P 25KVA 480-120/240V 115C DOE16 3R SERVICE CENTER LABEL	9T21S1250-LBL	Connection Diagram
Transformer Outline Drawing		
Outline drawing in .pdf format.	303B915AAP025	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.