

Product Selection



Model Type	Contacts		BBM/ MBB	Actuator	M20 Conduit		Quick Disconnect	
	Safety	Aux.			M20 Conduit	1/2in NPT Adaptor		End
Trojan 5 Standard	2 N.C.	1 N.O.	BBM	Standard	440K-T11090	440K-T11202	440K-T11205	
				Guide/Semi-Flex	440K-T11110	440K-T11203	440K-T11206	
				Guide/Fully-Flex	440K-T11467	440K-T11204	440K-T11207	
				—	440K-T11089	—	440K-T11129	
			BBM Gold Contacts	Standard	440K-T11085	—	—	
				MBB	Standard	440K-T11118	440K-T11208	440K-T11224
					Guide/Semi-Flex	440K-T11123	440K-T11209	440K-T11363
					Guide/Fully-Flex	440K-T11468	440K-T11210	440K-T11364
—	440K-T11146	440K-T11469	440K-T11365					
Trojan 5 GD2 Front Entry	2 N.C.	1 N.O.	BBM	GD2 Standard	440K-T11336	440K-T11211	440K-T11366	
				Guide/Semi-Flex	440K-T11337	440K-T11212	440K-T11367	
				Guide/Fully-Flex	440K-T11338	440K-T11213	440K-T11368	
				—	440K-T11147	—	440K-T11226	
			MBB	Standard	440K-T11339	440K-T11470	440K-T11369	
				Guide/Semi-Flex	440K-T11340	440K-T11471	440K-T11370	
				Guide/Fully-Flex	440K-T11341	440K-T11472	440K-T11371	
				—	440K-T11167	—	440K-T11372	
	Recommended mating cable for Trojan 5, 2m (6.5ft). See page 15-11 for details and additional lengths.						889R-F6ACA-2	