



Representative Image

**Catalog No. TC35321****Description: 30A 3P DBL THR N1 240V NONFUSE****UPC No 783164001686****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). 60/75 C conductor rating. Full cover interlocks. TC35321

**Descriptors**

Category	Double Throw
GO Schedule	SB

**Specifications**

Voltage	240 AC
Amperage	30 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 1 (Indoor)
Options	None
Wire Range (Cu/Al)	14-8 (Cu)
240 Vac, NEC Std, 3-ph	2.0 hp
GSA Compliance	Yes

**Classifications**

cUL Listed	Yes
UL Listed	Yes

**Dimensions**

Height	15.8 in
Depth	5.2 in
Width	10.4 in
Weight	14.0 lb

