



Catalog No. THN2261RDC

Description: 30A 2P HD N3R 600VDC NONFUSE SW

UPC No 783164082258

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

Designed specifically for 600Vdc motor applications. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. THN2261R



Representative Image

Descriptors

| | |
|-------------|------------|
| Category | Heavy Duty |
| GO Schedule | S1 |

Specifications

| | |
|--------------------|-------------------|
| Voltage | 600 DC |
| Amperage | 30 A |
| Poles | 2 |
| Wires | 2 |
| Fusing | No Fuse |
| Enclosure | NEMA 3R (Outdoor) |
| Options | None |
| Wire Range (Cu/Al) | 12-2 |
| 125 Vdc | 3.0 hp |
| 250 Vdc | 5.0 hp |
| 600 Vdc | 15.0 hp |
| GSA Compliance | Yes |

Classifications

| | |
|------------|-----|
| cUL Listed | Yes |
| UL Listed | Yes |

Dimensions

| | |
|--------|---------|
| Height | 13.1 in |
| Depth | 4.0 in |
| Width | 8.2 in |
| Weight | 11.0 lb |



