



PRINT

Manual Transfer Switch

T&B Catalog Number: OT60F3C
UPC Number: 80432541563
Status: Active

Description:

3 pole, 60 amps rated at 600 VAC, UL 98, double throw open non-fusible disconnect switch



SUBMITTAL
PACKAGE

Where To Buy

Enter Zip Code:

Enter Quantity:

GO

Features

- Quick make, quick brake mechanism
- Extremely compact size
- Finger-proof construction with no hazardous exposed parts

Application

- Suitable for use as motor disconnects or industrial control panel disconnects on service entrance equipment, panelboards, switchboards, industrial control equipment, motor control centers, etc.
- Motor feeder applications and motor feeder short circuit and ground fault protection
- Kits with base and/or DIN rail mounted switches and pistol handles

General

Style	Double Throw
Number of Poles	3
Series	Non-fusible

Approvals

UL Class	UL 98
----------	-------

Dimension Information

H x W x D (inches)	3.94 x 2.76 x 2.93
--------------------	--------------------

Specifications

Rated Current (Amps)	60
Rated Voltage AC	600

Packaging

Outer Package	1
Package Height	0.37
Package Length	0.82
Package Width	0.42
T&B Sold in UOM	Each
T&B Weight Per UOM	2.05 lbs. Each

HOME

Global Site
Report Issue

LOGIN

T&B Access (Dist only)
Suppliers
MyTNB

RESOURCES

Catalog PDFs
End User Toolkit
Solution Set Brochures
Vertical Market Brochures
Where To Buy

SUPPORT

Contact Us
Global Locations
Product Support
Tool Services
Legal/Privacy

COMPANY

About Us
Careers
Employees
News



© 2014 Thomas & Betts Corporation