

Control relays

K622 - K640

AC & DC operated

4



K6-40E-84



KC6-31Z-2.4

Control relays with screw connections

	Contact configuration		Thermal current A	Catalog number	List price
	N.O.	N.C.			
AC Operated	4 3 2	0 1 2	6	K6-40E-Δ K6-31Z-Δ K6-22Z-Δ	\$ 48
DC Operated	4 3 2	0 1 2	6	KC6-40E-Δ KC6-31Z-Δ KC6-22Z-Δ	59

Control relays with flat pin connections

	Contact configuration		Thermal current A	Catalog number	List price
	N.O.	N.C.			
AC Operated	4 3 2	0 1 2	6	K6-40E-FΔ K6-31Z-FΔ K6-22Z-FΔ	\$ 48
DC Operated	4 3 2	0 1 2	6	KC6-40E-FΔ KC6-31Z-FΔ KC6-22Z-FΔ	59

Control relays with soldering pin connections

	Contact configuration		Thermal current A	Catalog number	List price
	N.O.	N.C.			
AC Operated	4 3 2	0 1 2	6	K6-40E-PΔ K6-31Z-PΔ K6-22Z-PΔ	\$ 48
DC Operated	4 3 2	0 1 2	6	KC6-40E-PΔ KC6-31Z-PΔ KC6-22Z-PΔ	59

Coil voltage selection

Δ Coil voltage suffix. Refer to Coil Voltage Selection Chart and substitute the desired coil voltage suffix for the Δ.

Coil voltage selection chart

	Volts								
	12	24	42	48	110/125	110/120	220	220/240	380/415
AC (40-450 Hz)		01	02	03		84		80	85
DC	07	01	02	16	04		05		