



Catalog No. 9T83B2610

Description: AL 1P 15KVA 208-120/240 150C K1

UPC No 783173269343

Home > Transformers > Dry Type Vented > General Purpose

GE Type QL transformers meet NEMA TP-1 efficiency standards. They are available with aluminum or copper windings and utilize a UL recognized 220°C insulation system.

- Quiet Performance
- Core and coil assemblies are mounted on rubber isolation pads to reduce noise
- Bolted coil terminations
- Single-piece front/back is easily removable for service
- NEMA 2 drip-proof enclosure is standard; weathershield kits are available for conversion to NEMA 3R outdoor configuration
- Qualified to the seismic requirements of IEEE-693-2005, IBC-2012, and CBC 2013
- Copper or aluminum windings
- Copper ground strap
- Robust packaging with top and side protection protects against shipping damage
- Accessible mounting flanges with front/back slotted mounting holes make installation easier
- 100% factory tested for shorts and coil integrity, current and loss, voltage, impedance and noise.
- Clear, comprehensive documentation and labeling

Descriptors

| | |
|----------|-----------------|
| Category | General Purpose |
|----------|-----------------|

Specifications

| | |
|------------------|-----------|
| Phase | 1 |
| PriVoltage | 208 |
| SecVoltage | 120/240 |
| KVA | 15.0 KVA |
| Coil Material | AL |
| TempRise | 150.0 °C |
| Frequency | 60 Hz |
| AmbTemp | 40.0 °C |
| EnergyEfficiency | NEMA TP 1 |
| KFactor | K1 |
| Enclosure Type | NEMA 2 |
| Sound | Std |
| GSA Compliance | No |

Classifications

| | |
|----|---|
| CE | 0 |
|----|---|

Publications

| Title | Publication No. | Publication Type |
|--|-----------------|--------------------|
| UL Nameplate Drawing | | |
| UL Nameplate Drawing 9T83B2610-LBL | 9T83B2610-LBL | Connection Diagram |
| QL Dry Type Transformers | | |
| Rev. D | DEA-492 | Brochures |

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.