Instrument Transformers, Inc
a division of GE Multilin

Ground Fault Current Transformer Type HGF3C

Part Number 19RT-SD-38137

50:0.025 Amps (2000:1 Ratio)

Replaces Multilin P/N HGF3

Notes:
1. Ratio 50:0.025Amp
2. Insulation Class: 0.6kV, 10kV BIL
3. Frequency: 50-60Hz
4. DC Resistance approximately 26 ohms
5. Thermoplastic case on metal bracket
6. Terminals are #10-32 brass studs with one flat washer, lockwasher, and regular nut
7. Approximate weight: 3.0 lbs. (1.4 kg)
8. UL and cUL recognized
9. Dimensions shown as inches [mm]
10. Application: Ground fault sensors to work in conjunction with GE Multilin motor management relays.

Specially designed to match the ground fault input of GE Multilin motor protection relays and should be used to ensure correct performance. This CT can sense low leakage currents over the relay setting range with minimum error.





US, Canada, Asia, Latin America
Tel: +1-800-547-8629
Fax: +1-905-201-2455
e-mail: sales.multilin@ge.com

Europe, Middle East, Africa
Tel: +34 94 485 88 00
Fax: +34 94 485 88 45
e-mail: gemultilin.euro@ge.com