



T&B Catalog Number: B7S-30-10-1.7
UPC Number: 80432539478
Item Status: Active

Description:

The B7S-30-10 mini contactor is a compact 3 pole contactor with 1 auxiliary contact and screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Due to the low coil consumption, this device can be directly controlled by a PLC. Further features are the noiseless and hum-free coil, the integrated protective circuit with diodes and additional overvoltage protection, a switch position indication and the integrated possibility for rail or wall mounting. Auxiliary contacts,

Packaging

T&B Sold in UM:
T&B Weight per UOM: 4 lbs. per Each

General Information

Harmonized Code: 8536490065

HOME

[Global Site](#)
[Report Issue](#)

LOGIN

[T&B Access \(Dist only\)](#)
[Suppliers](#)
[MyTNB](#)

RESOURCES

[Catalog PDFs](#)
[End User Toolkit](#)
[Solution Set Brochures](#)
[Vertical Market Brochures](#)
[Where To Buy](#)

SUPPORT

[Contact Us](#)
[Global Locations](#)
[Product Support](#)
[Tool Services](#)
[Legal/Privacy](#)

COMPANY

[About Us](#)
[Careers](#)
[Employees](#)
[News](#)

