

Technical Data

Steel Disconnects N3R Outdoor Enclosure

Type	Volts	Fusing	Amps	HP Rating	Catalog No.	Std. Pkg.
Pullout	240	Fusible	30	3	TF30R	6
			60	10	TF60R	
		Non-Fusible	60	10	TFN60R	
Non-Automatic	240	Non-Fusible	60	10	TNA60R1¹	

¹ Device does not have removable closing cap.



Plastic Disconnects N3R Outdoor Enclosure

Type	Volts	Fusing	Amps	HP Rating	Catalog No.	Std. Pkg.
Pullout	240	Fusible	30	3	TPF30R	6
			60	10	TPF60R	
		Non-Fusible	60	10	TPN60R1¹	
			60	10	TPN60R	
Non-Automatic	240	Non-Fusible	60	10	TPNA60R1¹	


¹ Device does not have removable closing cap.



Steel Disconnects N3R Outdoor Enclosure with Ground Fault Receptacle

Type	Volts	Fusing	Amps	HP Rating	Catalog No.	Std. Pkg.
Pullout	240	Non-Fusible	60	10	TFN60RGFR¹	6
Non-Automatic					TNA60RGFR¹	

¹ These disconnects include a GFCI outlet.



Wire Range

Connector	Copper		Aluminum	
	Solid	Strand	Solid	Strand
Line	14-8	14-2	12-8	12-2
Load	14-8	14-2	12-8	12-2
Neutral	—	—	—	—
Equipment Ground	12-8	12-2	12-8	12-2

Dimensions (inches)

Catalog No.	Height (A)	Width (B)	Depth (C)
TF30R	7.5	5.19	2.5
TF60R	9.25	5.19	2.5
TFN60R	7.5	5.19	2.5
TFN60RGFR	7.13	5.5	5.19
TNA60R1	7.5	5.19	2.5
TNA60RGFR	7.13	5.5	5.19
TPF30R	7	5.75	3.13
TPF60R	7	5.75	3.13
TPN60R	8	5	3
TPN60R1	7.5	5.19	2.5
TPNA60R1	7	5.75	3.13

