

General Information

Extended Product Type:	AF16-40-00-11
Product ID:	1SBL177201R1100
EAN:	3471523115118
Catalog Description:	AF16-40-00-11 24-60V50/60HZ 20-60VDC Contactor
Long Description:	AF16 4-pole contactors are used for controlling power circuits up to 690 V AC and 440 V DC. They are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...). AF... contactors include an electronic coil interface accepting a wide control voltage $U_c \min. \dots U_c \max.$ Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available. Note: - AF...-...-11 not suitable for a direct control by PLC-output. - AF...-...-11 type available in some countries: please consult your ABB representative.

Additional Information

ABB Industrial IT Suite:	Control IT
ABS Certificate:	ABS_15-GE1349500-PDA_90682247
Ambient Air Temperature:	Close to Contactor for Storage -60...+80 °C Near Contactor for Operation in Free Air -40 ... +70 °C
Block Contactor Type:	4-Pole Contactor
CB Certificate:	CB_SE_70857M1
CCC Certificate:	CCC_2010010304445624
Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
Coil Voltage Code:	11
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Connecting Capacity Main Circuit:	Flexible with Insulated Ferrule 1x 0.75...4 mm ² Flexible with Insulated Ferrule 2x 0.75...2.5 mm ² Flexible with Ferrule 1/2x 0.75...6 mm ² Rigid 1/2x 1...6 mm ²
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 35 A
Country of Origin:	France (FR)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	1SBC101420D0201
Declaration of Conformity - CE:	1SBD250001U1000
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
E-number:	3211465
EAC Certificate:	EAC_RU C-FR ME77 B01010
EAN:	3471523115118
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / Contactors
EPLAN Function Definition:	Coil / Coil, 2 connection points / Coil for power contactor A1_A2 NO contact / NO contact. 2 connection points / Power NO contact 1 2

	NO contact / NO contact, 2 connection points / Power NO contact 3_4 NO contact / NO contact, 2 connection points / Power NO contact 5_6 NO contact / NO contact, 2 connection points / Power NO contact 7_8
EPLAN Macro:	9AKK106930A0692
ETIM 4:	EC000066 - Magnet contactor, AC-switching
ETIM 5:	EC000066 - Magnet contactor, AC-switching
ETIM 6:	EC000066 - Power contactor, AC switching
Environmental Information:	1SBD250147E1000
GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
General Use Rating UL/CSA:	(600 V AC) 30 A
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SBC101027M6801
Invoice Description:	AF16-40-00-11 24-60V50/60HZ 20-60VDC Contactor
LR Certificate:	LRS_1300087E1
Low Coil Consumption:	No
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 106 A
Maximum Electrical Switching Frequency:	AC-1 600 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Maximum Operating Altitude Permissible:	3000 m
Minimum Order Quantity:	1 piece
Mounted Auxiliary Contacts:	0 NO, 0 NC
Mounted Auxiliary Contacts 1st Stack:	0 NO, 0 NC
Mounted Auxiliary Contacts 2nd Stack:	0 NO, 0 NC
Mounting Position:	Max. add-on N.C. auxiliary contacts: see accessory fitting details for a 4-pole contactor AF09 ... AF38
Mounting Positions:	1SBC500297F0000
Number of Auxiliary Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Main Contacts NC:	0
Number of Main Contacts NO:	4
Object Classification Code:	Q
Operate Time:	Between Coil De-energization and NC Contact Closing 13...98 ms Between Coil De-energization and NO Contact Opening 11...95 ms Between Coil Energization and NC Contact Opening 38...90 ms Between Coil Energization and NO Contact Closing 40...95 ms
Order Multiple:	1 piece
Package Level 1 EAN:	3471523115118
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 Height:	47 mm
Package Level 1 Length:	79 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	87 mm
Package Level 2 Height:	315 mm
Package Level 2 Length:	300 mm
Package Level 2 Units:	54 piece
Package Level 2 Width:	250 mm
Package Level 3 Units:	1296 piece
Power Loss:	at Rated Operating Conditions AC 4-pole Pole 1 3 W

Power Loss:	at Rated Operating Conditions AC-1 per Pole 1.2 W
Product Main Type:	AF16
Product Name:	Block Contactor
Product Net Depth:	77 mm
Product Net Height:	86 mm
Product Net Weight:	0.270 kg
Product Net Width:	45 mm
Product Packing Type:	Box
RINA Certificate:	RINA_ELE084013XG
RMRS Certificate:	RMRS_1400682124
Rated Control Circuit Voltage (U_c):	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 30 A (690 V) 60 °C 30 A (690 V) 70 °C 26 A
Rated Operational Current AC-3 (I_e):	(220 / 230 / 240 V) 60 °C 18 A (380 / 400 V) 60 °C 18 A (415 V) 60 °C 18 A (440 V) 60 °C 18 A (500 V) 60 °C 15 A (690 V) 60 °C 10.5 A
Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 4 kW (380 / 400 V) 7.5 kW (400 V) 7.5 kW (415 V) 9 kW (440 V) 9 kW (500 V) 9 kW (690 V) 9 kW
Rated Operational Voltage:	Main Circuit 690 V
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A
Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations acc. to IEC 60068-2-6:	5 ... 300 Hz 4 g closed position / 2 g open position
RoHS Date:	20090609
RoHS Information:	1SBD251011E1000
Selling Unit of Measure:	piece
Short Description:	AF16-40-00-11 24-60V50/60HZ 20-60VDC Contactor
Standards:	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14
Terminal Type:	Screw Terminals
Tightening Torque:	Control Circuit 1.2 N·m Main Circuit 1.5 N·m
Tightening Torque UL/CSA:	Control Circuit 11 in·lb

Main Circuit 13 in·lb

UL Certificate:	UL_20120918-E319322-3-1
UL Listing Card:	UL_E319322
Wire Stripping Length:	Control Circuit 10 mm Main Circuit 10 mm
DNV GL Certificate:	DNV-GL_E13871

