



Representative Image

**Catalog No. TDT3365SS****Description: 400A 3P DBL THR 4/4X SS 600V FUSIBL****UPC No 783164486070****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). 60/75 C conductor rating. Full cover interlocks. NEMA 4 X 304 Stainless Steel enclosure. TDT3365S

**Descriptors**

Category	Double Throw
GO Schedule	SB

**Specifications**

Voltage	600 AC
Amperage	400 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 4/4X Stainless Steel
Wire Range (Cu/Al)	(2) 1/0 - (2) 300 or (1) 1/0 - 750 (Cu/Al)
240 Vac, NEC Std, 3-ph	50.0 hp
240 Vac, Time Delay, 3-ph	125.0 hp
480 Vac, NEC Std, 3-ph	100.0 hp
480 Vac, Time Delay, 3-ph	250.0 hp
600 Vac, NEC Std, 3-ph	125.0 hp
600 Vac, Time Delay, 3-ph	350.0 hp
250 Vdc	50.0 hp
GSA Compliance	No

**Classifications**

cUL Listed	Yes
UL Listed	Yes

**Dimensions**

Height	37.9 in
Depth	6.5 in
Width	19.6 in
Weight	260.0 lb

  
**by ABB**

