

Lighting Contactors

CR463L

Modified Assembled Forms – Electrically Held

Section 3

CR463L Electrically Held Contactors

Follow the diagram and tables below to select the options and corresponding product number digits for your modified contactor. Total the prices for each selection to arrive at the total list price, GO-10MB.

	1	2	3	4	5	6	7	8	9
CR463L			A						

CR463L Base Price		
NO Power Pole Contact Configuration	1	
NC Power Pole Contact Configuration	2	
Standard Control	3	
Coil Voltage	4	
Additional Auxiliary Contacts	5	
Enclosures	6	
Pilot Devices	7	
Pilot Lights	8	
Control Circuit Fuses/ Control Power Transformers	9	
Total		

1 & 2 Power Pole Contact Configuration

The number of NO contacts is digit 1 and the number of NC contacts is digit 2.

NO Contacts Digit 1	List Price Adder, GO-10MB								
	NC Contacts Digit 2								
	0	1	2	3	4	5	6	7	8
0									
1									
2									
3									
4									
5									
6									
7									
8									
9									
10 (B) ¹									
11 (C) ¹									
12 (D) ¹									

¹For digit 1 with 10 NO contacts use B; for 11 NO contacts, use C; for 12 NO contacts, use D.

3 Standard Control

Digit 3: A

4 Coil Voltage

There is no price adder to coil selection.

Coil Voltage		
AC, 60Hz	AC, 50Hz	Digit 4
24V	20V	C
28V	24V	D
115-120V	110V	J
200-208V	—	L
230-240V	220V	S
277V	240V	N
347V	—	T
460-480V	440V	U
575-600V	550V	Y

