



## Catalog No. TH2262DC

**Description: 60A 2P HD N1 600VDC FUSIBLE**

**UPC No 783164082173**

**Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed specifically for 600Vdc motor applications. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH2262DC



Representative Image

### Descriptors

Category	Heavy Duty
GO Schedule	S1

### Specifications

Voltage	600 DC
Amperage	60 A
Poles	2
Wires	2
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	None
Wire Range (Cu/Al)	12-2
125 Vdc	5.0 hp
250 Vdc	10.0 hp
600 Vdc	25.0 hp
GSA Compliance	No

### Classifications

cUL Listed	Yes
UL Listed	Yes

### Dimensions

Height	21.3 in
Depth	5.0 in
Width	9.1 in
Weight	18.0 lb



