Industrial USB Cables

AB *Allen-Bradley*

9300-USBCBL-CNSL, 9300-USBCBL-CP3 and 9300-USBCBL-PM02

Benefits

- Single cable solution for serial connectivity
- No additional drivers are needed (Windows 7 or higher)
- Directly connect from personal computer USB port to serial devices
- Built-in USB adapter uses industry standard chipset
- High quality cables with molded strain relief
- USB to serial conversion is transparent to application software

As technology evolves, so do the physical connections to hardware. As a global leader in industrial networking technology, Rockwell Automation now offers three more avenues of connectivity. The 9300-USBCBL-CNSL, the 9300-USBCBL-CP3 and the 9300-USBCBL-PM02 cables all replace cumbersome combinations of serial adapters and cables. Each allows you to directly connect to the USB port on your computer, simplifying the set-up and installation of switches and/or devices.

The 9300-USBCBL-CNSL cable allows you to directly connect to a Cisco or Stratix® switch. Conveniently configure using the command-line interface and run diagnostics from the switch. This cable replaces the need for a combination of a serial adapter and Cisco console cable.

The 9300-USBCBL-CP3 and 9300-USBCBL-PM02 cables allow you to quickly and easily connect directly to a controller's serial port via the USB port on your computer. These cables support the RSLinx® Auto-Configure feature. Both come in high visibility orange. This 9300-USBCBL-CP3 cable is designed for use with SLC™, PLC-5®, ControlLogix® and CompactLogix™ controllers, as well as PanelView™ Plus 7 Standard and Performance and includes the null adapter for downloads with standard PanelView™ graphic terminals. It replaces the combination of a serial adapter and 1756-CP3 or 1747-CP3 cable. The 9300-USBCBL-PM02 cable is designed for use with MicroLogix™ controllers and PanelView Plus 7 Standard and Performance and replaces the combination of a serial adapter and 1761-CBL-PM02.

Services & Support
Servicios y Soporte · 服务与支持 · Serviços e Suporte · Services et Assistance technique · Dienstleistungen und Unterstützung

LISTEN. THINK. SOLVE.®

AB *Allen-Bradley* • *Rockwell Software*

Rockwell Automation

Cable Specifications

	9300-USBCBL-CNSL	9300-USBCBL-CP3	9300-USBCBL-PM02
Designed for use with	Cisco and Stratix switches	CompactLogix, ControlLogix, PanelView Plus 7 Standard and Performance, PLC-5 and SLC	MicroLogix controllers and PanelView Plus 7 Standard and Enhanced
Connector Style	USB-A RJ45	USB-A 9 Pin D-sub connector	USB-A 8-pin MicroLogix
Cable Type	Serial	Serial	Serial
Cable Length	2 meters	2 meters	2 meters
Software Compatibility	Cisco Command-Line Interface (CLI)	RSLinx & RSLinx Enterprise	RSLinx & RSLinx Enterprise

www.rockwellautomation.com