

	Description	Handle Color	Frame Size	Cat. No.
	• P-style handle for G, H, I, and J frames • Medium handles for K, M, and N frames • Rated 3/3R/4/4X/12 • Accepts 3 padlocks	Black/Grey	G, H, I, J	140U-PB
		Red/Yellow		140U-PY
		Black/Grey	K, M, N	140U-HM4
		Red/Yellow		140U-HM4E
Representative Photo				

	Description	Shaft Length	Frame Size	Cat. No.
	Extension Shaft	12 in. (305 mm)	G, H, I, J	194R-S1
		21 in. (533 mm)		194R-S2
		12 in. (305 mm)	K, M, N	140U-R5
21 in. (533 mm)		140U-R6		
Representative Photo				

	Description	Shaft Length	Frame Size	Cat. No.
	NFPA 79 internal operating handle with shaft Internal handle permits operation of the molded case circuit breaker when the door is open in compliance with NFPA 79.	12 in. (305 mm)	G, H, I, J	140G-N1
		21 in. (533 mm)		140G-N2
		12 in. (305 mm)	K, M, N	140G-N7
		21 in. (533 mm)		140G-N8
Representative Photo				

	Description	Frame Size	Cat. No.
	Rotary, Variable Depth Operating Mechanism • Direct molded case circuit breaker mount • G, H, I, and J frame use 194R-S1 or 194R-S2 shafts (140G-N1 or 140G-N2 NFPA) • K, M, and N frames use 194R-R7 or 194R-R8 shafts (140G-R7 or 140G-R8 NFPA) • Shaft secured with set screw or cotter pin	G, I	140G-G-RMX
		H, J	140G-H-RMX
		K	140G-K-RMX
		M	140G-M-RMX
		N	140G-N-RMX
Representative Photo			

Description	Frame Size	Cat. No.
Support Bracket Supplied as standard with NFPA variable depth operator kits	G, H, I, J	140G-G-OSB
	K	140G-K-OSB
	M	140G-M-OSB
	N	140G-N-OSB

Auxiliary Contacts for Handle Mechanism Mounting

Suitable for:

- 140G-G-RMB, -RMY, RMX

- 140G-H-RMB, -RMY, RMX

- 140G-K-RMB, -RMY, RMX

- 140G-M-RMB, -RMY, RMX

	Description	Pkg. Qty	Frame Size	Cat. No.
	Early Make Handle Auxiliary Contact Open 400V	2	G, H, I, J	140G-G-EAM1B
	Early Break Handle Auxiliary Contact Close 400V	2		140G-G-EAB1B
	Early Make Handle Auxiliary Contact Close 250V	2	K	140G-K-EAM1A
M			140G-M-EAM1A	
Representative Photo				

Direct Rotary Operators