

Safety Switches

AC Disconnects

Spec-Setter™ Safety Switches

Section 4

Air Conditioner Disconnects

- Puller or Non-Automatic Type
- UL and cUL Listed
 - Fusible – UL869
 - Service Equipment
 - No fuse – UL1429
 - Enclosed Pull-out Switch



Steel Disconnects N3R Outdoor Enclosure

Type	Volts	Fusing	Amps	HP Rating	Product No.	Standard Package
Pullout	240V	Fusible	30	3	TF30R	6
			60	10	TF60R	
		Non-Fusible	60	10	TFN60R	
			60	10	TNA60R1 ¹	
Non-Automatic	240V	Non-Fusible	60	10	TNA60R1 ¹	

¹Device does not have removable closing cap.



Plastic Disconnects N3R Outdoor Enclosure

Type	Volts	Fusing	Amps	HP Rating	Product No.	Standard Package
Pullout	240V	Fusible	30	3	TPF30R	6
			60	10	TPF60R	
		Non-Fusible	60	10	TPN60R	
			60	10	TPN60R1 ¹	
Non-Automatic	240V	Non-Fusible	60	10	TPNA60R1 ¹	

¹Device does not have removable closing cap.



Steel Disconnects N3R Outdoor Enclosure with Ground Fault Receptacle

Type	Volts	Fusing	Amps	HP Rating	Product No.	Standard Package
Pullout	240V	Non-Fusible	60	10	TFN60RGFR ²	6
Non-Automatic					TNA60RGFR ²	

²These disconnects include a GFCI outlet



Wire Range Table

	Copper		Aluminum	
	Solid	Stranded	Solid	Stranded
Connector	14 - 8	14 - 2	12 - 8	12 - 2
Line	14 - 8	14 - 2	12 - 8	12 - 2
Load	-	-	-	-
Neutral	-	-	-	-
Equipment Ground	12 - 8	12 - 2	12 - 8	12 - 2

Dimensions (inches)

Product No.	Height (A)	Width (B)	Depth (C)
TF30R	7.5	5.19	2.5
TF60R	9.25	5.19	2.5
TFN60R	7.5	5.19	2.5
TFN60RGFR	7.13	5.5	5.19
TNA60R1	7.5	5.19	2.5
TNA60RGFR	7.13	5.5	5.19
TPF30R	7	5.75	3.13
TPF60R	7	5.75	3.13
TPN60R	8	5	3
TPN60R1	7.5	5.19	2.5
TPNA60R1	7	5.75	3.13

