Cordsets and Patchcords, DC Micro Style

18 and 22 AWG, Yellow, Black, or Blue PVC

Pinout and Color Code

	Face View Pinout									
	2-1	Pin	3-	Pin	4-Pin		5-Pin			
Color			1-	5	5 2 1					
Code				Female	Male					
А	1 NA 2 NA 3 Brown	4 Blue 5 NA	1 Brown 2 NA 3 Blue	4 Black 5 NA	1 Brown 2 White 3 Blue	4 Black 5 NA	1 Brown 2 White 3 Blue	4 Black 5 Grey		
В	1 Brown 2 NA 3 NA	4 Blue 5 NA	-	_	_		_			

Product Selection

			Wire Size	Cat. No.∗				
No. of Pins	Color Code	Jacket Color	[AWG]	Straight Female	Right Angle Female	Straight Male	Right Angle Male	
2-Pin	А	Yellow		889D-F2AC-2	889D-R2AC-2	889D-M2AC-2	889D-E2AC-2	
2-PIII	В	Black	22	889D-F2BC-Q2	889D-R2BC-Q2	_	_	
3-Pin	Α	Yellow	22	889D-F3AC-2	889D-R3AC-2	889D-M3AC-2	889D-E3AC-2	
	А	Yellow		889D-F4AC-2	889D-R4AC-2	889D-M4AC-2	889D-E4AC-2	
4 Din		Yellow	18	889D-F4AE-2	889D-R4AE-2	889D-M4AE-2	889D-E4AE-2	
4-Pin		Black	22	889D-F4BC-2	889D-R4BC-2	889D-M4BC-2	889D-E4BC-2	
		Blue		889D-F4LC-2	889D-R4LC-2	889D-M4LC-2	889D-E4LC-2	
5 Di-	А	Yellow	22	889D-F5AC-2	889D-R5AC-2	889D-M5AC-2	889D-E5AC-2	
5-Pin		Black		889D-F5BC-2	889D-R5BC-2	889D-M5BC-2	889D-E5BC-2	

^{*} The 2 at the end of the cat. no. is for 2 m cable length. Replace the 2 with 5 (5 m) or 10 (10 m) for standard cable lengths.

Patchcords Patchcords

				Cat. No.∜				
No. of Pins	Color Code	Jacket Color	Wire Size [AWG]	Straight Female Straight Male	Straight Female Right Angle Male	Right Angle Female Straight Male	Right Angle Female Right Angle Male	
2-Pin	А	Yellow	22	889D-F2ACDM-2	889D-F2ACDE-2	889D-R2ACDM-2	889D-R2ACDE-2	
2-7111	В	Black	22	889D-F2BCDM-Q2	889D-F2BCDE-Q2	889D-R2BCDM-Q2	889D-R2BCDE-Q2	
3-Pin	А	Yellow	22	889D-F3ACDM-2	889D-F3ACDE-2	889D-R3ACDM-2	889D-R3ACDE-2	
	А	Yellow	22	889D-F4ACDM-2	889D-F4ACDE-2	889D-R4ACDM-2	889D-R4ACDE-2	
	A‡	Yellow	22	889D-F4ACDM-V2	889D-F4ACDE-V2	889D-R4ACDM-V2	889D-R4ACDE-V2	
4-Pin	А	Yellow	18	889D-F4AEDM-2	889D-F4AEDE-2	889D-R4AEDM-2	889D-R4AEDE-2	
	A	Black	22	889D-F4BCDM-2	889D-F4BCDE-2	889D-R4BCDM-2	889D-R4BCDE-2	
	А	Blue	22	889D-F4LCDM-2	889D-F4LCDE-2	889D-R4LCDM-2	889D-R4LCDE-2	
F Din	А	Yellow	22	889D-F5ACDM-2	889D-F5ACDE-2	889D-R5ACDM-2	889D-R5ACDE-2	
5-Pin		Black		889D-F5BCDM-2	889D-F5BCDE-2	889D-R5BCDM-2	889D-R5BCDE-2	

The 2 at the end of the cat. no. is for 2 m cable length. Replace the 2 with OM3 (0.3 m), 1 (1 m), 5 (5 m), or 10 (10 m) for standard cable lengths.

Note: Stainless steel connector versions may be ordered by adding an S to the cat. no., e.g., 889DS-F4AC-__.



[‡] See Wiring Diagrams on page 3-44