


	Description	Frame Size	Handle Type	Cable Length	Cat. No.
	- For use with NEMA-style flange enclosures. - Includes handle, MCCB operator, cable, and necessary hardware. - Pre-assembled for ease of installation. - Replacement Hardware is listed on page 100	M	Non-metallic Handle, Type 1/3/12/4/4X	4 ft (1.3 m)	140G-M-FCX04
				6 ft (1.9 m)	140G-M-FCX06
				10 ft (3.0 m)	140G-M-FCX10
			Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-M-FCS04
				6 ft (1.9 m)	140G-M-FCS06
				10 ft (3.0 m)	140G-M-FCS10
			Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-M-FMX04
				6 ft (1.9 m)	140G-M-FMX06
				10 ft (3.0 m)	140G-M-FMX10
	Left-hand flange-mount bracket - relocates cable to left side - ideal for enclosures less than 15 in. (38.1 cm) deep	M	—	—	140G-BML
				—	140G-BNL
				—	140G-BNL

Additional Accessories

	Description	Frame Size	Cat. No.
	Trip Test Battery	H, J, K, M (LSI, LSIG, MM) N/NS (LSI)	140G-ELTT
	Battery Unit Used to interrogate the last trip of the MCCB when supplemental control power is not present or is lost. Use with LSIG and LSIG-MM breakers	N, NS	140G-ELBU
	Padlockable Handle Block Padlocking Hasp Lock-OFF only	G, I	140G-G-PL
		H, J	140G-H-PL
		N	140G-N-PL
		NS	140G-NS-PL
		R	140G-R-PL
	Padlocking Flange Supplied with toggle extension and escutcheon. Lock-OFF only	K	140G-K-TPA
		M	140G-M-TPA
	Direct Mechanical Lock to Door	N	140G-N-SINT