



DC Micro Cordsets & Patchcords 889D

- 4-, 5-, and 8-pin connectors
- Straight or right angle versions
- 22 or 24 AWG cable
- Oil-resistant yellow, black or red PVC jacket

Product Selection

Cordsets

| Female (Sensor End) Connector Style | Cable | | | Cat. No. ^{1,3} | |
|--|---|-------------------------------------|---------------------|-------------------------|------------------------------------|
| | Wire Color | | Assembly Rating | | Length [m (ft)] |
| 4-pin straight | 1 Brown 2 White | 3 Blue 4 Black | 22 AWG 250V, 4 A | 2 (6.56) | 889D-F4AC-2 |
| 4-pin right angle | | | | | 889D-R4AC-2 |
| 5-pin straight | 1 Brown 2 White | 3 Blue 4 Black 5 Grey | | | 889D-F5AC-2 |
| 8-pin straight | 1 White 2 Brown 3 Green 4 Yellow | 5 Grey 6 Pink 7 Blue 8 Red | | | 24 AWG, 30V AC/36V DC, 1.5 A |

Patchcords

| Female (Sensor End) Connector Style | Male (I/O End) Connector Style | Cable | | Cat. No. ¹ |
|--|-----------------------------------|---------------------|-----------------|----------------------------|
| | | Assembly Rating | Length [m (ft)] | |
| 4-pin straight | 4-pin straight | 22 AWG 250V, 4 A | 2 (6.56) | 889D-F4ACDM-2 |
| | 4-pin right angle | | | 889D-F4ACDE-2 |
| 4-pin right angle | 4-pin straight | | | 889D-R4ACDM-2 |
| | 4-pin right angle | | | 889D-R4ACDE-2 |
| 5-pin straight | 5-pin straight | | | 889D-F5ACDM-2 |
| 8-pin straight | 8-pin straight | | | 889D-F8ABDM-2 ² |

¹ Replace the **2** after the dash with **1, 5, or 10** for additional lengths in meters.

² The 8-pin cordset is for Safety devices. To order with a red PVC jacket, replace the **A** in the catalog number with an **N**. For example, 889D-F8**NB**-2 or 889D-F8**NBDM**-2.

³ To order with black PVC jacket, replace the **A** in the catalog number with a **B**. For example, 889D-F4**BC**-2.

Connection Systems

Terminal Blocks



4-2...4-23

Wiring Systems



4-24...4-25

Signal Interface



4-26...4-29



4-30...4-39

Safety Connection Systems



4-40...4-43

Network Media



4-44...4-51