

Product Selection

Model Type	Contacts		Actuator	M20 Conduit		Quick Disconnect
	Safety	Aux.		Standard	1/2in NPT Adaptor	End Entry
Standard	2 N.C.	—	Standard	440K-T11303	440K-T11267	440K-T11307
			Fully-Flex	440K-T11395	440K-T11273	440K-T11384
			—	440K-T11269	—	440K-T11385
	1 N.C.	1 N.O.	Standard	440K-T11305	440K-T11268	440K-T11386
			Fully-Flex	440K-T11396	440K-T11276	440K-T11387
			—	440K-T11270	—	440K-T11388
GD2 Front Entry	2 N.C.	—	Standard	440K-T11463	440K-T11288	440K-T11389
			Fully-Flex	440K-T11397	440K-T11287	440K-T11390
			—	440K-T11280	—	440K-T11391
	1 N.C.	1 N.O.	Standard	440K-T11398	440K-T11284	440K-T11392
			Fully-Flex	440K-T11399	440K-T11283	440K-T11393
			—	440K-T11279	—	440K-T11394
		Recommended mating cable, 2m (6.5ft). See page 15-10 for details and additional lengths.				889D-F4AC-2

Accessories

Description		For Dimensions See Page	Catalogue Number
	Standard Actuator (Standard model only)	14-5	440K-A11238
	GD2 Standard Actuator (GD2 model only)	14-4	440G-A27011
	Flat Actuator	14-5	440K-A11112