



Product Selection

Terminal Chambers



No. of Pins	Cable Diameter [mm (in.)]	Assembly Rating	Thread Size	Cat. No.		
				Straight Female Internal Threads	Straight Male Internal Threads	Straight Male External Threads
3-Pin	6.0...8.0 (0.23...0.31)	250V, 12 A	PG9	* 871A-TS3-N2	* 871A-TS3-NU2	* 871A-TS3-NM2
	10.0...12.0 (0.39...0.47)		PG13.5	871A-TS3-N1	871A-TS3-NU1	871A-TS3-NM1
4-Pin	6.0...8.0 (0.23...0.31)	250V, 9 A	PG9	* 871A-TS4-N1	* 871A-TS4-NU1	* 871A-TS4-NM1
	10.0...12.0 (0.39...0.47)		PG13.5	871A-TS4-N2	871A-TS4-NU2	871A-TS4-NM2
	12.0...14.0 (0.47...0.55)		PG16	871A-TS4-N3	871A-TS4-NU3	871A-TS4-NM3
5-Pin	6.0...8.0 (0.24...0.32)	250V, 9 A	PG9	* 871A-TS5-N1	* 871A-TS5-NU1	* 871A-TS5-NM1
	10.0...12.0 (0.39...0.47)		PG13.5	871A-TS5-N2	871A-TS5-NU2	871A-TS5-NM2
	12.0...14.0 (0.47...0.55)		PG16	871A-TS5-N3	871A-TS5-NU3	871A-TS5-NM3

* Available in right angle. Replace the S in the cat. no. with an R (i.e. 871A-TR3-N2)

Note:Stainless steel connector versions may be ordered by adding an S to the cat. no., e.g., 871AS-TS3-N2.