


	Lockable Twist Knob <ul style="list-style-type: none"> For one padlock 5 mm (3/16 in.) Ø shackle Can be locked in OFF position 	Black	140M-C, D, F; 140U-D	140M-C-KN1
		Red/Yellow		140M-C-KRY1
	Locking Tag <ul style="list-style-type: none"> Padlock attachment to the lockable handles Up to three padlocks 4...8 mm (5/16 in.) Ø shackle 		140M-C-KN1, 140M-C-KRY1	140M-C-M3
	Padlockable Operating Knob <ul style="list-style-type: none"> Accepts 8 mm (5/16 in.) Ø padlock shackle – up to three padlocks Permits padlocking in the off position 	Black	140-CMN	140-KN
		Red/Yellow		140-KRY
	Door Coupling Handle <ul style="list-style-type: none"> For 3 padlocks 4...8 mm (5/16 in.) in diameter IP66 Protection/Type 1, 4, 4X, 12 Interlock override capability 	Black	140M-C, D, F; 140U-D	140M-C-DN66
			140-CMN	140-CDN66
	<ul style="list-style-type: none"> Can be modified for locking in ON position Ships with coupling – order extension shaft and legend plate separately Mounting depth (front of DIN Rail to front of enclosure door): <ul style="list-style-type: none"> 140M-C: 105.5 mm ± 5 mm (4.15 in. ± 3/16 in.) 140M-D: 114.5 mm ± 5 mm (4.5 in. ± 3/16 in.) 140M-F: 137.1 mm ± 5 mm (5.4 in. ± 3/16 in.) 140-CMN: 169 mm +/- 5 mm (6.7 in. +/- 3/16 in.) 140U-D: 114.5mm +/- 5mm (4.5 in. +/- 3/16 in.) ser E or later handles only 	Red/Yellow	140M-C, D, F; 140U-D	140M-C-DRY66
			140-CMN	140-CDRY66
	Extension Shaft Cut to required length for mounting depth (front of DIN Rail to front of enclosure door): <ul style="list-style-type: none"> 140M-C: 117...338 mm (4.6...13.3 in.) 140M-D: 126...347 mm (5.0...13.7 in.) 140M-F: 149...369 mm (5.9...14.5 in.) 140-CMN: 180...403 mm (7.1...15.9 in.) 140U-D: 126...347 mm (5.0...13.7 in.) ser E or later handles only Extension Shaft (Extended Length) Cut to required length for mounting depth (front of DIN Rail to front of enclosure door): <ul style="list-style-type: none"> 140M-C: 117...488 mm (4.6...19.2 in.) 140M-D: 126...497 mm (5.0...19.6 in.) 140M-F: 149...519 mm (5.9...20.4 in.) 140-CMN: 180...553 mm (7.1...21.8 in.) 140U-D: 126...497 mm (5.0...19.6 in.) ser E or later handles only 		140M-C-DN66, 140M-C-DRY66, 140-CDN66, 140-CDRY66	140M-C-DS
	Door coupling handle Type 3, 3R, 4, 4X, 12 (IP66) For up to 2 padlocks Fits in 30.5 mm cutout Requires 140M-C-DNC coupler	Black	140M-C, -D, -F; 140U-D	140M-SB
	Door coupling handle Type 3, 3R, 4, 4X, 12 (IP66) For up to 2 padlocks Fits in 30.5 mm cutout Requires 140M-C-DNC coupler	Red/Yellow	140M-C, -D, -F; 140U-D	140M-SY
	Extension shaft - cut to required length 12 in. (30.48 cm)		140M-SB, 140M-SY	140M-S1
	Extension shaft - cut to required length 21 in. (53.34 cm)		140M-SB, 140M-SY	140M-S2
	Coupler Included with Cat. Nos. 140M-C-DN66 and 140M-C-DRY66		140M-C, D, F; 140U-D	140M-C-DNC
	Extension Shaft Support <ul style="list-style-type: none"> Provides consistent alignment of the 140M-C-DS and 140M-C-DSL shafts with the 140M-C-DN66 or 140M-C-DRY66 door coupling handles. It is recommended for shaft lengths >200 mm. Snaps on the right side of the 140M-C, -D, -F or 140U-D and allows for the addition of one side mounted auxiliary contact. Width 9 mm. For use with screw-mounted or hat rail mounted devices. 		140M-C, D, F; 140U-D	140M-C-SHS
	Legend Plate <ul style="list-style-type: none"> Marking: "Hauptschalter" and "Main Switch" Marking: "Not-Aus" and "Emergency Off" 		140-CDN66	140M-C-DFCN
			140-CDRY66	140M-C-DFCRY
	IP65 Non-Metallic Enclosure <ul style="list-style-type: none"> Knockouts for M20 and M25 fittings Suitable for flexible cable with internal ground wire or conduit when externally grounded around the outside of the enclosure (no UL/CSA approval) 	Black Handle	140M-C	198E-AYTG2
		Red/Yellow Handle	140M-C	198E-AYTJ2
	Screw Adapter <ul style="list-style-type: none"> For screw arrangement of a motor protection circuit breaker Must be ordered in multiples of 10 (10 pcs/pkg) 		140M-C, D, F; 140U-D	140M-C-N45