

## Operating Levers

### Operating Levers



For use with 802M, 802MC, 802R, 802T, 802X, and 802XR

### Roller Levers

| Type                                                                                                                                           | Roller Material                 | Roller Diameter [mm (in.)] | Roller Width [mm (in.)] | Cat. No.  |
|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------|-------------------------|-----------|
| <br>Non-Adj. Cast Lever<br>0.75 in. Radius                     | Metal                           | 19.05 (0.75)               | 6.86 (0.27)             | 802T-W9A  |
|                                                                                                                                                |                                 |                            |                         |           |
| <br>Non-Adj. Cast Lever<br>1.5 in. Radius<br>Roller on Front  | Nylon                           | 19 (0.75)                  | 7.11 (0.28)             | 802T-W1   |
|                                                                                                                                                |                                 | 19 (0.75)                  | 25.4 (1.0)              | 802T-W1H  |
|                                                                                                                                                | Dual nylon                      | 19.05 (0.75)               | 25.4 (1) each           | 802T-W1HH |
|                                                                                                                                                | Steel                           | 19 (0.75)                  | 6.35 (0.25)             | 802T-W1A  |
|                                                                                                                                                |                                 | 19.05 (0.75)               | 19.05 (0.75)            | 802T-W1N  |
| <br>Non-Adj. Cast Lever<br>1.5 in. Radius<br>Roller on Front | Ball bearing                    | 19 (0.75)                  | 5.84 (0.23)             | 802T-W1B  |
|                                                                                                                                                | Beryllium copper (non-sparking) | 19.05 (0.75)               | 7.11 (0.28)             | 802T-W1J  |
|                                                                                                                                                | Nylon                           | 19.05 (0.75)               | 19.05 (0.75)            | 802T-W1L  |
| <br>Non-Adj. Cast Lever<br>1.5 in. Radius<br>Roller on Rear  | Nylon                           | 19.05 (0.75)               | 7.11 (0.28)             | 802T-W1E  |
|                                                                                                                                                |                                 |                            | 25.4 (1)                | 802T-W1D  |
|                                                                                                                                                |                                 | 38.1 (1.5)                 | 7.11 (0.28)             | 802T-W1G  |
| <br>Non-Adj. Cast Lever<br>1.5 in. Radius<br>Roller on Rear  | Steel                           | 19.05 (0.75)               | 6.35 (0.25)             | 802T-W1F  |
|                                                                                                                                                |                                 |                            | 19.05 (0.75)            | 802T-W1C  |
|                                                                                                                                                | Nylon                           | 19.05 (0.75)               | 19.05 (0.75)            | 802T-W1M  |
|                                                                                                                                                | Nylon                           | 19.05 (0.75)               | 7.11 (0.28)             | 802T-W20  |