




	1492-WFB4			1492-WFB424			1492-WFB4250		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single-circuit fuse block.			Single-circuit fuse block with LED blown fuse indicator.			Single-circuit fuse block with neon blown fuse indicator.		
Approvals		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	15 A	15 A	15 A ❶	15 A	15 A	15 A ❶	15 A	15 A	15 A ❶
Wire Range (Rated Cross Section)	#22... #12 AWG	#22... #12 AWG	0.5... 4 mm ²	#22... #12 AWG	#22... #12 AWG	0.5... 4 mm ²	#22... #12 AWG	#22... #12 AWG	0.5... 4 mm ²
Indicator Type	Non-Indicating			LED			Neon		
Leakage Current	—			2mA @ 24V			1mA @ 264V		
Working Voltage	Per Fuse Rating			10-57V AC/DC			85-264V AC		
Fuse Size (Not Supplied)	5 x 20 mm			5 x 20 mm			5 x 20 mm		
Wire Strip Length	0.31" (8 mm)			0.31" (8 mm)			0.31" (8 mm)		
Recommended Tightening Torque	5.0...5.6 lb-in. (0.6 Nm)			5.0...5.6 lb-in. (0.6 Nm)			5.0...5.6 lb-in. (0.6 Nm)		
Density	38 pcs./ft (125/m)			38 pcs./ft (125/m)			38 pcs./ft (125/m)		
Insulation Temperature Range	-40...+195°F (-40...+90°C)			-40...+195°F (-40...+90°C)			-40...+195°F (-40...+90°C)		
Terminal Blocks	Cat. No.	Pcs./ Pkg.		Cat. No.	Pcs./ Pkg.		Cat. No.	Pcs./ Pkg.	
Terminal Block	1492-WFB4	50		1492-WFB424	50		1492-WFB4250	50	
Accessories (page 185)	Cat. No.	Pcs./ Pkg.		Cat. No.	Pcs./ Pkg.		Cat. No.	Pcs./ Pkg.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	5		199-DR1	5		199-DR1	5	
1 m Symmetrical DIN (Aluminum)	1492-DR5	5		1492-DR5	5		1492-DR5	5	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier	Not Required	—		Not Required	—		Not Required	—	
End Anchors:									
DIN Rail — Normal Duty	1492-EA35	50		1492-EA35	50		1492-EA35	50	
DIN Rail — Heavy Duty	1492-EAH35	10		1492-EAH35	10		1492-EAH35	10	
Jumpers:									
Side Jumper — 10-pole Insulated	1492-SJFB8-10	10		1492-SJFB8-10	10		1492-SJFB8-10	10	
Other Accessories:									
Partition Plate	1492-PPSL3	50		1492-PPSL3	50		1492-PPSL3	50	
Group Marking Carrier	1492-GM35	10		1492-GM35	10		1492-GM35	10	
Marking Systems:									
Snap-in Marker Card — For Base Block	1492-SM8X12	5		1492-SM8X12	5		1492-SM8X12	5	
For Handle	1492-SM6X9	5		1492-SM6X9	5		1492-SM6X9	5	
Individual Marker Tabs (single char.)	1492-MP ❷	10		1492-MP ❷	10		1492-MP ❷	10	

❶ IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.