

Screw Connection Terminal Blocks

Standard Feed-Through Blocks

1492-J3												
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
	2.36\" (60 mm)											
1492-J4												
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
	2.36\" (60 mm)											
1492-J6												
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
	2.36\" (60 mm)											
Specifications	Feed-through terminal block											
Certifications	UL	CSA	IEC	ATEX	UL	CSA	IEC	ATEX	UL	CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	690V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	25 A	20 A	24 A	21 A	35 A	25 A	32 A	28 A	50 A	41 A	36 A	
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm²	2.5 mm² (#20...14 AWG)	#22...10 AWG	#26...10 AWG	4 mm²	4 mm² (#20...12 AWG)	#22...8 AWG	6 mm²	6 mm² (#20...10 AWG)	
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)				9.0 lb•in (1.0 N•m)				14.2 lb•in (1.6 N•m)			
Density	59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				37 pcs/ft (123 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color:	Grey	1492-J3	100		1492-J4	100		1492-J6	100		100	
	Red	1492-J3-RE	100		1492-J4-RE	100		1492-J6-RE	100		100	
	Blue	1492-J3-B	100		1492-J4-B	100		1492-J6-B	100		100	
	Black	1492-J3-BL	100		1492-J4-BL	100		1492-J6-BL	100		100	
	Green	1492-J3-G	100		1492-J4-G	100		1492-J6-G	100		100	
	Yellow	1492-J3-Y	100		1492-J4-Y	100		1492-J6-Y	100		100	
	Orange	1492-J3-OR	100		1492-J4-OR	100		1492-J6-OR	100		100	
	Brown	1492-J3-BR	100		1492-J4-BR	100		1492-J6-BR	100		100	
	White	1492-J3-W	100		1492-J4-W	100		1492-J6-W	100		100	
	Violet	1492-J3-V	100		1492-J4-V	100		—	—		—	
Mounting Rails:	199-DR1		10		199-DR1	10		199-DR1	10		10	
1 m Symmetrical DIN (Steel)	1492-DR5		10		1492-DR5	10		1492-DR5	10		10	
1 m Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6	2		1492-DR6	2		2	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR7		2		1492-DR7	2		1492-DR7	2		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7	2		1492-DR7	2		2	
End Barriers	Grey	1492-EBJ3	50		1492-EBJ3	50		1492-EBJ3	50		50	
	Blue	1492-EBJ3-B	50		1492-EBJ3-B	50		1492-EBJ3-B	50		50	
	Yellow	1492-EBJ3-Y	50		1492-EBJ3-Y	50		1492-EBJ3-Y	50		50	
End Anchors and Retainers:	1492-EAJ35		100		1492-EAJ35	100		1492-EAJ35	100		100	
DIN Rail — Normal Duty	1492-EAHJ35		50		1492-EAHJ35	50		1492-EAHJ35	50		50	
DIN Rail — Heavy Duty	1492-ERL35		20		1492-ERL35	20		1492-ERL35	20		20	
Screwless End Retainer	1492-ERL35		20		1492-ERL35	20		1492-ERL35	20		20	
Jumpers:*	1492-CJJ5-10		20		1492-CJJ6-10	20		1492-CJJ8-10	20		20	
Screw Center Jumper — 10-pole	1492-CJJ5-4		50		1492-CJJ6-4	50		1492-CJJ8-4	50		50	
Screw Center Jumper — 4-pole	1492-CJJ5-3		50		1492-CJJ6-3	50		1492-CJJ8-3	50		50	
Screw Center Jumper — 3-pole	1492-CJJ5-2		50		1492-CJJ6-2	50		1492-CJJ8-2	50		50	
Screw Center Jumper — 2-pole	1492-CJJ5-2		50		1492-CJJ6-2	50		1492-CJJ8-2	50		50	
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-50		10		1492-CJLJ6-41 (41-pole)	10		—	—		—	
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-10		20		1492-CJLJ6-10	20		—	—		—	
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-9		20		—	—		—	—		—	
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-8		20		—	—		—	—		—	
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-7		20		—	—		—	—		—	
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-6		20		—	—		—	—		—	
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-5		20		—	—		—	—		—	
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-4		60		1492-CJLJ6-4	60		—	—		—	
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-3		60		1492-CJLJ6-3	60		—	—		—	
Plug-in Center Jumper — 2-Pole	1492-CJLJ5-2		60		1492-CJLJ6-2	60		—	—		—	
Insulated Side Jumper — 24-Pole	1492-SJ5B-24		50		—	—		—	—		—	
Insulated Side Jumper — 10-Pole	1492-SJ5B-10		50		—	—		—	—		—	
Screw Type Jumper Notching Tool	1492-T1		1		1492-T1	1		1492-T1	1		1	
Other Accessories:	1492-EBJ16		20		1492-EBJ16	20		1492-EBJ16	20		20	
Partition Plate	1492-TPS23		20		1492-TPS23L	50		1492-TPS23L	50		50	
Test Plug Socket	1492-TP23		20		1492-TP23	20		1492-TP23	20		20	
Test Plug	1492-TPJ5		25		1492-TPJ6	25		—	—		—	
Test Plug (Stackable)	1492-TPJ5		25		1492-TPJ6	25		—	—		—	
Electrical Warning Plate	1492-EWPJ5		25		1492-EWPJ5	25		1492-EWPJ8	50		50	
Marking Systems:	1492-M5X12 (144/card)		5		1492-M6X12 (120/card)	5		1492-MR8X12 (84/card)	5		5	
Snap-in Marker Cards	1492-M5X5 (200/card)		5		1492-M6X5 (200/card)	5		1492-M8X5 (160/card)	5		5	

* Use of center jumpers may affect spacings, requiring derating of terminal blocks. See page 12-83 for details.

Screw Connection Terminal Blocks

Standard Feed-Through Blocks




1492-J10

1492-J16

1492-J35

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Feed-through terminal block				Feed-through terminal block				Feed-through terminal block			
Certifications												
Voltage Rating	600V AC/DC		1000V AC/DC	550V AC/DC	600V AC/DC		1000V AC/DC	690V AC/DC	1000V AC/DC	600V AC/DC	1000V AC/DC	690V AC/DC
Maximum Current	65 A	50 A	57 A	50 A	85 A		76 A	66 A	150 A	120 A	125 A	109 A
Wire Range (Rated Cross Section)	#18...6 AWG		10 mm ²	10 mm ² (#16...8 AWG)	#18...4 AWG		16 mm ²	16 mm ² (#16...6 AWG)	#12...1/0 AWG	#12...2 AWG	35 mm ²	35 mm ² (#14...2 AWG)
Wire Strip Length	0.47 in. (12 mm)				0.63 in. (16 mm)				0.70 in. (18 mm)			
Recommended Tightening Torque	20.4 lb•in (2.3 N•m)				35.0 lb•in (4.0 N•m)				51.0 lb•in (5.8 N•m)			
Density	30 pcs/ft (100 pcs/m)				25 pcs/ft (83 pcs/m)				19 pcs/ft (62 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											

Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color:						
Grey	1492-J10	50	1492-J16	50	1492-J35	40
Red	1492-J10-RE	50	1492-J16-RE	50	—	—
Blue	1492-J10-B	50	1492-J16-B	50	1492-J35-B	40
Black	1492-J10-BL	50	1492-J16-BL	50	—	—
Green	1492-J10-G	50	1492-J16-G	50	—	—
Yellow	1492-J10-Y	50	1492-J16-Y	50	1492-J35-Y	40
Orange	1492-J10-OR	50	1492-J16-OR	50	—	—
Brown	1492-J10-BR	50	1492-J16-BR	50	—	—
White	1492-J10-W	50	1492-J16-W	50	—	—
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails:						
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10
1 m Symmetrical Heavy Duty DIN (Steel, unslotted)	199-DR4	5	199-DR4	5	199-DR4	5
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2
1 m Symmetrical Heavy Duty DIN (Copper, unslotted)	1492-DR8	5	1492-DR8	5	1492-DR8	5
1 m Symmetrical Heavy Duty DIN (Steel)	1492-DR9	5	1492-DR9	5	1492-DR9	5
End Barriers						
Grey	1492-EBJ3	50	1492-EBJ16	20	1492-EBJ16	20
Blue	1492-EBJ3-B	50	1492-EBJ16-B	20	1492-EBJ16-B	20
Yellow	1492-EBJ3-Y	50	1492-EBJ16-Y	20	1492-EBJ16-Y	20
End Anchors and Retainers:						
DIN Rail — Normal Duty	1492-EAJ35	100	—	—	—	—
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50
Screwless End Retainer	1492-ERL35	20	—	—	—	—
Jumpers:						
Screw Center Jumper — 10-pole	1492-CJJ10-10	20	1492-CJJ12-10	10	1492-CJJ16-10	10
Screw Center Jumper — 4-pole	1492-CJJ10-4	50	1492-CJJ12-4	20	1492-CJJ16-4	20
Screw Center Jumper — 3-pole	1492-CJJ10-3	50	1492-CJJ12-3	20	1492-CJJ16-3	20
Screw Center Jumper — 2-pole	1492-CJJ10-2	50	1492-CJJ12-2	20	1492-CJJ16-2	20
Screw Type Jumper Notching Tool	1492-T1	1	1492-T1	1	1492-T1	1
Other Accessories:						
Partition Plate	1492-EBJ16	20	1492-PPJD3	20	1492-PPJD3	20
Test Plug Socket	1492-TPS23L	50	1492-TPS4L	50	1492-TPS4L	50
Test Plug	1492-TP23	20	1492-TP40	20	1492-TP40	20
Electrical Warning Plate	1492-EWPJ8	50	1492-EWPJ12	50	1492-EWPJ12	50
Marking Systems:						
Snap-in marker cards	1492-M7X12 (108/card)	5	1492-M7X12 (108/card)	5	1492-M7X12 (108/card)	5
Snap-in marker cards	1492-M5X5 (200/card)	5	1492-M5X5 (200 card)	5	1492-M5X5 (200/card)	5

Screw Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-J50				1492-J70				1492-J120			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block				Feed-through terminal block			
Certifications	CSA IEC ATEX				CSA IEC ATEX				CSA IEC			
Voltage Rating	1000V AC/DC 600V AC/DC 1000V AC/DC 690V AC/DC				600V AC/DC 1000V AC/DC 690V AC/DC				1000V AC/DC			
Maximum Current	150 A				175 A 205 A 192 A 167 A				228 A 220 A 269 A			
Wire Range (Rated Cross Section)	#10... 1/0 AWG	#8... 1/0 AWG	50 mm ²	#10... 1/0 AWG 50 mm ²	#6...2/0 AWG 70 mm ²				#4... 250 MCM AWG	#4... 4/0 AWG	16... 120 mm ²	
Wire Strip Length	0.94 in. (24 mm)				0.87 in. (22 mm)				1.06 in. (27 mm)			
Recommended Tightening Torque	31.5 lb•in (3.6 N•m)				87.0 lb•in (9.8 N•m)				141.6 lb•in (16.0 N•m)			
Density	16 pcs/ft (54 pcs/m)				14 pcs/ft (48 pcs/m)				11 pcs/ft (37 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.
Color:	Grey	1492-J50		10		1492-J70		10		1492-J120		5
	Blue	1492-J50-B		10		1492-J120-B		5		1492-J120-B		5
Accessories		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)		199-DR1		10		199-DR1		10		—		—
1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)		199-DR4		5		199-DR4		5		199-DR4		5
1 m Symmetrical DIN (Aluminum)		1492-DR5		10		1492-DR5		10		—		—
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2		1492-DR6		2		—		—
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2		1492-DR7		2		—		—
1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)		1492-DR8		5		1492-DR8		5		1492-DR8		5
1 m Symmetrical Heavy Duty DIN (Steel)		1492-DR9		5		1492-DR9		5		1492-DR9		5
End Barriers		Not Required		—		Not Required		—		Not Required		—
End Anchors: DIN Rail — Heavy Duty		1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50
Jumpers:												
Screw Center Jumper — 4-pole		1492-CJJ18-4		10		1492-CJJ20-4		5		1492-CJJ27-4		5
Screw Center Jumper — 3-pole		1492-CJJ18-3		10		1492-CJJ20-3		5		1492-CJJ27-3		5
Screw Center Jumper — 2-pole		1492-CJJ18-2		10		1492-CJJ20-2		5		1492-CJJ27-2		5
Other Accessories:												
Control Circuit Tap*		1492-J50A		5		1492-J70A		5		1492-J120A		5
Electrical Warning Plate		1492-EWPJ18		50		1492-EWPJ18		50		—		—
Marking Systems:												
Snap-in marker cards		1492-M7X12 (108/card)		5		1492-M7X12 (108/card)		5		1492-MR8X12 (84/card)		5
Snap-in marker cards		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M7X12 (108/card)		5

* Auxiliary connection, allowing a single additional #26...8 AWG wire connection.

Screw Connection Terminal Blocks

Space-Saver Feed-Through Blocks




1492-W3

1492-W4

1492-W6

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Single-circuit terminal block.				Single-circuit terminal block.				Single-circuit terminal block.			
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX		IEC	CSA	ATEX
Voltage Rating	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC
Maximum Current	20 A	24 A	20 A	24 A	30 A	32 A	30 A	32 A	40 A	41 A	40 A	41 A
Wire Range (Rated Cross Section)	#30...14 AWG	0.5...2.5 mm ²	#22...14 AWG	2.5 mm ²	#22...10 AWG	0.5...4.0 mm ²	#22...10 AWG	4.0 mm ²	#22...10 AWG	0.5...6.0 mm ²	#22...10 AWG	6.0 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.35 in. (9 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	5.0...5.6 lb•in (0.6 N•m)				5.0...5.6 lb•in (0.6 N•m)				5.6...6.8 lb•in (0.7 N•m)			
Density	61 pcs/ft (200 pcs/m)				50 pcs/ft (166 pcs/m)				43 pcs/ft (142 pcs/m)			
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color:	Grey	1492-W3	50		1492-W4	50			1492-W6	50		
	Red	1492-W3-RE	50		1492-W4-RE	50			1492-W6-RE	50		
	Blue	1492-W3-B	50		1492-W4-B	50			1492-W6-B	50		
	Black	1492-W3-BL	50		1492-W4-BL	50			1492-W6-BL	50		
	Green	1492-W3-G	50		1492-W4-G	50			1492-W6-G	50		
	Yellow	1492-W3-Y	50		1492-W4-Y	50			1492-W6-Y	50		
	Orange	1492-W3-OR	50		1492-W4-OR	50			1492-W6-OR	50		
	Brown	1492-W3-BR	50		1492-W4-BR	50			1492-W6-BR	50		
	White	1492-W3-W	50		1492-W4-W	50			1492-W6-W	50		
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barrier	1492-EB3		50		1492-EB3		50		1492-EB10		50	
End Anchors and Retainers:												
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Jumpers:												
Insulated Side Jumper	1492-SJ5-10 (10-pole)		10		1492-N42 (2-pole)	50			—		—	
					1492-SJ6-10 (10-pole)	10						
Center Jumper — 50-pole	1492-CJ5-50		5		1492-CJ6-50		5		—		—	
Center Jumper — 40-pole	—		—		—		—		1492-CJ7-40		5	
Center Jumper — 10-pole	1492-CJ5-10		10		1492-CJ6-10		10		1492-CJ7-10		10	
Center Jumper — 5-pole	1492-CJ5-5		10		1492-CJ6-5		10		1492-CJ7-5		10	
Center Jumper — 4-pole	1492-CJ5-4		10		1492-CJ6-4		10		1492-CJ7-4		10	
Center Jumper — 3-pole	1492-CJ5-3		10		1492-CJ6-3		10		1492-CJ7-3		10	
Center Jumper — 2-pole	1492-CJ5-2		10		1492-CJ6-2		10		1492-CJ7-2		10	
Center Jumper Link	1492-CJL5		10		1492-CJL6		10		1492-CJL7		10	
Center Jumper Cover — White*	1492-CJCW5		20		1492-CJCW6		20		1492-CJCW6		20	
Other Accessories:												
Partition Plate	1492-PP3		50		1492-PP3		50		1492-PP10		50	
Separation Plate	1492-SP3		50		1492-SP3		50		—		—	
Test Plug	—		—		1492-TP28		10		1492-TP28		10	
Stackable Test Plug (with Legs)	—		—		1492-TP6EWL		10		—		—	
Stackable Test Plug (without Legs)	—		—		1492-TP6E		10		—		—	
Test Plug Adapter	1492-TA285		10		1492-TA40		10		1492-TA40		10	
Electrical Warning Plate (1-pole)	1492-EWP5		10		1492-EWP6		10		1492-EWP7		10	
Electrical Warning Plate (4-pole)	1492-EWP5-4		10		1492-EWP6-4		10		1492-EWP7-4		10	
Marking Systems:												
Snap-in Marker Cards	1492-MS5X12 (80/card)		5		1492-MS6X12 (80/card)		5		1492-MS6X12 (80/card)		5	

* May only be used as a marking surface. Cannot be installed over a center jumper.

Screw Connection Terminal Blocks



Space-Saver Feed-Through Blocks

1492-W10

1492-W16S

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications					Specifications				
Single-circuit terminal block.					Single-circuit terminal block.				
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX	
Voltage Rating	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC	
Maximum Current	50 A	57 A	50 A	50 A	85 A	76 A	85 A	76 A	
Wire Range (Rated Cross Section)	#22...8 AWG	10 mm ²	#22...8 AWG	0.5...10 mm ²	#14...4 AWG	16 mm ²	#14...4 AWG	2.5...16 mm ²	
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				
Recommended Tightening Torque	12.2...13.4 lb•in (1.4 N•m)				18...20 lb•in (2.1 N•m)				
Density	38 pcs/ft (125 pcs/m)				27 pcs/ft (90 pcs/m)				
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				
Terminal Blocks		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.		
Color:	Grey	1492-W10		50	1492-W16S		50		
	Red	1492-W10-RE		50	1492-W16S-RE		50		
	Blue	1492-W10-B		50	1492-W16S-B		50		
	Black	1492-W10-BL		50	1492-W16S-BL		50		
	Green	1492-W10-G		50	1492-W16S-G		50		
	Yellow	1492-W10-Y		50	1492-W16S-Y		50		
	Orange	1492-W10-OR		50	1492-W16S-OR		50		
	Brown	1492-W10-BR		50	1492-W16S-BR		50		
	White	1492-W10-W		50	1492-W16S-W		50		
Accessories		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.		
Mounting Rails:									
1 m Symmetrical DIN (Steel)		199-DR1		10	199-DR1		10		
1 m Symmetrical DIN (Aluminum)		1492-DR5		10	1492-DR5		10		
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2	1492-DR6		2		
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2	1492-DR7		2		
End Barrier		1492-EB10		50	1492-EB10		50		
End Anchors:									
DIN Rail — Normal Duty		1492-EAJ35		100	1492-EAJ35		100		
DIN Rail — Heavy Duty		1492-EAHJ35		50	1492-EAHJ35		50		
Jumpers:									
Side Jumper — 10-pole insulated		1492-SJ8-10		10	—		—		
Center Jumper — 40-pole		1492-CJ8-40		5	—		—		
Center Jumper — 10-pole		1492-CJ8-10		10	1492-CJS11-10		10		
Center Jumper — 5-pole		1492-CJ8-5		10	1492-CJS11-5		10		
Center Jumper — 4-pole		1492-CJ8-4		10	1492-CJS11-4		10		
Center Jumper — 3-pole		1492-CJ8-3		10	1492-CJS11-3		10		
Center Jumper — 2-pole		1492-CJ8-2		10	1492-CJS11-2		10		
Center Jumper Link		1492-CJL8		10	—		—		
Center Jumper Cover — White		1492-CJCW6		20	—		—		
Other Accessories:									
Partition Plate		1492-PP10		50	1492-PP10		50		
Test Plug		1492-TP28		10	—		—		
Test Plug Adapter		1492-TA40		10	1492-TA40L		10		
Electrical Warning Plate (1-pole)		1492-EWP8		10	1492-EWP11		10		
Electrical Warning Plate (4-pole)		1492-EWP8-4		10	1492-EWP11-4		10		
Marking Systems:									
Snap-in Marker Card		1492-MS8X12 (56/card)		5	1492-MS6X12 (80/card)		5		

Screw Connection Terminal Blocks

Multi-Circuit Feed-Through Blocks




1492-JD3

1492-JD4

1492-JT3M

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.






Specifications		Two-level, two-circuit feed-through terminal block				Two-level, two-circuit feed-through terminal block				Three-level, three-circuit terminal block with ground point		
Certifications			CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC
Voltage Rating		600V AC/DC	300V AC/DC	400V AC/DC	275V AC/DC	600V AC/DC	300V AC/DC	800V AC/DC	550V AC/DC	300V AC/DC		400V AC/DC
Maximum Current		20 A	10 A	24 A	21 A	35 A	30 A	32 A	28 A	10 A		24 A
Wire Range (Rated Cross Section)		#22...12 AWG	26...12 AWG	2.5 mm²	2.5 mm² (20...14 AWG)	#26...10 AWG		0.5...4 mm²	4 mm² (20...12 AWG)	#22...12 AWG	#26...10 AWG	0.5...2.5 mm²
Wire Strip Length		0.39 in. (10 mm)				0.315 in. (8 mm)				0.28 in. (7 mm)		
Recommended Tightening Torque		4.5...7.1 lb•in (0.5...0.8 N•m)				4.5 lb•in (0.5 N•m)				4.4 lb•in (0.5 N•m)		
Density		59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating		See page 12-42										
Terminal Blocks		Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Color:	Grey	1492-JD3			100	1492-JD4			100	1492-JT3M		50
	Red	1492-JD3-RE			100	1492-JD4-RE			100	—		—
	Blue	1492-JD3-B			100	1492-JD4-B			100	—		—
	Black	1492-JD3-BL			100	1492-JD4-BL			100	—		—
	Green	1492-JD3-G			100	1492-JD4-G			100	—		—
	Yellow	1492-JD3-Y			100	1492-JD4-Y			100	—		—
	Orange	1492-JD3-OR			100	1492-JD4-OR			100	—		—
	Brown	1492-JD3-BR			100	1492-JD4-BR			100	—		—
	White	1492-JD3-W			100	1492-JD4-W			100	—		—
Accessories		Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)		199-DR1			10	199-DR1			10	199-DR1		10
1 m Symmetrical DIN (Aluminum)		1492-DR5			10	1492-DR5			10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6			2	1492-DR6			2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7			2	1492-DR7			2	1492-DR7		2
End Barrier	Grey	1492-EBJD3			20	1492-EBJD4			20	1492-EBJ3TM		20
	Blue	1492-EBJD3-B			20	1492-EBJD4-B			20	—		—
	Yellow	1492-EBJD3-Y			20	—			—	—		—
End Anchor and Retainers:												
Screwless End Retainer		1492-ERL35			20	—			—	—		—
DIN Rail — Normal Duty		1492-EAJ35			100	—			—	—		—
DIN Rail — Heavy Duty		1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35		50
Jumpers:												
Center Jumper — 41-pole		—			—	‡	1492-CJLJ6-41		10	—		—
Center Jumper — 10-pole		⌘	1492-CJJ5-10		20	‡	1492-CJLJ6-10		20	—		—
Center Jumper — 4-pole		⌘	1492-CJJ5-4		50	‡	1492-CJLJ6-4		60	—		—
Center Jumper — 3-pole		⌘	1492-CJJ5-3		50	‡	1492-CJLJ6-3		60	—		—
Center Jumper — 2-pole		⌘	1492-CJJ5-2		50	‡	1492-CJLJ6-2		60	—		—
Insulated Side Jumper — 50-Pole		—			—	—			—	1492-SJ6A-50		5
Insulated Side Jumper — 24-Pole		1492-SJ5A-24			50	—			—	—		—
Insulated Side Jumper — 10-Pole		1492-SJ5A-10			50	—			—	—		—
Screw Type Jumper Notching Tool		1492-T1			1	—			—	—		—
Other Accessories:												
Partition Plate		1492-PPJD3			20	1492-PPJD3			20	1492-PPJD3		20
Test Plug Socket		1492-TPS23			20	—			—	—		—
Test Plug		1492-TP23			20	—			—	—		—
Snap-in marker cards		1492-M5X5 (200/card)			5	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)		5
Snap-in marker cards		1492-M5X8 (144/card)			5	1492-MR6X8 (120/card)			5	1492-MR6X8 (120/card)		5

⌘ Screw Center Jumpers, ‡ Plug-in Center Jumpers

Screw Connection Terminal Blocks




Specialty Feed-Through Blocks

1492-J2Q				1492-J3TW				1492-J4TW													
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.																					
Specifications				Feed-through terminal block with 2 connection points on each side				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 3 connection points, 2 on one side									
Certifications				UL [®] CSA		IEC		UL [®] CSA		IEC		ATEX		UL [®] CSA		IEC					
Voltage Rating				300V AC/DC		800V AC/DC		300V AC/DC		800V AC/DC		550V AC/DC		600V AC/DC		500V AC/DC					
Maximum Current				25 A		10 A		17.5 A		—				30 A				32 A			
Maximum Current				Single Side		—		10 A		15 A		17.5 A		15 A		—		—			
Current				Twin Side		—		20 A		24 A		21 A		—		—					
Wire Range (Rated Cross Section)				Single Side		#22...12 AWG		#26...12 AWG		1.5 mm ²		#22...12 AWG		26...12 AWG		2.5 mm ² (#20...14 AWG)		#30...10 AWG		4 mm ²	
Twin Side				—		#22...14 AWG		26...14 AWG		1.5 mm ²		1.5 mm ² (#20...16 AWG)									
Wire Strip Length				0.28 in. (7 mm)		Single Side: 0.39 in. (10 mm)				Twin Side: 0.26 in. (7 mm)				0.39 in. (10 mm)							
Recommended Tightening Torque				4.5 lb•in (0.5 N•m)		Single Side: 7.0 lb•in (0.8 N•m)				Twin Side: 4.5 lb•in (0.5 N•m)				6.2 lb•in (0.7 N•m)							
Density				59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)							
Housing Temperature Range				-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)							
Short-Circuit Current Rating				See page 12-42																	
Terminal Blocks				Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.							
Color:				Grey		1492-J2Q		100		1492-J3TW		100		1492-J4TW		50					
				Red		1492-J2Q-RE		100		1492-J3TW-RE		100		—		—					
				Blue		1492-J2Q-B		100		1492-J3TW-B		100		—		—					
				Black		1492-J2Q-BL		100		1492-J3TW-BL		100		—		—					
				Green		1492-J2Q-G		100		1492-J3TW-G		100		—		—					
				Yellow		1492-J2Q-Y		100		1492-J3TW-Y		100		—		—					
				Orange		1492-J2Q-OR		100		1492-J3TW-OR		100		—		—					
				Brown		1492-J2Q-BR		100		1492-J3TW-BR		100		—		—					
				White		1492-J2Q-W		100		1492-J3TW-W		100		—		—					
Accessories				Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.							
Mounting Rails:				199-DR1		10		199-DR1		10		199-DR1		10							
1 m Symmetrical DIN (Steel)				1492-DR5		10		1492-DR5		10		1492-DR5		10							
1 m Symmetrical DIN (Aluminum)				1492-DR6		2		1492-DR6		2		1492-DR6		2							
1 m Hi-Rise Sym. DIN (Aluminum)				1492-DR7		2		1492-DR7		2		1492-DR7		2							
1 m Angled Hi-Rise Sym. DIN (Steel)				1492-EBJ3		50		1492-EBJ3		50		1492-EBJ4TW		50							
End Barriers				Grey		1492-EBJ3-B		50		1492-EBJ3-B		50		—		—					
				Blue		1492-EBJ3-Y		50		1492-EBJ3-Y		50		1492-EBJ4TW-Y		50					
				Yellow		1492-ERL35		20		1492-ERL35		20		1492-ERL35		20					
End Anchors and Retainers:				1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100							
Screwless End Retainer				1492-EAH35		10		1492-EAH35		10		1492-EAH35		10							
DIN Rail — Normal Duty				1492-CJJ5-10		20		1492-CJJ5-10		20		—		—							
DIN Rail — Heavy Duty				1492-CJJ5-4		50		1492-CJJ5-4		50		—		—							
Jumpers:				1492-CJJ5-3		50		1492-CJJ5-3		50		—		—							
Screw Center Jumper — 10-pole				1492-CJJ5-2		50		1492-CJJ5-2		50		—		—							
Screw Center Jumper — 4-pole				—		—		1492-CJLJ5-50		10		1492-CJLJ6-41		10							
Screw Center Jumper — 3-pole				—		—		1492-CJLJ5-5, -6, -7, -8, -9, -10		20		1492-CJLJ6-10		20							
Screw Center Jumper — 2-pole				—		—		1492-CJLJ5-2, -3, -4		60		1492-CJLJ6-2, -3, -4		60							
Plug-in Center Jumper — 50-Pole (1492-J3TW)/ 41-Pole (1492-J4TW)				1492-SJ5B-24		50		1492-SJ5B-24		50		—		—							
Plug-in Center Jumper — 5-, 6-, 7-, 8-, 9-, 10-Pole				1492-SJ5B-10		50		1492-SJ5B-10		50		—		—							
Plug-in Center Jumper — 2-, 3-, 4-Pole				1492-T1		1		1492-T1		1		—		—							
Insulated Side Jumper — 24-Pole				1492-EBJ16		20		1492-EBJ16		20		—		—							
Insulated Side Jumper — 10-Pole				1492-TPS23L		50		1492-TPS23L		50		1492-TPS23L		50							
Screw Type Jumper Notching Tool				1492-TP23		20		1492-TP23		20		1492-TP23		20							
Other Accessories:				1492-TPJ5		25		1492-TPJ5		25		—		—							
Partition Plate				1492-M5X12 (144/card)		5		1492-M5X12 (144/card)		5		1492-MR6X12 (120/card)		5							
Test Plug Socket				1492-M6X12 (200/card)		5		1492-M6X12 (200/card)		5		1492-M6X12 (120/card)		5							
Test Plug																					
Test Plug (Stackable)																					
Marking Systems:																					
Snap-in marker card																					

* Use of center jumpers may affect spacings, requiring derating of terminal blocks.

Screw Connection Terminal Blocks

Specialty Feed-Through Blocks

	1492-J4Q				1492-JD3C				1492-JD4C			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Single-level feed-through terminal block with 2 connection points on each side				Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar			
Certifications		CSA	IEC			CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC			500V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	275V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	550V AC/DC
Maximum Current	30 A			32 A	20 A	10 A	24 A	21 A	35 A	30 A	32 A	28 A
Wire Range (Rated Cross Section)	#30...10 AWG			0.5...4 mm ²	#22...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (20...14 AWG)	#26...10 AWG		0.5...4 mm ²	4 mm ² (20...12 AWG)
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.28 in. (7 mm)			
Recommended Tightening Torque	6.2 lb•in (0.7 N•m)				4.5...7.1 lb•in (0.5...0.8 N•m)				4.5 lb•in (0.5 N•m)			
Density	49 pcs/ft (163 pcs/m)				59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating (SCCR)	See page 12-42											
Terminal Blocks		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.
Color: Grey		1492-J4Q		50		1492-JD3C		100		1492-JD4C		100
Accessories		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)		199-DR1		10		199-DR1		10		199-DR1		10
1 m Symmetrical DIN (Aluminum)		1492-DR5		10		1492-DR5		10		1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2		1492-DR6		2		1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2		1492-DR7		2		1492-DR7		2
End Barriers												
Grey		1492-EBJ4Q		50		1492-EBJD3		20		1492-EBJD4		20
Blue		—		—		1492-EBJD3-B		20		—		—
Yellow		1492-EBJ4Q-Y		50		1492-EBJD3-Y		20		—		—
End Anchors and Retainers:												
Screwless End Retainer		1492-ERL35		20		1492-ERL35		20		—		—
DIN Rail — Normal Duty		1492-EAJ35		100		1492-EAJ35		100		—		—
DIN Rail — Heavy Duty		1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50
Jumpers:*												
Screw Center Jumper — 41-pole		—		—		—		—		—		—
Screw Center Jumper — 10-pole		—		—		1492-CJJ5-10		20		—		—
Screw Center Jumper — 4-pole		—		—		1492-CJJ5-4		50		—		—
Screw Center Jumper — 3-pole		—		—		1492-CJJ5-3		50		—		—
Screw Center Jumper — 2-pole		—		—		1492-CJJ5-2		50		—		—
Plug-in Center Jumper — 41-Pole		1492-CJLJ6-41		10		—		—		1492-CJLJ6-41		10
Plug-in Center Jumper — 5-, 6-, 7-, 8-, 9-, 10-Pole		1492-CJLJ6-10		20		—		—		1492-CJLJ6-10		20
Plug-in Center Jumper — 2-, 3-, 4-Pole		1492-CJLJ6-2, -3, -4		60		—		—		1492-CJLJ6-2, -3, -4		60
Insulated Side Jumper — 24-Pole		—		—		1492-SJ5A-24		50		—		—
Insulated Side Jumper — 10-Pole		—		—		1492-SJ5A-10		50		—		—
Screw Type Jumper Notching Tool		—		—		1492-T1		1		—		—
Other Accessories:												
Partition Plate		—		—		1492-PPJD3		20		1492-PPJD3		20
Test Plug Socket		—		—		1492-TPS23		20		—		—
Test Plug		—		—		1492-TP23		20		—		—
Test Plug (Stackable)		—		—		—		—		—		—
Marking Systems:												
Snap-in marker card		1492-MR6X12 (120/card)		5		1492-M5X8 (144/card)		5		1492-MR6X8 (120/card)		5
		1492-M6X12 (120/card)		5		1492-M5X5 (200/card)		5		1492-M6X5 (200/card)		5

* Use of center jumpers may affect spacings, requiring derating of terminal blocks; see page 12-83 for details.

Screw Connection Terminal Blocks

Specialty Feed-Through Blocks

	1492-W4TW			1492-WR3			1492-J4M		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
	Feed-through terminal block with 3 connection points, 2 on one side			Single-circuit terminal block with terminals on common side.			Motor connection terminal block cluster with 3 feeds and ground		
Specifications									
Certifications							Certifications on individual blocks (1492-J4, JG4)		
Voltage Rating	600V AC/DC 600V AC/DC 800V AC/DC			300V AC/DC 500V AC/DC					
Maximum Current	30 A 20 A 32 A			15 A 15 A					
Wire Range (Rated Cross Section)	#18...10 AWG #22...12 AWG 0.5...4 mm ²			#22...14 AWG 0.5...2.5 mm ²			#22...10 AWG 4 mm ²		
Wire Strip Length	0.35 in. (9 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Recommended Tightening Torque	5.0...5.6 lb•in (0.6 N•m)			5.0...5.6 lb•in (0.6 N•m)			9.0 lb•in (1.0 N•m)		
Density	50 pcs/ft (166 pcs/m)			61 pcs/ft (200 pcs/m)			12 pcs/ft (40 pcs/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)			-40...+195 °F (-40...+90 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating				See page 12-42					
Terminal Blocks									
Color:	Grey	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
	Grey/Green/Yellow	1492-W4TW	50	1492-WR3	50	—	—	1492-J4M	20
	Red	1492-W4TW-RE	50	—	—	—	—	—	—
	Blue	1492-W4TW-B	50	—	—	—	—	—	—
	Black	1492-W4TW-BL	50	—	—	—	—	—	—
	Green	1492-W4TW-G	50	—	—	—	—	—	—
	Yellow	1492-W4TW-Y	50	—	—	—	—	—	—
	Orange	1492-W4TW-OR	50	—	—	—	—	—	—
	Brown	1492-W4TW-BR	50	—	—	—	—	—	—
	White	1492-W4TW-W	50	—	—	—	—	—	—
Accessories									
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1			199-DR1	10	199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5			1492-DR5	10	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			1492-DR6	2	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			1492-DR7	2	1492-DR7	2	1492-DR7	2
End Barriers	Grey	1492-EB3TW	50	1492-EBR3	50	Not Required	—	—	—
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35			1492-ERL35	20	1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty	1492-EAJ35			1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty	1492-EAHJ35			1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50
Jumpers:									
Side Jumper — 10-pole insulated	1492-SJ6-10*			1492-SJ5-10	10	—	—	—	—
Screw Center Jumper — 50-pole	1492-CJ6-50			1492-CJD5-50	5	—	—	—	—
Screw Center Jumper — 10-pole	1492-CJ6-10			1492-CJD5-10	10	1492-CJJ6-10	20	1492-CJJ6-10	20
Screw Center Jumper — 5-pole	1492-CJ6-5			1492-CJD5-5	10	—	—	—	—
Screw Center Jumper — 4-pole	1492-CJ6-4			1492-CJD5-4	10	1492-CJJ6-4	50	1492-CJJ6-4	50
Screw Center Jumper — 3-pole	1492-CJ6-3			1492-CJD5-3	10	1492-CJJ6-3	50	1492-CJJ6-3	50
Screw Center Jumper — 2-pole	1492-CJ6-2			1492-CJD5-2	10	1492-CJJ6-2	50	1492-CJJ6-2	50
Center Jumper Cover — White†	1492-CJCW6			1492-CJCW5	20	—	—	—	—
Center Jumper Link	1492-CJL6			1492-CJL5	10	—	—	—	—
Screw Type Jumper Notching Tool	—			—	—	1492-T1	1	—	—
Other Accessories:									
Partition Plate	1492-PP10			1492-EBR3	50	1492-EBJ16	20	—	—
End Cover*	1492-EC3TW			—	—	—	—	—	—
Test Plug Socket	—			—	—	1492-TPS23L	50	—	—
Test Plug	1492-TP28			—	—	1492-TP23	20	—	—
Test Adapter	1492-TA40			1492-TA285	10	1492-TPJ6	25	—	—
Electrical Warning Plate	—			—	—	1492-EWPJ5	50	—	—
Marking Systems:									
Snap-in marker cards	1492-MS6X9 (80/card)			1492-MS5X9 (80/card)	5	1492-M6X12 (120/card)	5	—	—

* Use side jumpers on the single conductor side only.

* Provides IP2X Finger Safety when a W4 is mounted on open side of Cat. No. 1492-W4TW.

† May only be used as a marking surface. Cannot be installed over a center jumper.


Screw Connection Terminal Blocks

Specialty Feed-Through Blocks

1492-J4CTB

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Single-level feed through block with circuit-break test/measurement plug capability

Certifications	UL	CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC
Maximum Current	8 A		6 A
Wire Range (Rated Cross Section)	#26...10 AWG		0.5...4 mm ²
Wire Strip Length	0.394 in. (10 mm)		
Recommended Tightening Torque	4.4...7.1 lb•in (0.5...0.8 N•m)		
Density	49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42		

Terminal Blocks**Cat. No.****Pkg Qty.**

Color:	Grey	1492-J4CTB	50
--------	------	------------	----

Accessories**Cat. No.****Pkg Qty.**

Mounting Rails:			
1 m Symmetrical DIN (Steel)	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2
End Barrier	Grey	1492-EBJ4CTB	50
End Anchors:			
Screwless End Retainer	1492-ERL35		20
DIN Rail - Normal Duty	1492-EAJ35		100
DIN Rail - Heavy Duty	1492-EAHJ35		50
Other Accessories:			
Test Plug - Make Before Break	1492-TPCMB		25
Test Plug - Break Before Make	1492-TPCBM		25
Marking Systems:			
Snap-in marker cards	1492-MR6X8 (120/card)		5
Snap-in marker cards	1492-M6X5 (200/card)		5

Screw Connection Terminal Blocks



Stab-Connect Feed-Through

1492-J3F

1492-JD3F

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Feed-through terminal block with stab connections on one side

Two-level, two-circuit feed-through terminal block with stab connections on one side

Certifications		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		400V AC/DC
Maximum Current	16 A	10 A	16 A (2 x 8)	10 A		16 A (2 x 8)
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm²	#22...12 AWG	#26...12 AWG	2.5 mm²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)			4.5...7.1 lb•in (0.5...0.8 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42					



Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color: Grey	1492-J3F	50	1492-JD3F	50
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails:				
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2
End Barrier	1492-EBJ3	50	1492-EBJD3	20
End Anchors and Retainers:				
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50
Fast-on Connector (Size 0.110 in.)	800M-NT2	100	800M-NT2	100
Connector Insulation Sleeve	1492-FCS	100	1492-FCS	100
Jumpers:				
Screw Center Jumper — 10-pole	1492-CJJ5-10	20	1492-CJJ5-10	20
Screw Center Jumper — 4-pole	1492-CJJ5-4	50	1492-CJJ5-4	50
Screw Center Jumper — 3-pole	1492-CJJ5-3	50	1492-CJJ5-3	50
Screw Center Jumper — 2-pole	1492-CJJ5-2	50	1492-CJJ5-2	50
Insulated Side Jumper — 24-Pole	1492-SJ5B-24	50	1492-SJ5A-24	50
Insulated Side Jumper — 10-Pole	1492-SJ5B-10	50	1492-SJ5A-10	50
Screw Type Jumper Notching Tool	1492-T1	1	1492-T1	1
Other Accessories:				
Partition Plate	1492-EBJ16	20	1492-PPJD3	20
Marking Systems:				
Snap-in marker cards	1492-M5X12 (144/card)	5	1492-M5X8 (144/card)	5
Snap-in marker cards	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5

1492-WTF3...

1492-WTS3...

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.









Specifications	Three-circuit terminal block.			Three-level sensor block.		
Certifications		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		250V AC/DC	300V AC/DC		250V AC/DC
Maximum Current	10 A		24 A	10 A		24 A
Wire Range (Rated Cross Section)	#26...14 AWG		0.5...2.5mm ²	#26...14 AWG		0.5...2.5 mm ²
Recommended Tightening Torque	4.2...4.6 lb•in (0.5 N•m)			4.2...4.6 lb•in (0.5 N•m)		
Density	60 pcs/ft (197 pcs/m)			60 pcs/ft (197 pcs/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)			-40...+195 °F (-40...+90 °C)		
Indicator Type WTF3/WTS3	No indicator			No indicator		
WTF3LP/WTS3LP	Red LED for PNP devices (10...50V)			Red LED for PNP devices (10...50V)		
WTF3LN/WTS3LN	Red LED for NPN devices (10...50V)			Red LED for NPN devices (10...50V)		
Leakage Current WTF3/WTS3	—			—		
WTF3LP/WTS3LP	2.69 mA @ 50V			2.69 mA @ 50V		
WTF3LN/WTS3LN	2.69 mA @ 50V			2.69 mA @ 50V		
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)		
Short-Circuit Current Rating	See page 12-42					

Terminal Blocks		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color:	Grey	1492-WTF3	50	1492-WTS3	50
	Blue	—	—	1492-WTS3-B	50
	Grey for PNP devices	1492-WTF3LP	50	1492-WTS3LP	50
	Grey for NPN devices	1492-WTF3LN	50	1492-WTS3LN	50
Accessories		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails:					
1 m Symmetrical DIN (Steel)		199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2	1492-DR7	2
End Barrier		1492-EBTF3	50	1492-EBTS3	50
End Anchors and Retainers:					
Screwless End Retainer		1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50	1492-EAHJ35	50
Jumpers:					
Center Jumper — 50-pole		1492-CJT5-50	5	1492-CJT5-50	5
Center Jumper — 10-pole		1492-CJT5-10	10	1492-CJT5-10	10
Center Jumper — 3-pole		1492-CJT5-3	10	1492-CJT5-3	10
Center Jumper — 2-pole		1492-CJT5-2	10	1492-CJT5-2	10
Center Jumper Link		1492-CJL5	10	1492-CJL5	10
Center Jumper Cover — Red		1492-CJCR5	10	1492-CJCR5	10
Center Jumper Cover — Blue		1492-CJCB5	10	1492-CJCB5	10
Side — 20-pole Insulated Red		1492-SJT5-20-R	10	1492-SJT5-20-R	10
Side — 20-pole Insulated Blue		1492-SJT5-20-B	10	1492-SJT5-20-B	10
Other Accessories:					
Partition Plate		1492-PPTS3	50	1492-PPTS3	50
Test Plug Adapter		1492-TA285	10	1492-TA285	10
Electrical Warning Plate	4-Pole	1492-EWP5-4	10	1492-EWP5-4	10
	1-Pole	1492-EWP5	10	1492-EWP5	10
Marking Systems:					
Snap-in Marker Card		1492-MS5X9 (80/card)	5	1492-MS5X9 (80/card)	5

Screw Connection Terminal Blocks

Grounding Blocks




1492-JG2Q				1492-JG3				1492-JG3TW			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
	<i>Feed-through grounding terminal block with 2 connection points on each side</i>			<i>Feed-through grounding terminal block</i>			<i>Feed-through grounding terminal block with 3 connection points, 2 on one side</i>				
		CSA	IEC		CSA	IEC	ATEX		CSA	IEC	ATEX
	—	—	—	—	—	—	—	—	—	—	—
	Maximum Current	Grounding			Grounding			Grounding			
Wire Range (Rated Cross Section)	#22...14 AWG	1.5 mm ²	#22...12 AWG	2.5 mm ²	2.5 mm ² (#20...14 AWG)	Single Side: #22...12 AWG		2.5 mm ²	2.5 mm ² (#20...14 AWG)		
						Twin Side: #26...12 AWG		1.5 mm ²	1.5 mm ² (#20...16 AWG)		
Wire Strip Length	0.28 in. (7 mm)		0.39 in. (10 mm)			Single Side: 0.39 in. (10 mm)					
						Twin Side: 0.28 in. (7 mm)					
Recommended Tightening Torque	5.0 lb•in (0.6 N•m)		7.1 lb•in (0.8 N•m)			Single Side: 7.1 lb•in (0.8 N•m)					
Mounting Torque — Center Screw	3.5...5.3 lb•in (0.4...0.6 N•m)		3.5...6.2 lb•in (0.4...0.6 N•m)			Twin Side: 4.5 lb•in (0.5 N•m)					
Density	59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating	See page 12-42										
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.					
Color: Green/Yellow	1492-JG2Q	100	1492-JG3	100	1492-JG3TW	100					
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.					
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10					
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10					
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2					
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2					
End Barrier Yellow	1492-EBJ3-Y	50	1492-EBJ3-Y	50	1492-EBJ3-Y	50					
End Anchors and End Retainers:											
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20					
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100					
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50					
Marking Systems:											
Snap-in marker cards	1492-M5X12 (144/card)	5	1492-M5X12 (144/card)	5	1492-M5X12 (144/card)	5					
Snap-in marker cards	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5					

	1492-JG4				1492-JG4TW			1492-JG4Q		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
Specifications	Feed-through grounding terminal block				Single-level grounding terminal block with 3 connection points, 2 on one side			Single-level grounding terminal block with two connection points on each side		
Certifications		CSA	IEC	ATEX		CSA	IEC		CSA	IEC
Voltage Rating	—				—			—		
Maximum Current	Grounding				Grounding			Grounding		
Wire Range (Rated Cross Section)	#22...10 AWG		4 mm ²	4 mm ² (#20...12 AWG)	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.394 in. (10 mm)			0.394 in. (10 mm)		
Recommended Tightening Torque	9 lb•in (1.0 N•m)				6.2 lb•in (0.7 N•m)			6.2 lb•in (0.7 N•m)		
Mounting Torque - Center Screw	4.4...7.1 lb•in (0.5...0.8 N•m)				—			—		
Density	49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42									
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color: Green/Yellow	1492-JG4			100	1492-JG4TW		50	1492-JG4Q		50
Accessories	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7		2	1492-DR7		2
End Barrier Yellow	Not Required			—	1492-EBJ4TW-Y		50	1492-EBJ4Q-Y		50
End Anchors:										
Screwless End Retainer	1492-ERL35			20	1492-ERL35		20	1492-ERL35		20
DIN Rail - Normal Duty	1492-EAJ35			100	1492-EAJ35		100	1492-EAJ35		100
DIN Rail - Heavy Duty	1492-EAHJ35			50	1492-EAHJ35		50	1492-EAHJ35		50
Marking Systems:										
Snap-in marker cards	1492-M6X12 (120/card)			5	1492-MR6X12 (120/card)		5	1492-MR6X12 (120/card)		5
Snap-in marker cards	1492-M6X5 (200/card)			5	1492-M6X12 (120/card)		5	1492-M6X12 (120/card)		5

Screw Connection Terminal Blocks




Grounding Blocks




Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.	1492-JG6				1492-JG10			
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—				—			
Maximum Current	Grounding				Grounding			
Wire Range (Rated Cross Section)	#22...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)		#16...6 AWG	10 mm ²	10 mm ² (#16...8 AWG)	
Wire Strip Length	0.47 in. (12 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	14.2 lb•in (1.6 N•m)				20.4 lb•in (2.3 N•m)			
Mounting Torque — Center Screw	4.4...8.9 lb•in (0.5...1.0 N•m)				4.4...8.9 lb•in (0.5...1.0 N•m)			
Density	37 pcs/ft (123 pcs/m)				30 pcs/ft (100 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42							
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color: Green/Yellow	1492-JG6		50		1492-JG10		50	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:								
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2	
End Anchors and End Retainers:								
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50	
Marking Systems:								
Snap-in marker cards	1492-MR8X12 (84/card)		5		1492-M7X12 (108/card)		5	
Snap-in marker cards	1492-M8X5 (160/card)		5		1492-M8X5 (160/card)		5	

	1492-JG16				1492-JG35				1492-JG50			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
	Feed-through grounding terminal block				Feed-through grounding terminal block				Feed-through grounding terminal block			
Specifications												
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding			
Wire Range (Rated Cross Section)	#24...4 AWG	16 mm ²	16 mm ² (#16...6 AWG)		#12...1 AWG	#12...2 AWG	35 mm ²	35 mm ² (#14...2 AWG)	#10...1/0 AWG	#14...1/0 AWG	50 mm ²	50 mm ² (10...1/0 AWG)
Wire Strip Length	0.63 in. (16 mm)				0.70 in. (18 mm)				0.94 in. (24 mm)			
Recommended Tightening Torque	35.0 lb•in (4.0 N•m)				51.0 lb•in (5.8 N•m)				31.5 lb•in (3.6 N•m)			
Mounting Torque — Center Screw	10.6...21.2 lb•in (1.2...2.4 N•m)				10.6...21.2 lb•in (1.2...2.4 N•m)				17.7...35.4 lb•in (2.0...4.0 N•m)			
Density	25 pcs/ft (83 pcs/m)				19 pcs/ft (62 pcs/m)				16 pcs/ft (54 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color: Green/Yellow	1492-JG16			50	1492-JG35			25	1492-JG50			10
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1			10	—			—	—			—
1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)	199-DR4			5	199-DR4			5	199-DR4			5
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	—			—
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	—			—
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	—			—	—			—
1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	1492-DR8			5	1492-DR8			5	1492-DR8			5
1 m Symmetrical Heavy Duty DIN (Steel)	1492-DR9			5	1492-DR9			5	1492-DR9			5
End Barrier	Not Required			—	Not Required			—	Not Required			—
End Anchors:												
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50
Marking Systems:												
Snap-in marker cards	1492-M7X12 (108/card)			5	1492-M7X12 (108/card)			5	1492-M7X12 (108/card)			5
Snap-in marker cards	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5

Screw Connection Terminal Blocks




Grounding Blocks

	1492-JG70				1492-JG120			1492-JDG3			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block			Two-circuit terminal block with one feed-through and one grounding circuit			
Certifications		CSA	IEC	ATEX		CSA	IEC		CSA	IEC	ATEX
Voltage Rating	—				—			300V AC/DC		400V AC/DC	275V AC/DC
Maximum Current	Grounding				—			20 A		24 A	21 A
Wire Range (Rated Cross Section)	#6...2/0 AWG		70 mm ²	70 mm ² (#8...2/0 AWG)	#4...3/0 AWG	#4...4/0 AWG	16...95 mm ²	#22...12 AWG		2.5 mm ²	2.5 mm ² (#20...14 AWG)
Wire Strip Length	0.87 in. (22 mm)				1.06 in. (27 mm)			0.39 in. (10 mm)			
Recommended Tightening Torque	87.0 lb•in (9.8 N•m)				88.5 lb•in (10 N•m)			4.5...7.1 lb•in. (0.5...0.8 N•m)			
Mounting Torque — Center Screw	17.7...35.4 lb•in (2.0...4.0 N•m)				—			—			
Density	14 pcs/ft (48 pcs/m)				11 pcs/ft (37 pcs/m)			59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42										
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.			Pkg Qty.
Color: Green/Yellow	1492-JG70			10	1492-JG120		5	—			—
Grey	—			—	—		—	1492-JDG3			100
Accessories	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails:	—			—	—		—	199-DR1			10
1 m Symmetrical DIN (Steel)	—			—	—		—	1492-DR5			10
1 m Symmetrical DIN (Aluminum)	—			—	—		—	1492-DR6			2
1 m Hi-Rise Sym. DIN (Aluminum)	—			—	—		—	1492-DR7			2
1 m Angled Hi-Rise Sym. DIN (Steel)	—			—	—		—	—			—
Screw Type 1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	1492-DR8			5	1492-DR8		5	—			—
End Barrier Grey	Not Required			—	—		—	1492-EBJD3			20
Yellow	Not Required			—	—		—	1492-EBJD3-Y			20
Jumpers:	—			—	—		—	1492-CJJ5-10			20
Screw Center Jumper — 10-pole	—			—	—		—	1492-CJJ5-4			50
Screw Center Jumper — 4-pole	—			—	—		—	1492-CJJ5-3			50
Screw Center Jumper — 3-pole	—			—	—		—	1492-CJJ5-2			50
Screw Center Jumper — 2-pole	—			—	—		—	1492-SJ5A-24			50
Insulated Side Jumper — 24-Pole	—			—	—		—	1492-SJ5A-10			50
Insulated Side Jumper — 10-Pole	—			—	—		—	—			—
End Anchors and Retainers:	—			—	—		—	1492-ERL35			20
Screwless End Retainer	—			—	—		—	1492-EAJ35			100
DIN Rail — Normal Duty	—			—	—		—	1492-EAJ35			100
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35		50	1492-EAHJ35			50
Marking Systems:	—			—	—		—	—			—
Snap-in marker cards	1492-M7X12 (108/card)			5	1492-MR8X12 (84/card)		5	1492-M5X8 (200/card)			5
Snap-in marker cards	1492-M8X5 (160/card)			5	1492-M7X12 (108/card)		5	1492-M5X5 (144/card)			5

1492-JDG3C					1492-JDG4				1492-JDG4C			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Two-level grounding terminal block with commoning bar				Two-circuit terminal block with one feed-through and one grounding				Two-level grounding terminal block with commoning bar			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—				600V AC/DC	300V AC/DC	800V AC/DC	550V AC/DC	—			
Maximum Current	Grounding				35 A	30 A	32 A	28 A	Grounding			
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (#20...14 AWG)	#26...10 AWG		4 mm ²	4 mm ²	#26...10 AWG	4 mm ²	4 mm ²	
Wire Strip Length	0.39 in. (10 mm)				0.31 in. (8 mm)				0.31 in. (8 mm)			
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)				4.5...8.8 lb•in (0.5...1.0 N•m)				4.5...8.8 lb•in (0.5...1.0 N•m)			
Mounting Torque — Center Screw	—				—				—			
Density	59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating												
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color: Green/Yellow	1492-JDG3C			100	—			—	1492-JDG4C			100
Grey	—			—	1492-JDG4			100	—			—
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2
Screw Type 1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	—			—	—			—	—			—
End Barrier												
Grey	1492-EBJD4			20	1492-EBJD4			20	1492-EBJD4			20
Yellow	1492-EBJD4-Y			20	1492-EBJD4-Y			20	1492-EBJD4-Y			20
Jumpers:												
Screw Center Jumper — 41-pole	—			—	1492-CJLJ6-41			10	—			—
Center Jumper — 10-pole	—			—	1492-CJLJ6-10			20	—			—
Center Jumper — 4-pole	—			—	1492-CJLJ6-4			60	—			—
Center Jumper — 3-pole	—			—	1492-CJLJ6-3			60	—			—
Center Jumper — 2-pole	—			—	1492-CJLJ6-2			60	—			—
End Anchors and Retainers:												
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50
Marking Systems:												
Snap-in marker cards	1492-M5X8 (144/card)			5	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5
Snap-in marker cards	1492-M5X5 (200/card)			5	1492-MR6X8 (120/card)			5	1492-MR6X8 (120/card)			5

Screw Connection Terminal Blocks

Space-Saver Grounding Blocks

	1492-WG4				1492-WG6				1492-WG10S		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
	Single-circuit grounding terminal block.				Single-circuit grounding terminal block.				Single-circuit grounding terminal block.		
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX		CSA	IEC
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding		
Wire Range (Rated Cross Section)	#22...12 AWG	4 mm ²	#22...12 AWG	4 mm ²	#22...10 AWG	6 mm ²	#22...10 AWG	6 mm ²	#22...8 AWG	#22...8 AWG	10 mm ²
Wire Strip Length	0.43 in. (11 mm)				0.47 in. (12 mm)				0.43 in. (11 mm)		
Recommended Tightening Torque	5.6...6.8 lb•in (0.7 N•m)				5.6...6.8 lb•in (0.7 N•m)				7.1 lb•in (0.8 N•m)		
Density	50 pcs/ft (166 pcs/m)				43 pcs/ft (142 pcs/m)				38 pcs/ft (125 pcs/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color: Green/Yellow	1492-WG4	50			1492-WG6	50			1492-WG10S	10	
Accessories	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1	10			199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10			1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2			1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2			1492-DR7	2			1492-DR7	2	
End Barrier	1492-EB3-Y	50			1492-EB10-Y	50			1492-EB10-Y	50	
End Anchors:											
DIN Rail — Normal Duty	1492-EAJ35	100			1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50			1492-EAHJ35	50			1492-EAHJ35	50	
Marking Systems:											
Snap-in Marker Card	1492-MS6X12 (80/card)	5			1492-MS6X12 (80/card)	5			1492-MS6X12 (80/card)	5	


Screw Connection Terminal Blocks

Space-Saver Grounding Blocks

1492-WG16S

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Single-circuit grounding terminal block.

Certifications		CSA	IEC
Voltage Rating	—	—	—
Maximum Current	Grounding		
Wire Range (Rated Cross Section)	#14...4 AWG		2.5...16 mm ²
Wire Strip Length	0.51 in. (13 mm)		
Recommended Tightening Torque	18...20 lb•in (2.1 N•m)		
Center Screw Mounting Torque	10.6 lb•in (1.2 N•m)		
Density	27 pcs/ft (90 pcs/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)		

Terminal Blocks**Cat. No.****Pkg Qty.**




Color:	Green/Yellow	1492-WG16S	25
--------	--------------	-------------------	----

Accessories**Cat. No.****Pkg Qty.**

Mounting Rails:			
1 m Symmetrical DIN (Steel)	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2
1 m Symmetrical DIN (Copper)	1492-DR8		5
1 m Symmetrical DIN (Steel)	1492-DR9		5
End Barrier	Not Required		—
End Anchors:			
DIN Rail — Normal Duty	1492-EAJ35		100
DIN Rail — Heavy Duty	1492-EAHJ35		50
Marking Systems:			
Snap-in Marker Card	1492-MS6X12 (80/card)		5

Screw Connection Terminal Blocks

Isolation Blocks




1492-JKD3				1492-JKD3TP			1492-JKD4		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Feed through terminal block with knife disconnect			Feed-through terminal block with knife disconnect and test screws			Feed-through terminal block with knife disconnect		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC
Maximum Current	10 A		24 A	10 A		24 A	22 A	10 A	32 A
Wire Range (Rated Cross Section)	#22...12 AWG		2.5 mm ²	#22...12 AWG		2.5 mm ²	#22...10 AWG		0.05...4.0 mm ²
Fuse Size (Dummy Fuse Supplied)	—			—			—		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.512 in. (13 mm)		
Recommended Tightening Torque	7.1 lb•in. (0.8 N•m)			7.1 lb•in. (0.8 N•m)			9.0 lb•in. (1.0 N•m)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color:	Grey	1492-JKD3	100	1492-JKD3TP	100		1492-JKD4	100	
	Blue	1492-JKD3-B	100	—	—		1492-JKD4-B	100	
with Test Points	Grey	—	—	—	—		1492-JKD4TP	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers	Grey	1492-EBJ3	50	1492-EBJ3	50		1492-EBJ3	50	
	Yellow	—	—	—	—		1492-EBJ3-Y	50	
End Anchors:									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers:									
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-50	10		1492-CJLJ5-50	10		—	—	
Plug-in Center Jumper — 41-Pole	—	—		—	—		1492-CJLJ6-41	10	
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-10	20		1492-CJLJ5-10	20		1492-CJLJ6-10	20	
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-9	20		1492-CJLJ5-9	20		—	—	
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-8	20		1492-CJLJ5-8	20		—	—	
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-7	20		1492-CJLJ5-7	20		—	—	
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-6	20		1492-CJLJ5-6	20		—	—	
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-5	20		1492-CJLJ5-5	20		—	—	
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-4	60		1492-CJLJ5-4	60		1492-CJLJ6-4	60	
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-3	60		1492-CJLJ5-3	60		1492-CJLJ6-3	60	
Plug-in Center Jumper — 2-Pole	1492-CJLJ5-2	60		1492-CJLJ5-2	60		1492-CJLJ6-2	60	
Insulated Side Jumper — 24-Pole	1492-SJ5B-24	50		1492-SJ5B-24	50		—	—	
Insulated Side Jumper — 10-Pole	1492-SJ5B-10	50		1492-SJ5B-10	50		—	—	
Uninsulated Side Jumper — 10-Pole	—	—		—	—		—	—	
Side Jumper — Insulating Sleeve	—	—		—	—		—	—	
Screw Type Jumper Notching Tool	1492-T1	1		1492-T1	1		—	—	
Other Accessories:									
Partition Plate	1492-EBJ16	20		1492-EBJ16	20		1492-EBJ16	20	
Test Plug	—	—		1492-TP23	20		—	—	
Marking Systems:									
Snap-in marker cards	1492-M5X12 (144/card)	5		1492-M5X12 (144/card)	5		1492-MR6X12 (120/card)	5	
Snap-in marker cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M6X12 (120/card)	5	

1492-JKD4TW

1492-JKD4Q

1492-H7

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.





Specifications		Feed-through terminal block with knife disconnect; 3 connection points, 2 on one side			Feed-through terminal block with knife disconnect; 2 connection points on each side			Handle-style isolating terminal block		
Certifications		UL	CSA	IEC	UL	CSA	IEC	UL	CSA	IEC
Voltage Rating		600V AC/DC		500V AC/DC	600V AC/DC		500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current		25 A		30 A	25 A		30 A	15 A	15 A	15 A
Wire Range (Rated Cross Section)		#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4.0 mm ²
Fuse Size (Dummy Fuse Supplied)		—			—			1/4 x 1-1/4 in.		
Wire Strip Length		0.39 in. (10 mm)			0.39 in. (10 mm)			0.38 in. (9.7 mm)		
Recommended Tightening Torque		6.2 lb•in (0.7 N•m)			6.2 lb•in (0.7 N•m)			7.1 lb•in (0.8 N•m)		
Density		49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			33 pcs/ft (109 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-40...+221 °F (-40...+105 °C)		
Short-Circuit Current Rating		See page 12-42								
Terminal Blocks		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color:	Grey	1492-JKD4TW		50	1492-JKD4Q		50	—		—
With Test Points	Grey	1492-JKD4TWTP		50	1492-JKD4QTP		50	—		—
	Black	—		—	—		—	1492-H7		25
Accessories		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:		—		—	—		—	1492-N1		20
3 ft Scored A-B Rail		—		—	—		—	1492-N22		20
3 ft Rigid A-B Rail		—		—	—		—	1492-N44		2
3 ft Rigid Rise A-B Rail		—		—	—		—	1492-N25		2
Standoff Brackets (use every 12 in.) 		—		—	—		—	1492-N25		2
1 m Symmetrical DIN (Steel)		199-DR1		10	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)		1492-DR5		10	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2	1492-DR7		2	1492-DR7		2
End Barrier	Grey	1492-EBJ4TW		50	1492-EBJ4Q		50	1492-N37		50
	Yellow	1492-EBJ4TW-Y		50	1492-EBJ4Q-Y		50	—		—
End Anchors and Retainers:		—		—	—		—	1492-N23		10
A-B Rail — Heavy Duty		—		—	—		—	1492-N47		50
A-B Rail — Normal Duty		—		—	—		—	1492-ERL35		20
Screwless End Retainer		1492-ERL35		20	1492-ERL35		20	1492-ERL35		100
DIN Rail - Normal Duty		1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		50
DIN Rail - Heavy Duty		1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		—
Jumpers:		1492-CJLJ6-41		10	1492-CJLJ6-41		10	—		—
Plug-in Center Jumper — 41-pole		1492-CJLJ6-10		20	1492-CJLJ6-10		20	—		—
Plug-in Center Jumper — 10-pole		1492-CJLJ6-4		60	1492-CJLJ6-4		60	—		—
Plug-in Center Jumper — 4-pole		1492-CJLJ6-3		60	1492-CJLJ6-3		60	—		—
Plug-in Center Jumper — 3-pole		1492-CJLJ6-2		60	1492-CJLJ6-2		60	—		—
Plug-in Center Jumper — 2-pole		—		—	—		—	1492-N49		10
Uninsulated Side Jumper — 10-Pole		—		—	—		—	1492-SJS		10
Side Jumper — Insulating Sleeve		—		—	—		—	—		—
Other Accessories:		—		—	—		—	—		—
Partition Plate		—		—	—		—	—		—
Marking Systems:		1492-MR6X12 (120/card)		5	1492-MR6X12 (120/card)		5	1492-MS8X12 (56/card)		5
Snap-in marker cards		1492-M6X12 (120/card)		5	1492-M6X12 (120/card)		5	1492-MS8X9 (56/card)		5
Snap-in marker cards		—		—	—		—	1492-ALHFB (50/sheet)		1
Adhesive Labels		—		—	—		—	—		—

* For use with 1492-N22 DIN rail only.

Screw Connection Terminal Blocks

Plug-In Style Terminal Blocks

1492-J3P				1492-J3PTP				1492-JD3P			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
	Selectable component plug-in terminal block			Selectable component plug-in terminal block with test plug socket			Two Circuit selectable component plug-in terminal block				
Specifications											
Certifications		CSA	IEC		CSA	IEC		CSA	IEC		
Voltage Rating	600V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC		
Maximum Current	20 A	10 A	24 A	20 A	10 A	24 A	20 A		24 A		
Wire Range (Rated Cross Section)	#30...12 AWG		2.5 mm ²	#30...12 AWG		2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.31 in. (8 mm)				
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)				
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating	See page 12-42										
Terminal Blocks		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		
Color:	Grey	1492-J3P	100		1492-J3PTP	100		1492-JD3P	50		
	Red	1492-J3P-RE	100		—	—		—	—		
Accessories		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		
Mounting Rails:											
1 m Symmetrical DIN (Steel)		199-DR1	10		199-DR1	10		199-DR1	10		
1 m Symmetrical DIN (Aluminum)		1492-DR5	10		1492-DR5	10		1492-DR5	10		
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2		1492-DR6	2		1492-DR6	2		
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2		1492-DR7	2		1492-DR7	2		
End Barriers		1492-EBJ3	50		1492-EBJ3	50		1492-EBJD3P	20		
End Anchors and Retainers:											
Screwless End Retainer		1492-ERL35	20		1492-ERL35	20		1492-ERL35	20		
DIN Rail — Normal Duty		1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100		
DIN Rail — Heavy Duty		1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50		
Jumpers* ⚡:											
Center Jumper — 50-Pole		1492-CJLJ5-50	10		1492-CJLJ5-50	10		—	—		
Center Jumper — 10-Pole		1492-CJLJ5-10	20		1492-CJLJ5-10	20		1492-CJJ5-10	20		
Center Jumper — 9-Pole		1492-CJLJ5-9	20		1492-CJLJ5-9	20		—	—		
Center Jumper — 8-Pole		1492-CJLJ5-8	20		1492-CJLJ5-8	20		—	—		
Center Jumper — 7-Pole		1492-CJLJ5-7	20		1492-CJLJ5-7	20		—	—		
Center Jumper — 6-Pole		1492-CJLJ5-6	20		1492-CJLJ5-6	20		—	—		
Center Jumper — 5-Pole		1492-CJLJ5-5	20		1492-CJLJ5-5	20		—	—		
Center Jumper — 4-Pole		1492-CJLJ5-4	60		1492-CJLJ5-4	60		1492-CJJ5-4	50		
Center Jumper — 3-Pole		1492-CJLJ5-3	60		1492-CJLJ5-3	60		1492-CJJ5-3	50		
Center Jumper — 2-Pole		1492-CJLJ5-2	60		1492-CJLJ5-2	60		1492-CJJ5-2	50		
Screw Type Jumper Notching Tool		—	—		—	—		1492-T1	1		
Other Accessories:											
Partition Plate		1492-EBJ16	20		1492-EBJ16	20		1492-PPJD3P	20		
Test Plug		—	—		1492-TP23	20		—	—		
Disconnect Plug		1492-DPL	50		1492-DPL	50		1492-DPL	50		
Component Plug		1492-CPL	50		1492-CPL	50		1492-CPL	50		
Fuse Plug											
Without Blown Fuse Indicator		1492-FPK2	20		1492-FPK2	20		1492-FPK2	20		
10...36V Blown Fuse Indicator		1492-FPK224	20		1492-FPK224	20		1492-FPK224	20		
35...70V Blown Fuse Indicator		1492-FPK248	20		1492-FPK248	20		1492-FPK248	20		
60...150V Blown Fuse Indicator		1492-FPK2120	20		1492-FPK2120	20		1492-FPK2120	20		
140...250V Blown Fuse Indicator		1492-FPK2250	20		1492-FPK2250	20		1492-FPK2250	20		
Marking Systems:											
Snap-in marker cards		1492-M5X12 (144/card)	5		1492-M5X12 (144/card)	5		1492-SM5X10 (144/card)	5		
Snap-in marker cards		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		

* Cat. nos. 1492-J3P and J3PTP use screwless center jumpers. Cat. No. 1492-JD3P uses a screw-type center jumper.

‡ Use of Center Jumpers may affect spacings, requiring derating of terminal blocks. See the Terminal Block selection guide, pub. no. 1492-SG008*.




Screw Connection Terminal Blocks

Plug-In Style Terminal Blocks

1492-JD3PTP				1492-JD3PSS			1492-JD3PSSTP		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit selectable component plug-in terminal block with test plug socket			Two-circuit selectable component plug-in terminal block with internal surge suppressor			Two-circuit selectable component plug-in terminal block with internal surge suppressor and test plug socket		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		115V AC	300V AC/DC		115V AC/DC
Maximum Current	20 A		24 A	20 A		24 A	20 A		24 A
Wire Range (Rated Cross Section)	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey	1492-JD3PTP	50		1492-JD3PSS	50		1492-JD3PSSTP	50	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers	1492-EBJD3P	20		1492-EBJD3P	20		1492-EBJD3P	20	
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers:									
Screw Center Jumper — 10-Pole	1492-CJJ5-10	20		1492-CJJ5-10	20		1492-CJJ5-10	20	
Screw Center Jumper — 4-Pole	1492-CJJ5-4	50		1492-CJJ5-4	50		1492-CJJ5-4	50	
Screw Center Jumper — 3-Pole	1492-CJJ5-3	50		1492-CJJ5-3	50		1492-CJJ5-3	50	
Screw Center Jumper — 2-Pole	1492-CJJ5-2	50		1492-CJJ5-2	50		1492-CJJ5-2	50	
Screw Type Jumper Notching Tool	1492-T1	1		1492-T1	1		1492-T1	1	
Other Accessories:									
Partition Plate	1492-PPJD3P	20		1492-PPJD3P	20		1492-PPJD3P	20	
Test Plug	1492-TP23	20		—	—		1492-TP23	20	
Disconnect Plug	1492-DPL	50		1492-DPL	50		1492-DPL	50	
Component Plug	1492-CPL	50		1492-CPL	50		1492-CPL	50	
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20		1492-FPK2	20		1492-FPK2	20	
10...36V Blown Fuse Indicator	1492-FPK224	20		1492-FPK224	20		1492-FPK224	20	
35...70V Blown Fuse Indicator	1492-FPK248	20		1492-FPK248	20		1492-FPK248	20	
60...150V Blown Fuse Indicator	1492-FPK2120	20		1492-FPK2120	20		1492-FPK2120	20	
140...250V Blown Fuse Indicator	1492-FPK2250	20		1492-FPK2250	20		1492-FPK2250	20	
Group Marking Carrier	1492-GM35	25		1492-GM35	25		1492-GM35	25	
Marking Systems:									
Snap-in marker cards	1492-SM5X10 (144/card)	5		1492-SM5X10 (144/card)	5		1492-SM5X10 (144/card)	5	
Snap-in marker cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	

Screw Connection Terminal Blocks

Double-Level Plug-In Style Terminal Blocks

	1492-JDG3P			1492-JDG3PTP			1492-JDG3PSS		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit block with ground connection			Two-circuit block with test plug socket and ground connection			Single-circuit block with MOV to ground		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC	300V AC/DC		115V AC
Maximum Current	20 A		24 A	20 A		24 A	20 A		24 A
Wire Range (Rated Cross Section)	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey	1492-JDG3P	50		1492-JDG3PTP	50		1492-JDG3PSS	50	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers	1492-EBJD3P	20		1492-EBJD3P	20		1492-EBJD3P	20	
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers:									
Screw Center Jumper — 10-Pole	1492-CJJ5-10	20		1492-CJJ5-10	20		—	—	
Screw Center Jumper — 4-Pole	1492-CJJ5-4	50		1492-CJJ5-4	50		—	—	
Screw Center Jumper — 3-Pole	1492-CJJ5-3	50		1492-CJJ5-3	50		—	—	
Screw Center Jumper — 2-Pole	1492-CJJ5-2	50		1492-CJJ5-2	50		—	—	
Screw Type Jumper Notching Tool	1492-T1	1		1492-T1	1		—	—	
Other Accessories:									
Partition Plate	1492-PPJD3P	20		1492-PPJD3P	20		1492-PPJD3P	20	
Test Plug	—	—		1492-TP23	20		—	—	
Disconnect Plug	1492-DPL	50		1492-DPL	50		1492-DPL	50	
Component Plug	1492-CPL	50		1492-CPL	50		1492-CPL	50	
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20		1492-FPK2	20		1492-FPK2	20	
10...36V Blown Fuse Indicator	1492-FPK224	20		1492-FPK224	20		1492-FPK224	20	
35...70V Blown Fuse Indicator	1492-FPK248	20		1492-FPK248	20		1492-FPK248	20	
60...150V Blown Fuse Indicator	1492-FPK2120	20		1492-FPK2120	20		1492-FPK2120	20	
140...250V Blown Fuse Indicator	1492-FPK2250	20		1492-FPK2250	20		1492-FPK2250	20	
Marking Systems:									
Snap-in marker cards	1492-SM5X10 (144/card)	5		1492-SM5X10 (144/card)	5		1492-SM5X10 (144/card)	5	
Snap-in marker cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	


Screw Connection Terminal Blocks

Double-Level Plug-In Style Terminal Blocks

1492-JDG3PSSTP

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.






Single-circuit block with MOV to ground and test plug socket

Specifications			
Certifications	UL	CSA	IEC
Voltage Rating	300V AC/DC		
Maximum Current	20 A		
Wire Range (Rated Cross Section)	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42		

Terminal Blocks	Cat. No.	Pkg Qty.
Color: Grey	1492-JDG3PSSTP	50
Accessories	Cat. No.	Pkg Qty.
Mounting Rails:		
1 m Symmetrical DIN (Steel)	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2
End Barriers	1492-EBJD3P	20
End Anchors and Retainers:		
Screwless End Retainer	1492-ERL35	20
DIN Rail — Normal Duty	1492-EAJ35	100
DIN Rail — Heavy Duty	1492-EAHJ35	50
Other Accessories:		
Partition Plate	1492-PPJD3P	20
Test Plug	1492-TP23	20
Disconnect Plug	1492-DPL	50
Component Plug	1492-CPL	50
Fuse Plug		
Without Blown Fuse Indicator	1492-FPK2	20
10...36V Blown Fuse Indicator	1492-FPK224	20
35...70V Blown Fuse Indicator	1492-FPK248	20
60...150V Blown Fuse Indicator	1492-FPK2120	20
140...250V Blown Fuse Indicator	1492-FPK2250	20
Marking Systems:		
Snap-in marker cards	1492-SM5X10 (144/card)	5
Snap-in marker cards	1492-M5X5 (200/card)	5

Screw Connection Terminal Blocks

Internal Component Blocks

1492-J3DF				1492-JD3DF*			1492-JD3DR*			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
	Single-level diode forward terminal block with test plug sockets			Two-Level terminal block with a diode in forward bias between the levels.			Two-Level terminal block with a diode in reverse bias between the levels.			
	Certifications		CSA	IEC		CSA	IEC		CSA	IEC
	Voltage Rating	300V AC/DC		500V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC
	Diode Reverse Voltage Rating	—			1000V			1000V		
Maximum Current	20 A	10 A	6 A	20 A	10 A	—	20 A	10 A	—	
Diode Current*	—			1 A			1 A			
Resistor Type	—			—			—			
Resistor Value	—			—			—			
Current through Busbar	10 A	1 A	14 A	10 A			10 A			
Wire Range (Rated Cross Section)	#26...12 AWG		0.5...2.5 mm ²	#22...12 AWG	#26...12 AWG	2.5 mm ²	#22...12 AWG	#26...12 AWG	2.5 mm ²	
Wire Strip Length	0.394 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)			
Recommended Tightening Torque	4.4...6.2 lb•in (0.5...0.7 N•m)			4.5...7.1 lb•in (0.5...0.8 N•m)			4.5...7.1 lb•in (0.5...0.8 N•m)			
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See [T-8479231]									
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	
Color: Black	1492-J3DF		50	1492-JD3DF		1	1492-JD3DR		1	
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10	199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10	1492-DR5		10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2	1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2	1492-DR7		2	
End Barrier	1492-EBJ3		50	1492-EBJD3		20	1492-EBJD3		20	
End Anchors:										
Screwless End Retainer	1492-ERL35		20	1492-ERL35		20	1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50	
Jumpers:										
Screw Center Jumper — 10-pole	—		—	1492-CJJ5-10		20	1492-CJJ5-10		20	
Screw Center Jumper — 4-pole	—		—	1492-CJJ5-4		50	1492-CJJ5-4		50	
Screw Center Jumper — 3-pole	—		—	1492-CJJ5-3		50	1492-CJJ5-3		50	
Screw Center Jumper — 2-pole	—		—	1492-CJJ5-2		50	1492-CJJ5-2		50	
Insulated Side Jumper — 24-Pole	—		—	1492-SJ5A-24		50	1492-SJ5A-24		50	
Insulated Side Jumper — 10-Pole	—		—	1492-SJ5A-10		50	1492-SJ5A-10		50	
Screw Type Jumper Notching Tool	—		—	1492-T1		1	1492-T1		1	
Other Accessories:										
Partition Plate	1492-SPJ3		50	1492-PPJD3		20	1492-PPJD3		20	
Other Accessories:										
Test Plug	1492-TP23		20	—		—	—		—	
Marking Systems:										
Snap-in marker card	1492-MR5X12 (120/card)		5	1492-M5X8 (144/card)		5	1492-M5X8 (144/card)		5	
Snap-in marker card	1492-M5X12 (144/card)		5	1492-M5X5 (200/card)		5	1492-M5X5 (200/card)		5	

* See page 12-97 for component specifications.

Screw Connection Terminal Blocks



Internal Component Blocks

1492-JD3RC001*

1492-JD3SS

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Two-level terminal block with a 249 ohm resistor between the levels			Two-level terminal block with an MOV between the levels		
Certifications		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC	300V AC/DC	400V AC/DC	600V AC/DC	115V AC/DC	
Resistor Type	Precision Wire Wound			—		
Resistor Value	249 Ω, 1/2 W			—		
Current through Busbar	20 A	10 A	—	20 A	10 A	24 A
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm²	#22...12 AWG	#26...12 AWG	2.5 mm²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)			4.5...7.1 lb•in (0.5...0.8 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color: Grey	1492-JD3RC001		1	1492-JD3SS		1
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Steel)						
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2
End Barrier	1492-EBJD3		20	1492-EBJD3		20
End Anchors:	1492-ERL35		20	1492-ERL35		20
Screwless End Retainer						
DIN Rail — Normal Duty	1492-EAJ35		100	1492-EAJ35		100
DIN Rail — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50
Jumpers:	1492-CJJ5-10		20	1492-CJJ5-10		20
Screw Center Jumper — 10-pole						
Screw Center Jumper — 4-pole	1492-CJJ5-4		50	1492-CJJ5-4		50
Screw Center Jumper — 3-pole	1492-CJJ5-3		50	1492-CJJ5-3		50
Screw Center Jumper — 2-pole	1492-CJJ5-2		50	1492-CJJ5-2		50
Insulated Side Jumper — 24-Pole	1492-SJ5A-24		50	1492-SJ5A-24		50
Insulated Side Jumper — 10-Pole	1492-SJ5A-10		50	1492-SJ5A-10		50
Screw Type Jumper Notching Tool	1492-T1		1	1492-T1		1
Other Accessories:	1492-PPJD3		20	1492-PPJD3		20
Partition Plate						
Marking Systems:	1492-M5X8 (144/card)		5	1492-M5X8 (144/card)		5
Snap-in marker card						
Snap-in marker card	1492-M5X5 (200/card)		5	1492-M5X5 (200/card)		5

* See page 12-97 for component specifications.


Screw Connection Terminal Blocks

Thermocouple Blocks

1492-JTC3...

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	<i>Two circuit terminal block with current bars made of thermocouple material</i>	
Certifications	IEC	ATEX
Voltage Rating	—	55V AC/DC
Wire Range (Rated Cross Section)	#30...12 AWG 2.5 mm ²	#20...14 AWG 2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)	
Recommended Tightening Torque	3.5...5.3 lb•in (0.4...0.6 N•m)	
Density	29 pcs/ft (98 pcs/m)	
Housing Temperature Range	-58...+248 °F (-50...+120 °C)	
Short-Circuit Current Rating	See page 12-42	
Terminal Blocks	Cat. No.	Pkg Qty.
Color/Type/Material		
Gray/Type B/1 S-Copper, 1 E-Copper	1492-JTC3B	50
Gray/Type E/1 Chromel, 1 Constantan	1492-JTC3E	50
Gray/Type J/1 Iron, 1 Constantan	1492-JTC3J	50
Gray/Type K/1 Chromel, 1 Alumel	1492-JTC3K	50
Gray/Type N/1 Ni-Cr-Si, 1 Ni-Si-Mg	1492-JTC3N	50
Gray/Type S/1 E-Copper, 1 A-Copper	1492-JTC3S	50
Gray/Type T/1 E-Copper, 1 Constantan	1492-JTC3T	50
Accessories	Cat. No.	Pkg Qty.
Mounting Rails:		
1 m Symmetrical DIN (Steel)	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2
End Barrier	1492-EBJ3	50
End Anchors and Retainers:		
Screwless End Retainer	1492-ERL35	20
DIN Rail — Normal Duty	1492-EAJ35	100
DIN Rail — Heavy Duty	1492-EAHJ35	50
Other Accessories:		
Partition Plate	1492-EBJ16	20
Marking Systems:		
Snap-in marker cards	1492-M5X12 (144/card)	5
Individual Marker Tabs (Single Char.)	1492-M5X5 (200/card)	5

Screw Connection Terminal Blocks




Neutral Disconnect & Installation Blocks

1492-JDG3ND				1492-JD3N			1492-JDG3N		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	3-Level terminal block with neutral disconnect and ground connection			2-Level feed-through terminal block for installation applications			3-Level terminal block with 2 feed-through and ground connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		400V AC/DC	300V AC/DC		400V AC/DC	300V AC/DC		400V AC/DC
Maximum Current	15 A	10 A	24 A	15 A	10 A	24 A	15 A	10 A	24 A
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm²	#22...12 AWG	#26...12 AWG	2.5 mm²	#22...12 AWG	#26...12 AWG	2.5 mm²
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Recommended Tightening Torque	7.0 lb•in (0.8 N•m)			7.0 lb•in (0.8 N•m)			7.0 lb•in (0.8 N•m)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color: Grey	1492-JDG3ND		50	1492-JD3N		50	1492-JDG3N		50
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2	1492-DR7		2
End Barriers Grey	1492-BSPJLD3N		20	1492-BSPJLD3N		20	1492-BSPJLD3N		20
Busbar Support Plates Blue	1492-BSPJLD3N-B		20	1492-BSPJLD3N-B		20	1492-BSPJLD3N-B		20
End Anchors and Retainers: Screwless End Retainer	1492-ERL35		20	1492-ERL35		20	1492-ERL35		20
End Anchor — Normal Duty	1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100
End Anchor — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50
Jumpers:									
Screw Center Jumper — 10-pole	1492-CJJN6-10		20	1492-CJJN6-10		20	1492-CJJN6-10		20
Screw Center Jumper — 4-pole	1492-CJJN6-4		50	1492-CJJN6-4		50	1492-CJJN6-4		50
Screw Center Jumper — 3-pole	1492-CJJN6-3		50	1492-CJJN6-3		50	1492-CJJN6-3		50
Screw Center Jumper — 2-pole	1492-CJJN6-2		50	1492-CJJN6-2		50	1492-CJJN6-2		50
Other Accessories:									
Test Plug Socket	1492-TPS23		20	1492-TPS23		20	1492-TPS23		20
Test Plug	1492-TP23		20	1492-TP23		20	1492-TP23		20
Neutral Connection Block (4 mm) Blue*	1492-JNC4-B		50	—		—	—		—
Neutral Bus Bar (1 m)	1492-NBB3-1M		5	—		—	—		—
Marking Systems:									
Snap-in Marker Cards	1492-M6X5 (200/card)		5	1492-M6X5 (200/card)		5	1492-M6X5 (200/card)		5

* These terminals mount on the 1492-NBB3-1M Neutral Busbar. They can accept 1492-M6X5 snap-in markers.

Screw Connection Terminal Blocks

Single-Circuit Neutral Disconnect Blocks



	1492-J3ND			1492-J4ND			1492-J16ND		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single-level screw neutral disconnect terminal block			Single-level screw neutral disconnect terminal block			Single-level screw neutral disconnect terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		400V AC/DC	600V AC/DC		400V AC/DC	300V AC/DC		400V AC/DC
Maximum Current	25 A	20 A	24 A	35 A	25 A	32 A	65 A		76 A
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm ²	#22...10 AWG	#26...10 AWG	4 mm ²	#14...6 AWG		16 mm ²
Wire Strip Length	0.394 in. (10 mm)			0.394 in. (10 mm)			0.47 in. (12 mm)		
Recommended Tightening Torque	7.1 lb•in (0.5 N•m)			9.0 lb•in (1.0 N•m)			19.5 lb•in (2.2 N•m)		
Density	59 pcs/ft (196 pcs/m)			49 pcs/f (163 pcs/m)			25 pcs/ft (83 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Blue	1492-J3ND	100		1492-J4ND	100		1492-J16ND	50	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers									
Busbar Support Plates	Blue 1492-BSPJ3ND-B	20		1492-BSPJ3ND-B	20		1492-BSPJ3ND-B	20	
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
End Anchor — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
End Anchor — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Neutral Connection Block (4 mm) Blue*	1492-JNC4-B	50		1492-JNC4-B	50		1492-JNC4-B	50	
Neutral Bus Bar (1 m)	1492-NBB3-1M	5		1492-NBB3-1M	5		1492-NBB3-1M	5	
Marking Systems:	1492-MR5X12 (120/card)	5		1492-MR6X12 (120/card)	5		1492-MR8X12 (84/card)	5	
Snap-in Marker Cards	1492-M5X5 (200/card)	5		1492-M6X5 (200/card)	5		1492-M7X12 (108/card)	5	

* These terminals mount on the 1492-NBB3-1M Neutral Busbar. They can accept 1492-M6X5 snap-in markers.

1492-H...

1492-WFB4...

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications

Single-circuit fusible terminal block with or without fuse indication.

Single-circuit fuse block with or without fuse indication.

Certifications	UL	CSA	IEC	UL	CSA	IEC
H6/WFB4	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC
Voltage Rating	H5/WFB424	10...57V AC/DC		10...57V AC/DC		
	H4/WFB4250	100...300V AC		85...264V AC		
Maximum Current		15 A		15 A		15 A *
Wire Range (Rated Cross Section)		#30...12 AWG	0.5...4 mm ²	#30...12 AWG		0.5...4 mm ²
Wire Strip Length		0.38 in. (9.7 mm)		0.31 in. (8 mm)		
Recommended Tightening Torque		7.1 lb•in (0.8 N•m)		2.65...5.3 lb•in (0.3...0.6 N•m)		
Density		33 pcs/ft (109pcs /m)		38 pcs/ft (125 pcs/m)		
Housing Temperature Range		-40...+195 °F (-40...+90 °C)		-40...+195 °F (-40...+90 °C)		
Indicator Type						
H6/WFB4		Non-Indicating			Non-Indicating	
H5/WFB424		Red LED			Red LED	
H4/WFB4250		Neon			Neon	
Leakage Current						
H6/WFB4		—			—	
H5/WFB424		2 mA @ 24V			2 mA @ 24V	
H4/WFB4250		2 mA @ 300V			2 mA @ 300V	
Fuse Size (Not Supplied)		1/4 x 1-1/4 in.			5 x 20 mm	
Short-Circuit Current Rating		See page 12-42				

Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color: Black No-indication	1492-H6	25	1492-WFB4	50
Black w/LED	1492-H5	25	1492-WFB424	50
Black w/Neon	1492-H4	25	1492-WFB4250	50
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails:				
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2
3 ft Scored A-B Rail	1492-N1	20	—	—
3 ft Rigid A-B Rail	1492-N22	20	—	—
3 ft High Rise A-B Rail	1492-N44	2	—	—
Standoff Brackets (Use Every 12 in.)	1492-N25	2	—	—
End Barrier	1492-N37	50	Not Required	—
End Anchors and Retainers:				
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50
A-B Rail — Heavy Duty	1492-N23	10	—	—
10-Pole Side Jumper *	1492-N49	10	1492-SJFB8-10	10
Side Jumper Insulating Sleeve	1492-SJS	10	—	—
Other Accessories:				
Partition Plate	—	—	1492-PPSL3	50
Marking Systems:				
Snap-In Marker Card — For Base Block	—	5	1492-MS8X12 (56/card)	5
	—	5	1492-MS8X9 (56/card)	5
For Handle	1492-MS8X12 (56/card)	5	1492-MS8X9 (56/card)	5
	1492-MS8X9 (56/card)	5		
Adhesive Labels	1492-ALHFB (50/sheet)	1	1492-ALHFB (50/card)	1

* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.

* Cat. No. 1492-N49 is uninsulated. Cat. No. 1492-SJFB8-10 is insulated.

Screw Connection Terminal Blocks



Fuse Blocks

1492-JD3FB

1492-JDG3FB

Dimensions are not intended to be used for manufacturing purposes.



Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Two-level terminal block with feed-through circuit and hinged-arm fuse circuit			Three-Level terminal block with feed-through circuit, hinged-arm fuse circuit, and ground point		
Certifications		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC
Maximum Fuse Circuit Current	10 A	10 A/250V	6.3 A*	10 A	10 A/250V	6.3 A*
Feed-through Circuit	20 A	25 A		20 A	25 A	
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	0.5...4 mm ²	#22...12 AWG	#26...12 AWG	0.5...4 mm ²
Fuse Size (Not Supplied)	5 x 20 mm			5 x 20 mm		
Wire Strip Length	0.35 in. (9 mm)			0.35 in. (9 mm)		
Recommended Tightening Torque	5.5 lb•in (0.6 N•m)			5.5 lb•in (0.6 N•m)		
Density	38 pcs/ft (125 pcs/m)			38 pcs/ft (125 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42					
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color: Grey	1492-JD3FB		50	1492-JDG3FB		50
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:						
1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2
End Barrier Grey	1492-EBJD3FB		20	1492-EBJD3FB		20
End Anchors:						
Screwless End Retainer	1492-ERL35		20	1492-ERL35		20
DIN Rail - Normal Duty	1492-EAJ35		100	1492-EAJ35		100
DIN Rail - Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50
Jumpers:						
Side Jumper — 4-pole	1492-SJ8A-4		50	1492-SJ8A-4		50
Side Jumper — 3-pole	1492-SJ8A-3		50	1492-SJ8A-3		50
Side Jumper — 2-pole	1492-SJ8A-2		50	1492-SJ8A-2		50
End Anchor Top Marker Carrier*	1492-GMC		50	1492-GMC		50
Cat. No. 1492-GMC Top Marker Tag	1492-M5X30 (20/card)		5	1492-M5X30 (20/card)		5
Marking Systems:						
Snap-in marker cards (Handle)	1492-M7X12 (108/card)		5	1492-M7X12 (108/card)		5
Snap-in marker cards (Handle)	1492-MR6X8 (120/card)		5	1492-MR6X8 (120/card)		5
Snap-in marker cards (Side)	1492-M6X5 (200/card)		5	1492-M6X5 (200/card)		5

* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.

* The Bulletin 1492-GMC marker carrier installs directly on the top of a 1492-EAJ35 end anchor or a 1492-ERL35 end retainer for group marking purposes.

1492-JC3			1492-JDC3			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.						
Specifications	Feed-Through terminal block with 2 plug-in comb connections on one side.		Two Circuit terminal block with plug-in comb connection on one side of each circuit.			
Certifications						
Voltage Rating	300V AC/DC		250V AC/DC	300V AC/DC		250V AC/DC
Maximum Current	20 A	10 A	10 A (2 x 8)	20 A (2 x 10)	24 A	17.5 A
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm²	#22...12 AWG	#26...12 AWG	2.5 mm²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Recommended Tightening Torque	4.5 lb•in (0.5 N•m)			4.5...7.1 lb•in (0.5...0.8 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42					
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color: Grey	1492-JC3		50	1492-JDC3		50
Socket Strips	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color/Quantity	Black/2-Pole	1492-QP5-2	100	Black/2-Pole	1492-QP5-2	100
	Black/3-Pole	1492-QP5-3	100	Black/3-Pole	1492-QP5-3	100
	Black/4-Pole	1492-QP5-4	100	Black/4-Pole	1492-QP5-4	100
	Black/5-Pole	1492-QP5-5	50	Black/5-Pole	1492-QP5-5	50
	Black/6-Pole	1492-QP5-6	50	Black/6-Pole	1492-QP5-6	50
	Black/7-Pole	1492-QP5-7	50	Black/7-Pole	1492-QP5-7	50
	Black/8-Pole	1492-QP5-8	50	Black/8-Pole	1492-QP5-8	50
	Black/9-Pole	1492-QP5-9	50	Black/9-Pole	1492-QP5-9	50
	Black/10-Pole	1492-QP5-10	50	Black/10-Pole	1492-QP5-10	50
	Black/11-Pole	1492-QP5-11	50	Black/11-Pole	1492-QP5-11	50
	Black/12-Pole	1492-QP5-12	50	Black/12-Pole	1492-QP5-12	50
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:						
1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2
Barrier Kit (Start/End)	1492-BKJC3		1★	1492-BKJDC3		1★
End Anchors and Retainers:						
Screwless End Retainer	1492-ERL35		20	1492-ERL35		20
DIN Rail — Normal Duty	1492-EAJ35		100	1492-EAJ35		100
DIN Rail — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50
Jumpers:						
Screw Center Jumper — 10-pole	1492-CJJ5-10		20	—		—
Screw Center Jumper — 4-pole	1492-CJJ5-4		50	—		—
Screw Center Jumper — 3-pole	1492-CJJ5-3		50	—		—
Screw Center Jumper — 2 pole	1492-CJJ5-2		50	—		—
Screw Type Jumper Notching Tool	1492-T1		1	—		—
Other Accessories:						
Open Pin Cover	1492-PCJC3		20	1492-PCJDC3		20
Group Marking Carrier	1492-GM35		25	1492-GM35		25
Marking Systems:						
Snap-in marker cards	1492-M5X12 (144/card)		5	1492-M5X12 (144/card)		5
Individual Marker Tabs (Single Char.)	1492-M5X5 (200/card)		5	1492-M5X5 (200/card)		5

* One kit consists of 10 start barriers and 10 end barriers. Barriers are required on both ends.

Screw Connection Terminal Blocks

Short-Circuit Current Ratings

Fuse Ratings

Cat. No.	Wire Range Cu [AWG]		Overcurrent Protection Fuse Required Class/Max. Current Rating [A]						Maximum Voltage [V]	SCCR, RMS SYM [A]
	Line	Load	J	T	RK1	RK5	G	CC		
1492-J3	14...12	14...12	30	30	—	—	30	30	600	100,000
1492-J3P										
1492-JD3SS										
1492-JD3										
1492-JD3C										
1492-JG3TW										
1492-JDG3C										
1492-JG3										
1492-J3F	14...12	14...12	30	30	—	—	30	30	300	100,000
1492-J3TW										
1492-JC3										
1492-JDC3										
1492-JKD3										
1492-JD3FB										
1492-JD3F										
1492-JDG3FB										
1492-JD3PSSTP										
1492-JD3PTP										
1492-JDG3P										
1492-JDG3PSS										
1492-JDG3PSSTP										
1492-JDG3PTP										
1492-JDG3										
1492-JD3PSS										
1492-JD3P										
1492-J4	14...10	14...10	60	60	30	—	60	30	600	100,000
1492-JG4										
1492-JKD4										
1492-J4TW										
1492-J4Q										
1492-JG4TW										
1492-JG4Q										
1492-JKD4TW										
1492-JKD4Q										
1492-JKD4TP										
1492-JD4C										
1492-JD4										
1492-JKD4QTP										
1492-JKD4TWTP										
1492-JSD4	14...10	14...10	60	60	30	—	60	30	300	100,000
1492-JKD4										
1492-J4CTB										
1492-J6	14...8	14...8	100	100	60	30	60	30	600	100,000
1492-JG6										
1492-J10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-JG10										
1492-J16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-JG16										
1492-J16ND										
1492-J35	12...1/0	12...1/0	200	200	100	30	60	30	600	100,000
1492-JG35										
1492-J50	6...1/0	6...1/0	200	200	100	30	60	30	600	100,000
1492-JG50										
1492-J70	1/0...3/0	1/0...3/0	400	400	200	100	60	30	600	100,000
1492-JG70										
1492-J120	4...4/0	4...4/0	400	400	200	100	60	30	600	100,000
1492-JG120										

Screw Connection Terminal Blocks

Short-Circuit Current Ratings — Overcurrent Ratings

Overcurrent Ratings

Cat. No.	Wire Range Cu [AWG] (Line and Load)	Overcurrent Protection Device Required	Max. Current [A]	SCCR, RMS Sym A 480Y/277V	SCCR, RMS Sym. A 600Y/347V
1492-J3	14...12	140M-D8E-__	16	65,000	30,000
1492-JG3TW		140M-C2E-B10		65,000	30,000
1492-J3P		140M-C2E-B16		65,000	30,000
1492-J3		140M-C2E-B25		65,000	30,000
1492-JD3		140M-C2E-B40		65,000	25,000
1492-JD3C		140M-C2E-B63		65,000	*
1492-JD3SS		140M-C2E-A__		65,000	30,000
1492-JDG3C		140M-C2E-C10		65,000	*
1492-JG3		140MC2E-C16		30,000	*
1492-J4		140M-F8E-__		65,000	30,000
1492-JG4	14...10	140M-D8E-C10	32	65,000	30,000
1492-J4TW		140M-D8E-C16		65,000	30,000
1492-J4Q		140M-D8E-C20		65,000	*
1492-JG4TW		140M-D8E-C25		30,000	*
1492-JG4Q		140M-D8E-B__		65,000	30,000
1492-JKD4TW		140M-C2E-B10		65,000	30,000
1492-JKD4Q		140M-C2E-B16		65,000	30,000
1492-JKD4TP		140M-C2E-B25		65,000	30,000
1492-JD4C		140M-C2E-B40		65,000	25,000
1492-JD4		140M-C2E-B63		65,000	*
1492-JKD4QTP		140M-C2E-C10		65,000	*
1492-JKD4TWTP		140M-C2E-C16		30,000	*
		140M-C2E-A__		65,000	30,000
1492-J6	14...8	140M-F8E-__	32	65,000	30,000
1492-JG6		140M-D8E-C10		65,000	30,000
		140M-D8E-C16		65,000	30,000
		140M-D8E-C20		65,000	*
		140M-D8E-C25		30,000	*
		140M-D8E-B__		65,000	30,000
		140M-C2E-B10		65,000	30,000
		140M-C2E-B16		65,000	30,000
		140M-C2E-B25		65,000	30,000
		140M-C2E-B40		65,000	25,000
		140M-C2E-B63		65,000	*
		140M-C2E-C10		65,000	*
		140M-C2E-C16		30,000	*
		140M-C2E-A__		65,000	30,000

* Bulletin 140M does not have ratings at this voltage.

Screw Connection Terminal Blocks

Short-Circuit Current Ratings — Overcurrent Ratings

Cat. No.	Wire Range Cu [AWG] (Line and Load)	Overcurrent Protection Device Required	Max. Current [A]	SCCR, RMS Sym A 480Y/277V	SCCR, RMS Sym. A 300V+	
1492-J3TW	14...12	140M-D8E-__	16	65,000	30,000	
1492-JC3		140M-C2E-B10		65,000	30,000	
1492-JDC3		140M-C2E-B16		65,000	30,000	
1492-J3F		140M-C2E-B25		65,000	30,000	
1492-JD3F		140M-C2E-B40		65,000	25,000	
1492-JKD3		140M-C2E-B63		65,000	*	
1492-JD3FB		140M-C2E-A__		65,000	30,000	
1492-JDG3FB		140M-C2E-C10		65,000	*	
1492-JD3PSSTP		140MC2E-C16		30,000	*	
1492-JD3PTP						
1492-JDG3P						
1492-JDG3PSS						
1492-JDG3PSSTP						
1492-JDG3PTP						
1492-JDG3						
1492-JD3P						
1492-JD3PSS						
1492-JKD4	14...10	140M-F8E-__	32	65,000	30,000	
1492-JSD4		140M-D8E-C10		65,000	30,000	
1492-J4CTB		140M-D8E-C16		65,000	30,000	
		140M-D8E-C20		65,000	*	
		140M-D8E-C25		30,000	*	
		140M-D8E-B__		65,000	30,000	
		140M-C2E-B10		65,000	30,000	
		140M-C2E-B16		65,000	30,000	
		140M-C2E-B25		65,000	30,000	
		140M-C2E-B40		65,000	25,000	
		140M-C2E-B63		65,000	*	
		140M-C2E-C10		65,000	*	
		140M-C2E-C16		30,000	*	
		140M-C2E-A__		65,000	30,000	

Cat. No.	Wire Range Cu [AWG] (Line and Load)	Overcurrent Protection Device Required	Max. Current [A]	SCCR, RMS Sym A 480V+	SCCR, RMS Sym. A 600Y 347V+
1492-J10	14...10	140M-H8P-__	50	50,000	30,000
1492-JG10					
1492-J16	14...4	140M-H8P-__	100	30,000	30,000
1492-JG16					
1492-J16ND	12...2	140M-H8P-__	100	50,000	30,000
1492-J35					
1492-JG35	2...1/0	140M-H8P-__	150	65,000	30,000
1492-J50					
1492-JG50					

Cat. No.	Wire Range Cu [AWG] (Line and Load)	Overcurrent Protection Device Required	Max. Current [A]	SCCR, RMS Sym A 480V+	SCCR, RMS Sym. A 600V+
1492-J70	4...1/0	140U-J0X3	175	65,000	*
	1/0	140U-J0X3		*	30,000
1492-J120	2...3/0	140U-J0X3	228	65,000	30,000

* Bulletin 140M does not have ratings at this voltage.

+ Voltage terminal block was tested at for respective SCCR

Allen-Bradley spring-clamp terminal blocks generally have been designed to meet the requirements of one or more regulatory bodies. Most products have also been tested per additional standards. The following is a listing of some of the regulatory bodies and standards which apply to Allen-Bradley spring-clamp terminal block products. See the particular product description for information on specific certifications and ratings.



(Underwriters Laboratories) — Allen-Bradley spring-clamp terminal blocks with one of these ratings have been tested by Underwriters Laboratories and meet the requirements of one or more of the following United States Standards:

- UL 486E — Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors
- UL 1059 — Standard for Terminal Blocks

Reference UL file E40735



(Underwriters Laboratories) — Allen-Bradley spring-clamp terminal blocks with this rating have been tested by Underwriters Laboratories and meet the requirements of one or more of the following Canadian Standards:

- CSA 22.2 No. 158 — Terminal Blocks

Reference UL file E40735



(Canadian Standards Association) — Allen-Bradley spring-clamp terminal blocks with this rating have been tested by the Canadian Standards Association and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference CSA files 677896



Allen-Bradley spring-clamp terminal blocks listed in this catalog meet the requirements of the Low Voltage Directive put forth by the European Union. Devices have been tested and comply with one or more of the following European Norms:

- EN 60947-1 — Low Voltage Switchgear and Controlgear: General Rules
- EN 60947-7-1 — Low Voltage Switchgear and Controlgear: Terminal Blocks for Copper Conductors
- EN 60947-7-2 — Low Voltage Switchgear and Controlgear: Protective Conductor Terminal Blocks for Copper Conductors
- EN 60947-7-3 — Low Voltage Switchgear and Controlgear: Safety Requirements for Fuse Terminal Blocks



ATEX — Devices listed in this catalog with “ATEX” ratings meet the following European Norms per DEMKO or KEMA, Approval Certification Bodies for the European Union:

- EN 60079-0 — Electrical Apparatus for Potentially Explosive Atmospheres — General Requirements
- EN 60079-7 — Electrical Apparatus for Potentially Explosive Atmospheres — Increased Safety “e”

Contact your local Allen-Bradley distributor for a copy of the certificate.

Ex e II — Bulletin 1492-L terminal blocks in this catalog meet the following Canadian Standards per Underwriters Laboratories:

- CAN/CSA E60079-7 — Electrical Apparatus for Explosive Atmospheres — Part 0 — General Requirements
- CAN/CSA E60079-0 — Electrical Apparatus for Explosive Atmospheres — Part 7 — Increased Safety “e”

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

AEx e II — Allen-Bradley spring-clamp terminal blocks with an “AEx e II” rating meet the following United States Standard per Underwriters Laboratories:

- UL 2279 — Standard for Electrical Equipment for Use in Class I, Zone 0, 1, and 2 Hazardous (Classified) Locations

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

Lloyd's Register — Bulletin 1492-L terminal blocks in this catalog have been certified for use in marine, off-shore, and industrial installations per the following standard:

- Lloyd's Register Test Specification No. 1:1996

Contact your local Allen-Bradley distributor for a copy of the certificate.

Spring-Clamp Connection Terminal Blocks

Introduction

The Allen-Bradley Line of Spring-Clamp Terminal Blocks...

The Bulletin 1492-L line of internationally approved spring-clamp IEC-style terminal blocks offers a variety of products that can make any application:


- **Fast** — Reduces wiring time by more than 50%
- **Practical** — Requires only a flat-head screwdriver for easy installation. Maintenance-free, no need to retighten
- **Reliable** — Secure contact is durable under extreme conditions such as high-vibration applications

Products Available in the 1492-L Spring-Clamp Line

- **Feed-Through Blocks**, accommodating wire sizes from #30...#2 AWG (0.2...35 mm²)
- **Grounding Blocks** for grounding a given circuit to the DIN Rail
- **Multi-Circuit Blocks** for doubling circuit wiring density
- **Isolation Blocks** for circuit isolation during testing and troubleshooting
- **Plug-In Style Terminal Blocks** accommodating component plugs, fuse plugs, and disconnect plugs
- **Sensor Blocks** for coordination of three-wire sensor groups with or without ground terminations
- **Electrical Component Blocks** which allow for the insertion of fixed components into control circuits. Components include diodes and surge suppression circuits

Tie-Point Block


(Cat. Nos. 1492-LD2C, LD3C, LD4C)



Diode Block

(Cat. Nos. 1492-LD4DF, 1492-LD4DR)


Uses a 1N4007 diode between the upper and lower levels for insertion into a control circuit. This block is useful in low voltage DC control circuits for directioning and suppression.



Surge Suppression Block

(Cat. No. 1492-LD4SS)

Provides a convenient means of incorporating transient suppression for relays, contactors and solenoids into a control system.



- **Test Blocks** for allowing a bank of pluggable terminal strips to be easily connected for test purposes
- A wide variety of snap-in markers are available for individual or group circuit identification
- A broad offering of accessories such as screwless end retainers, electrical warning plates, end barriers, protective stops and test plugs to provide exactly what the application requires
- Operating instructions (printed on an adhesive label), for fixing inside a panel
- **Mini-blocks** available in rail-mount or panel-mount configurations

Materials and Design Features

The 1492-L line is specially designed for safety, installation ease, and ruggedness. Features include:

- Tin-plated terminals and stainless steel spring clamps for resistance to corrosion and vibration
- Spring clamp design to minimize stress relaxation and maintain contact force, even under vibration
- Top wire entry for ease of installation
- Circuit testing with standard 2 mm diameter test probe or stackable test plugs on most spring-clamp blocks
- Insulation stops to ensure electrical connection when using smaller gauge wires
- Markers that are visible after terminal blocks are wired
- Multiple marking options
- Common profiles to minimize stocking of accessories
- Self-extinguishing, polyimide 6.6 housing materials with a flammability rating UL 94-V0 (1492-R terminal blocks have a UL 94-V2 flammability rating)
- Screwless center jumpers to simplify jumpering terminals together


Note: To ensure proper wire termination, these blocks are designed to accept only **one** wire per terminal.

www.ab.com/catalogs Preferred availability cat. nos. are **bold**.


Spring-Clamp Connection Terminal Blocks

Mini-Blocks with Center Jumper Option

1492-LMJ3



1492-LMJG3



Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.

Specifications

Mini rail-mount, feed-through terminal block with jumper capability

Mini rail-mount grounding terminal block

Certifications		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	600V AC/DC			500V AC/DC	275V AC/DC	—	—
Maximum Current	20 A			24 A	20 A	Grounding	
Wire Range (Rated Cross Section)	#26...12 AWG			2.5 mm²	#20...12 AWG	#26...12 AWG	2.5 mm²
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Color	Grey	1492-LMJ3			100	—	—
	Blue	1492-LMJ3-B			100	—	—
	Green/Yellow	—			—	1492-LMJG3	100
Accessories	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails 1 m Symmetrical DIN (Steel)	1492-DR3			5	1492-DR3		5
Screwless End Retainer	Grey	1492-ERL15			20	1492-ERL15	20
End Anchor	Grey	1492-EAJ15			50	1492-EAJ15	50
Jumpers	1492-CJLJ5-50			10	—		—
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-10			20	—		—
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-9			20	—		—
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-8			20	—		—
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-7			20	—		—
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-6			20	—		—
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-5			20	—		—
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-4			60	—		—
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-3			60	—		—
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-2			60	—		—
Plug-in Center Jumper — 2-Pole	1492-SJLM5-2			50	—		—
Side Jumper — 2-Pole	1492-TAL5-2			1	—		—
Side Jumper Installation Tool	1492-EBLMJ3			50	1492-EBLMJ3		50
End Barriers	Grey	1492-EBLMJ3-B			50	1492-EBLMJ3-B	50
	Blue	1492-EBLMJ3-Y			50	1492-EBLMJ3-Y	50
	Yellow	1492-SM5X10 (144/card)			5	1492-SM5X10 (144/card)	5
Marking Systems	1492-M5X5 (200/card)			5	1492-M5X5 (200/card)		5
Snap-in Marker Cards	1492-MH5X10 (96/card)			5	1492-MH5X10 (96/card)		5
Snap-In Marker Cards*							
Hinged marker cards*							

* Markers can be installed over center jumper channel, with or without center jumper installed.

Spring-Clamp Connection Terminal Blocks



Mini-Blocks, Interlocking, 600V UL Rated

	1492-LM3			1492-LM3Q			1492-LMG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Mini rail-mount, feed-through terminal block			Mini rail-mount, feed-through terminal block with 2 connection points on each side			Mini rail-mount grounding terminal block		
Certifications									
Voltage Rating	600V AC/DC			600V AC/DC			—		
Maximum Current	20 A	25 A	24 A	20 A	25 A	24 A	Grounding		
Wire Range (Rated Cross Section)	#26...12 AWG 2.5 mm ²			#26...12 AWG 2.5 mm ²			#26...12 AWG 2.5 mm ²		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)			30 pcs/ft (99 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-LM3		100	1492-LM3Q	100	—	—	
	Blue	1492-LM3-B		100	1492-LM3Q-B	100	—	—	
	Green/Yellow	—		—	—	—	1492-LMG3	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails 1 m Symmetrical Mini DIN (Steel)	1492-DR3	5		1492-DR3	5		1492-DR3	5	
Screwless End Retainer	Grey	1492-ERL15	20	1492-ERL15	20	1492-ERL15	1492-ERL15	20	20
End Anchor	Grey	1492-EAJ15	50	1492-EAJ15	50	1492-EAJ15	1492-EAJ15	50	50
Jumpers									
Side Jumper — 2-Pole		1492-SJLM5-2	50	1492-SJLM5-2	50	—	—	—	—
Side Jumper Installation Tool		1492-TAL5-2	1	1492-TAL5-2	1	—	—	—	—
End Barriers	Grey	1492-EBLM3	50	1492-EBLM3	50	1492-EBLM3	1492-EBLM3	50	50
	Blue	1492-EBLM3-B	50	1492-EBLM3-B	50	1492-EBLM3-B	1492-EBLM3-B	50	50
	Yellow	1492-EBLM3-Y	50	1492-EBLM3-Y	50	1492-EBLM3-Y	1492-EBLM3-Y	50	50
Marking Systems									
Snap-In Marker Cards		1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	1492-M5X10 (144/card)	5	5
Snap-In Marker Cards		1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	1492-M5X5 (200/card)	5	5
Hinged Marker Cards		1492-MH5X10 (96/card)	5	1492-MH5X10 (96/card)	5	1492-MH5X10 (96/card)	1492-MH5X10 (96/card)	5	5

Bulletin 1492

Spring-Clamp Connection Terminal Blocks

Mini-Blocks, Panel Mount




	1492-LMP3 ❄			1492-LMP3Q ❄		
Dimensions are not intended to be used for manufacturing purposes. Note: One end block and one end barrier or two end barriers must be used on each end of a terminal bank to provide mounting slots.						
Specifications	<i>Mini surface mount feed-through terminal block</i>			<i>Mini surface mount, feed-through terminal block with 2 connection points on each side</i>		
Certifications		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		800V AC/DC	600V AC/DC		800V AC/DC
Maximum Current	20 A	25 A	24 A	20 A	25 A	24 A
Wire Range (Rated Cross Section)	#26...12 AWG		2.5 mm ²	#26...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)			30 pcs/ft (99 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Color	Grey	1492-LMP3	100		1492-LMP3Q	100
	Blue	1492-LMP3-B	100		1492-LMP3Q-B	100
End Terminal Blocks (with Mounting Brackets)						
Color	Grey	1492-LMP3E	50		1492-LMP3QE	50
	Blue	1492-LMP3E-B	50		1492-LMP3QE-B	50
Accessories		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Mounting Foot❄		1492-MFLM	50		1492-MFLM	50
Jumpers						
Side Center Jumper — 2-Pole		1492-SJLM5-2	50		1492-SJLM5-2	50
Side Jumper Installation Tool		1492-TAL5-2	1		1492-TAL5-2	1
End Barriers (with Mounting Slots)	Grey	1492-EBLMP3	50		1492-EBLMP3	50
	Blue	1492-EBLMP3-B	50		1492-EBLMP3-B	50
Marking Systems						
Snap-In Marker Cards		1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5
Snap-In Marker Cards		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5
Hinged Marker Cards		1492-MH5X10 (96/card)	5		1492-MH5X10 (96/card)	5

❄ For a grouping of terminal blocks, use 1 end terminal block, select the number of terminal blocks, and use 1 end barrier. You can also use a group of terminal blocks with an end barrier on each end.

* Allows mounting to 15 mm and 35 mm DIN Rail. Recommended spacing is every fifth block on Cat. No. 1492-LMP3 and every third block on Cat. No. 1492-LMP3Q.




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L2				1492-L2T				1492-L2Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block with 2 connection points per side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	300V AC/DC		500V AC/DC	550V AC/DC	300V AC/DC		500V AC/DC	550V AC/DC	300V AC/DC		500V AC/DC	550V AC/DC
Maximum Current	15 A	20 A	17.5 A	15 A	15 A	20 A	17.5 A	15 A	15 A	20 A	17.5 A	15 A
Wire Range (Rated Cross Section)	#26...14 AWG		1.5 mm ²	1.5 mm ²	#26...14 AWG		1.5 mm ²	1.5 mm ²	#26...14 AWG		1.5 mm ²	1.5 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color	Grey		1492-L2		50	1492-L2T		50	1492-L2Q		50	
	Red		1492-L2-RE		50	1492-L2T-RE		50	1492-L2Q-RE		50	
	Blue		1492-L2-B		50	1492-L2T-B		50	1492-L2Q-B		50	
	Black		1492-L2-BL		50	1492-L2T-BL		50	1492-L2Q-BL		50	
	Green		1492-L2-G		50	1492-L2T-G		50	1492-L2Q-G		50	
	Yellow		1492-L2-Y		50	1492-L2T-Y		50	1492-L2Q-Y		50	
	Orange		1492-L2-OR		50	1492-L2T-OR		50	1492-L2Q-OR		50	
	Brown		1492-L2-BR		50	1492-L2T-BR		50	1492-L2Q-BR		50	
	White		1492-L2-W		50	1492-L2T-W		50	1492-L2Q-W		50	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails	1 m Symmetrical DIN (Steel)		199-DR1		10	199-DR1		10	199-DR1		10	
	1 m Symmetrical DIN (Aluminum)		1492-DR5		10	1492-DR5		10	1492-DR5		10	
	1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2	1492-DR6		2	1492-DR6		2	
	1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2	1492-DR7		2	1492-DR7		2	
End Barriers	Grey		1492-EBL2		50	1492-EBL2T		50	1492-EBL2Q		50	
	Blue		1492-EBL2-B		50	1492-EBL2T-B		50	1492-EBL2Q-B		50	
	Yellow		1492-EBL2-Y		50	1492-EBL2T-Y		50	1492-EBL2Q-Y		50	
End Anchors and Retainers	1492-ERL35		20		1492-ERL35	20		1492-ERL35	20		20	
Screwless End Retainer	1492-EAJ35		100		1492-EAJ35	100		1492-EAJ35	100		100	
DIN Rail — Normal Duty	1492-EAHJ35		50		1492-EAHJ35	50		1492-EAHJ35	50		50	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35	50		1492-EAHJ35	50		50	
Jumpers	1492-CJL4-10		20		1492-CJL4-10	20		1492-CJL4-10	20		20	
Plug-in Center Jumper — 10-Pole	1492-CJL4-5		60		1492-CJL4-5	60		1492-CJL4-5	60		60	
Plug-in Center Jumper — 5-Pole	1492-CJL4-4		60		1492-CJL4-4	60		1492-CJL4-4	60		60	
Plug-in Center Jumper — 4-Pole	1492-CJL4-3		60		1492-CJL4-3	60		1492-CJL4-3	60		60	
Plug-in Center Jumper — 3-Pole	1492-CJL4-2		60		1492-CJL4-2	60		1492-CJL4-2	60		60	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2		60		1492-CJL4-2	60		1492-CJL4-2	60		60	
Other Accessories	1492-PSL2-2		100		1492-PSL2-2	100		1492-PSL2-2	100		100	
Reducing Sleeves #28...#24 AWG (0.13...0.2 mm ²) White	1492-PSL2-5		100		1492-PSL2-5	100		1492-PSL2-5	100		100	
Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey	1492-TPL4		25		1492-TPL4	25		1492-TPL4	25		25	
Test Plug (Stackable)	1492-EWPL4		20		1492-EWPL4	20		1492-EWPL4	20		20	
Electrical Warning Plate	1492-M3X12 (120/card)		5		1492-M3X12 (120/card)	5		1492-M3X12 (120/card)	5		5	
Marking Systems	1492-M3X5 (100/card)		5		1492-M3X5 (100/card)	5		1492-M3X5 (100/card)	5		5	
Snap-In Marker Cards	1492-M3X5 (100/card)		5		1492-M3X5 (100/card)	5		1492-M3X5 (100/card)	5		5	




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L3				1492-L3T				1492-L3Q					
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.														
Specifications	Feed-through terminal block				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 2 points on each side					
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX		
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC		
Maximum Current	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A		
Wire Range (Rated Cross Section)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)		
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)					
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating (SCCR)	See page 12-78													
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.			
Color	Grey		1492-L3		100		1492-L3T		100		1492-L3Q		100	
	Red		1492-L3-RE		100		1492-L3T-RE		100		1492-L3Q-RE		100	
	Blue		1492-L3-B		100		1492-L3T-B		100		1492-L3Q-B		100	
	Black		1492-L3-BL		100		1492-L3T-BL		100		1492-L3Q-BL		100	
	Green		1492-L3-G		100		1492-L3T-G		100		1492-L3Q-G		100	
	Yellow		1492-L3-Y		100		1492-L3T-Y		100		1492-L3Q-Y		100	
	Orange		1492-L3-OR		100		1492-L3T-OR		100		1492-L3Q-OR		100	
	Brown		1492-L3-BR		100		1492-L3T-BR		100		1492-L3Q-BR		100	
	White		1492-L3-W		100		1492-L3T-W		100		1492-L3Q-W		100	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.			
Mounting Rails	199-DR1		10		199-DR1		10		199-DR1		10			
1 m Symmetrical DIN (Steel)	1492-DR5		10		1492-DR5		10		1492-DR5		10			
1 m Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2			
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR7		2		1492-DR7		2		1492-DR7		2			
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-EBL3		50		1492-EBL3T		50		1492-EBL3Q		50			
End Barriers	Grey		1492-EBL3-B		50		1492-EBL3T-B		50		1492-EBL3Q-B		50	
	Blue		1492-EBL3-Y		50		1492-EBL3T-Y		50		1492-EBL3Q-Y		50	
	Yellow		1492-EBL35		20		1492-EBL35		20		1492-EBL35		20	
End Anchors and Retainers	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100			
Screwless End Retainer	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50			
DIN Rail — Normal Duty	1492-CJK5-50		10		1492-CJK5-50		10		1492-CJK5-50		10			
Plug-in Center Jumper — 50-Pole	1492-CJK5-10		20		1492-CJK5-10		20		1492-CJK5-10		20			
Plug-in Center Jumper — 10-Pole	1492-CJK5-9		20		1492-CJK5-9		20		1492-CJK5-9		20			
Plug-in Center Jumper — 9-Pole	1492-CJK5-8		20		1492-CJK5-8		20		1492-CJK5-8		20			
Plug-in Center Jumper — 8-Pole	1492-CJK5-7		20		1492-CJK5-7		20		1492-CJK5-7		20			
Plug-in Center Jumper — 7-Pole	1492-CJK5-6		20		1492-CJK5-6		20		1492-CJK5-6		20			
Plug-in Center Jumper — 6-Pole	1492-CJK5-5		20		1492-CJK5-5		20		1492-CJK5-5		20			
Plug-in Center Jumper — 5-Pole	1492-CJK5-4		60		1492-CJK5-4		60		1492-CJK5-4		60			
Plug-in Center Jumper — 4-Pole	1492-CJK5-3		60		1492-CJK5-3		60		1492-CJK5-3		60			
Plug-in Center Jumper — 3-Pole	1492-CJK5-2		60		1492-CJK5-2		60		1492-CJK5-2		60			
Plug-in Center Jumper — 2-Pole	1492-PSL3-2		100		1492-PSL3-2		100		1492-PSL3-2		100			
Other Accessories	1492-PSL3-5		100		1492-PSL3-5		100		1492-PSL3-5		100			
Reducing Sleeves #30...#24 AWG (0.13...0.2 mm ²) White	1492-PSL3-10		100		1492-PSL3-10		100		1492-PSL3-10		100			
Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey	1492-TP23		20		1492-TP23		20		1492-TP23		20			
Test Plug	1492-TPL5		25		1492-TPL5		25		1492-TPL5		25			
Test Plug (Stackable)	1492-EWPL5		20		1492-EWPL5		20		1492-EWPL5		20			
Electrical Warning Plate	1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5			
Marking Systems	1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5			
Snap-In Marker Cards	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5			
Hinged Marker Cards	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5			
Hinged Marker Cards	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5			




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L4				1492-L4T				1492-L4Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 2 connection points on each side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	33 A	35 A	32 A	28 A	33 A	35 A	32 A	28 A	33 A	35 A	32 A	28 A
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)
Wire Strip Length	0.47 in. (12 mm)				0.47 in. (12 mm)				0.47 in. (12 mm)			
Density	49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-78											
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color	Grey	1492-L4		50	1492-L4T			50	1492-L4Q			50
	Red	1492-L4-RE		50	1492-L4T-RE			50	1492-L4Q-RE			50
	Blue	1492-L4-B		50	1492-L4T-B			50	1492-L4Q-B			50
	Black	1492-L4-BL		50	1492-L4T-BL			50	1492-L4Q-BL			50
	Green	1492-L4-G		50	1492-L4T-G			50	1492-L4Q-G			50
	Yellow	1492-L4-Y		50	1492-L4T-Y			50	1492-L4Q-Y			50
	Orange	1492-L4-OR		50	1492-L4T-OR			50	1492-L4Q-OR			50
	Brown	1492-L4-BR		50	1492-L4T-BR			50	1492-L4Q-BR			50
	White	1492-L4-W		50	1492-L4T-W			50	1492-L4Q-W			50
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails												
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2
End Barriers	Grey	1492-EBL4		50	1492-EBL4T			50	1492-EBL4Q			50
	Blue	1492-EBL4-B		50	1492-EBL4T-B			50	1492-EBL4Q-B			50
	Yellow	1492-EBL4-Y		50	1492-EBL4T-Y			50	1492-EBL4Q-Y			50
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50
Jumpers:												
Plug-in Center Jumper — 10-Pole	1492-CJK6-10			20	1492-CJK6-10			20	1492-CJK6-10			20
Plug-in Center Jumper — 9-Pole	1492-CJK6-9			20	1492-CJK6-9			20	1492-CJK6-9			20
Plug-in Center Jumper — 8-Pole	1492-CJK6-8			20	1492-CJK6-8			20	1492-CJK6-8			20
Plug-in Center Jumper — 7-Pole	1492-CJK6-7			20	1492-CJK6-7			20	1492-CJK6-7			20
Plug-in Center Jumper — 6-Pole	1492-CJK6-6			20	1492-CJK6-6			20	1492-CJK6-6			20
Plug-in Center Jumper — 5-Pole	1492-CJK6-5			20	1492-CJK6-5			20	1492-CJK6-5			20
Plug-in Center Jumper — 4-Pole	1492-CJK6-4			60	1492-CJK6-4			60	1492-CJK6-4			60
Plug-in Center Jumper — 3-Pole	1492-CJK6-3			60	1492-CJK6-3			60	1492-CJK6-3			60
Plug-in Center Jumper — 2-Pole	1492-CJK6-2			60	1492-CJK6-2			60	1492-CJK6-2			60
Other Accessories												
Reducing Sleeves #26...#24 AWG (0.13...0.2 mm ²) White	1492-PSL4-2			100	1492-PSL4-2			100	1492-PSL4-2			100
Reducing Sleeves #20...#22 AWG (0.25...0.5 mm ²) Grey	1492-PSL4-5			100	1492-PSL4-5			100	1492-PSL4-5			100
Reducing Sleeves #18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL4-10			100	1492-PSL4-10			100	1492-PSL4-10			100
Test Plug	1492-TP23			20	1492-TP23			20	1492-TP23			20
Test Plug (Stackable)	1492-TPL6			25	1492-TPL6			25	1492-TPL6			25
Electrical Warning Plate	1492-EWPL6			20	1492-EWPL6			20	1492-EWPL6			20
Marking Systems												
Snap-In Marker Cards	1492-M6X10 (120/card)			5	1492-M6X10 (120/card)			5	1492-M6X10 (120/card)			5
Snap-In Marker Cards	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5
Hinged Marker Cards	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5

Spring-Clamp Connection Terminal Blocks




Standard Feed-Through Blocks

	1492-L6				1492-L6T				1492-L10				
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.													
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block				
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX	
Voltage Rating	600V AC/DC			800V AC/DC	600V AC/DC			800V AC/DC	600V AC/DC			800V AC/DC	
Maximum Current	50 A			41 A	50 A			41 A	60 A			55 A	
Wire Range (Rated Cross Section)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...8 AWG)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	#16...6 AWG		10 mm ²	10 mm ² (16...8 AWG)	
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				0.70 in. (18 mm)				
Density	37 pcs/ft (123 pcs/m)				37 pcs/ft(123 pcs/m)				30 pcs/ft (99 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating	See page 12-78												
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	
Color	Grey			1492-L6	50	1492-L6T			50	1492-L10			25
	Red			1492-L6-RE	50	1492-L6T-RE			50	1492-L10-RE			25
	Blue			1492-L6-B	50	1492-L6T-B			50	1492-L10-B			25
	Black			1492-L6-BL	50	1492-L6T-BL			50	1492-L10-BL			25
	Green			1492-L6-G	50	1492-L6T-G			50	1492-L10-G			25
	Yellow			1492-L6-Y	50	1492-L6T-Y			50	1492-L10-Y			25
	Orange			1492-L6-OR	50	1492-L6T-OR			50	1492-L10-OR			25
	Brown			1492-L6-BR	50	1492-L6T-BR			50	1492-L10-BR			25
	White			1492-L6-W	50	1492-L6T-W			50	1492-L10-W			25
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	
Mounting Rails													
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10	
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2	
End Barriers	Grey	1492-EBL6		50	Grey	1492-EBL6T		50	Grey	1492-EBL10		20	
	Blue	1492-EBL6-B		50	Blue	1492-EBL6T-B		50	Blue	1492-EBL10-B		20	
	Yellow	1492-EBL6-Y		50	Yellow	1492-EBL6T-Y		50	Yellow	1492-EBL10-Y		20	
End Anchors and Retainers													
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20	
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100	
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50	
Jumpers													
Plug-in Center Jumper — 32-Pole	1492-CJL8-32			10	1492-CJL8-32			10	—			—	
Plug-in Center Jumper — 4-Pole	1492-CJL8-4			60	1492-CJL8-4			60	—			—	
Plug-in Center Jumper — 3-Pole	1492-CJL8-3			60	1492-CJL8-3			60	—			—	
Plug-in Center Jumper — 2-Pole	1492-CJL8-2			60	1492-CJL8-2			60	1492-CJL10-2			25	
Other Accessories													
Test Plug	—			—	—			—	1492-TP23			20	
Test Plug (Stackable)	1492-TPL8			25	1492-TPL8			25	—			—	
Electrical Warning Plate	1492-EWPL8			20	1492-EWPL8			20	1492-EWPL10			20	
Marking Systems													
Snap-In Marker Cards*	1492-M6X12 (120/card)			5	1492-M6X12 (120/card)			5	1492-M6X12 (120/card)			5	
Snap-In Marker Cards	1492-MR8X12 (84/card)			5	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5	
Hinged Marker Cards	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5	1492-MH5X15 (96/card)			5	

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

1492-L16					1492-L16D*					1492-L35				
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.														
	Feed-through terminal block				Power distribution block with center jumper connection/feed				Feed-through terminal block					
Certifications	UL	CSA	IEC	ATEX	UL	CSA	IEC		UL	CSA	IEC	ATEX		
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		500V AC/DC		600V AC/DC		800V AC/DC	690V AC/DC		
Maximum Current	65 A		76 A	66 A	65 A		76 A		120 A		125 A	109 A		
Wire Range (Rated Cross Section)	#14...4 AWG		16 mm ²	16 mm ² (16... 6 AWG)	#14...4 AWG		16 mm ²		#12...2 AWG		35 mm ²	35 mm ² 14...2 AWG		
Wire Strip Length	0.70 in. (18 mm)				0.70 in. (18 mm)				0.98 in. (25 mm)					
Density	25 pcs/ft (82 pcs/m)				20 pcs/ft (66 pcs/m)				18 pcs/ft (62 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating	See page 12-78													
Terminal Blocks		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			
Color	Grey	1492-L16	25			1492-L16D*	20			1492-L35	10			
	Red	1492-L16-RE	25			—	—			1492-L35-RE	10			
	Blue	1492-L16-B	25			—	—			1492-L35-B	10			
	Black	1492-L16-BL	25			—	—			1492-L35-BL	10			
	Green	1492-L16-G	25			—	—			1492-L35-G	10			
	Yellow	1492-L16-Y	25			—	—			1492-L35-Y	10			
	Orange	1492-L16-OR	25			—	—			1492-L35-OR	10			
	Brown	1492-L16-BR	25			—	—			1492-L35-BR	10			
	White	1492-L16-W	25			—	—			1492-L35-W	10			
Accessories		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			
Mounting Rails														
1 m Symmetrical DIN (Steel)		199-DR1	10			199-DR1	10			199-DR1	10			
1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)		199-DR4	5			199-DR4	5			199-DR4	5			
1 m Symmetrical DIN (Aluminum)		1492-DR5	10			1492-DR5	10			1492-DR5	10			
1 m Hi-Rise Symmetrical DIN (Aluminum)		1492-DR6	2			1492-DR6	2			1492-DR6	2			
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2			1492-DR7	2			1492-DR7	2			
1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)		1492-DR8	5			1492-DR8	5			1492-DR8	5			
1 m Symmetrical Heavy Duty DIN (Steel Slotted)		1492-DR9	5			1492-DR9	5			1492-DR9	5			
End Barriers	Grey	1492-EBL16	20		Integrated to Block		—		Integrated to Block		—			
	Blue	1492-EBL16-B	20		—		—		—		—			
	Yellow	1492-EBL16-Y	20		—		—		—		—			
End Anchors and Retainers														
Screwless End Retainer		1492-ERL35	20			1492-ERL35	20			1492-ERL35	20			
DIN Rail — Normal Duty		1492-EAJ35	100			1492-EAJ35	100			1492-EAJ35	100			
DIN Rail — Heavy Duty		1492-EAHJ35	50			1492-EAHJ35	50			1492-EAHJ35	50			
Jumpers														
Plug-in Center Jumper — 2-Pole		1492-CJL12-2	25			⚡	—			1492-CJL16-2	10			
Other Accessories														
Test Plug		1492-TP23	20			1492-TP23	20			1492-TP23	20			
Test Adapter		—	—			—	—			—	—			
Electrical Warning Plate		1492-EWPL12	20			1492-EWPL12	20			1492-EWPL16	20			
Marking Systems														
Snap-In Marker Cards‡		1492-M7X12 (108/card)	5			1492-M7X12 (108/card)	5			1492-M7X12 (108/card)	5			
Snap-In Marker Cards		1492-M8X5 (160/card)	5			1492-M8X5 (160/card)	5			1492-M8X5 (160/card)	5			
Hinged Marker Cards		1492-MH5X15 (96/card)	5			1492-MH5X15 (96/card)	5			1492-MH5X15 (96/card)	5			

* Can be electrically connected through center jumper for power distribution to 1492 - L3, L3Q, L4, L4T, L4Q, L6, and L6T terminal blocks. See page 12-55 for distribution guidelines.

⚡ Use defined center jumper for standard terminal blocks when connecting for power distribution.

‡ May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Power Distribution Blocks

Feed Left:





Feed Right:



The Cat. No. 1492-L16D feed terminal allows wires with a cross section from 4...14 AWG and up to 16 mm² to be used. Using standard cross connections, the potential can be distributed to any number of terminals with smaller cross sections. The following tables show some variants for potential distribution of the supply, the required cross connection, and the maximum current. The maximum current for the single terminal block must not be exceeded.

Feed Middle:






Feed Left				Feed Middle				Feed Right			
Feed Terminal	Feed	I_{max}	Jumper	Feed Terminal	Feed	I_{max}	Jumper	Feed Terminal	Feed	I_{max}	Jumper
1492-L3	4...14 AWG (16 mm ²)	62 A	1492-CJK5-*	1492-L3	#4...14 AWG (16 mm ²)	76 A	1492-CJK5-*	1492-L3	#4...14 AWG (16 mm ²)	62 A	1492-CJK5-*
1492-L3Q		62 A	1492-CJK5-*	1492-L3Q		76 A	1492-CJK5-*	1492-L3Q		62 A	1492-CJK5-*
1492-L4		76 A	1492-CJK6-*	1492-L4		76 A	1492-CJK6-*	1492-L4		76 A	1492-CJK6-*
								1492-L4T		76 A	1492-CJK6-*
								1492-L4Q		76 A	1492-CJK6-*
1492-L6		76 A	1492-CJL8-*	1492-L6		76 A	1492-CJL8-*	1492-L6		76 A	1492-CJL8-*
								1492-L6T		76 A	1492-CJL8-*

* See accessory section for availability of specific jumper pole configurations.

Spring-Clamp Connection Terminal Blocks

Multi-Circuit Feed-Through Blocks

	1492-LD2			1492-LD3			1492-L3QS		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit feed-through terminal block			Two-circuit feed-through terminal block			Side-by-side two circuit terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	20 A	25 A	27 A
Wire Range (Rated Cross Section)	#28... 16 AWG		1.5 mm ²	#30... 12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)		2.5 mm ² (20... 12 AWG)
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.
Color	Grey	1492-LD2	50	1492-LD3	25	1492-L3QS	50	1492-L3QS	50
	Red	1492-LD2-RE	50	1492-LD3-RE	25	1492-L3QS-RE	50	1492-L3QS-RE	50
	Blue	1492-LD2-B	50	1492-LD3-B	25	1492-L3QS-B	50	1492-L3QS-B	50
	Black	1492-LD2-BL	50	1492-LD3-BL	25	1492-L3QS-BL	50	1492-L3QS-BL	50
	Green	1492-LD2-G	50	1492-LD3-G	25	1492-L3QS-G	50	1492-L3QS-G	50
	Yellow	1492-LD2-Y	50	1492-LD3-Y	25	1492-L3QS-Y	50	1492-L3QS-Y	50
	Orange	1492-LD2-OR	50	1492-LD3-OR	25	1492-L3QS-OR	50	1492-L3QS-OR	50
	Brown	1492-LD2-BR	50	1492-LD3-BR	25	1492-L3QS-BR	50	1492-L3QS-BR	50
	White	1492-LD2-W	50	1492-LD3-W	25	1492-L3QS-W	50	1492-L3QS-W	50
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10	199-DR1	10	199-DR1
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10	1492-DR5	10	1492-DR5
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2	1492-DR6	2	1492-DR6
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2	1492-DR7	2	1492-DR7
End Barriers	Grey	1492-EBLD2	50	1492-EBLD3	20	1492-EBL3Q	50	1492-EBL3Q	50
	Blue	1492-EBLD2-B	20	1492-EBLD3-B	20	1492-EBL3Q-B	50	1492-EBL3Q-B	50
	Yellow	1492-EBLD2-Y	20	1492-EBLD3-Y	20	1492-EBL3Q-Y	50	1492-EBL3Q-Y	50
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20	1492-ERL35
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35
Jumpers									
Plug-in Center Jumper — 50-Pole	—	—	1492-CJK5-50	10	—	—	—	—	—
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20	1492-CJK5-10	20	—	—	—	—	—
Plug-in Center Jumper — 9-Pole	—	—	1492-CJK5-9	20	—	—	—	—	—
Plug-in Center Jumper — 8-Pole	—	—	1492-CJK5-8	20	—	—	—	—	—
Plug-in Center Jumper — 7-Pole	—	—	1492-CJK5-7	20	—	—	—	—	—
Plug-in Center Jumper — 6-Pole	—	—	1492-CJK5-6	20	—	—	—	—	—
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60	1492-CJK5-5	20	—	—	—	—	—
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60	1492-CJK5-4	60	—	—	—	—	—
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60	1492-CJK5-3	60	—	—	—	—	—
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60	1492-CJK5-2	60	—	—	—	—	—
Other Accessories									
Reducing Sleeves #28...24 AWG (0.13...0.2 mm ²)	1492-PSL2-2	100	1492-PSLS2-2	100	—	—	1492-PSL3-2	100	1492-PSL3-2
Reducing Sleeves #22...20 AWG (0.25...0.5 mm ²)	1492-PSL2-5	100	1492-PSLS2-5	100	—	—	1492-PSL3-5	100	1492-PSL3-5
Reducing Sleeves #18 AWG (0.75...1.0 mm ²)	—	—	—	—	—	—	1492-PSL3-10	100	1492-PSL3-10
Test Plug	1492-TPL4	25	—	—	1492-TP23	20	1492-TPL5	25	1492-TPL5
Electrical Warning Plate	1492-EWPL4	20	—	—	1492-EWPL5	20	—	—	—
Marking Systems									
Snap-In Marker Cards	1492-M3X12 (120/card)*	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)
Hinged Marker Cards	1492-M3X5 (100/card)	5	1492-M5X5 (200/card)	5	1492-MH5X10 (96/card)	5	—	—	—

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks



Multi-Circuit Feed-Through Blocks

1492-LD4

1492-LTF3

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Two-circuit feed-through terminal block

Three-circuit feed-through terminal block with multiple cross connection points

	UL	CSA	IEC	UL	CSA	IEC
Certifications						
Voltage Rating	600V AC/DC		800V AC/DC	300V AC/DC		500V AC/DC
Maximum Current	25 A	30 A	32 A	15 A		20 A
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	#26...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		

Terminal Blocks

		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color	Grey	1492-LD4	20	1492-LTF3	25
	Red	1492-LD4-RE	20	—	—
	Blue	1492-LD4-B	20	—	—
	Black	1492-LD4-BL	20	—	—
	Green	1492-LD4-G	20	—	—
	Yellow	1492-LD4-Y	20	—	—
	Orange	1492-LD4-OR	20	—	—
	Brown	1492-LD4-BR	20	—	—
	White	1492-LD4-W	20	—	—




Accessories

		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails					
1 m Symmetrical DIN (Steel)		199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2	1492-DR7	2
End Barriers	Grey	1492-EBLD4	20	1492-EBLTF3	20
	Blue	1492-EBLD4-B	20	—	—
	Yellow	1492-EBLD4-Y	20	—	—
End Anchors and Retainers					
Screwless End Retainer		1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50	1492-EAHJ35	50
Jumpers					
Plug-in Center Jumper — 50-Pole		—	—	1492-CJK5-50	10
Plug-in Center Jumper — 10-Pole		1492-CJK6-10	20	1492-CJK5-10	20
Plug-in Center Jumper — 9-Pole		1492-CJK6-9	20	1492-CJK5-9	20
Plug-in Center Jumper — 8-Pole		1492-CJK6-8	20	1492-CJK5-8	20
Plug-in Center Jumper — 7-Pole		1492-CJK6-7	20	1492-CJK5-7	20
Plug-in Center Jumper — 6-Pole		1492-CJK6-6	20	1492-CJK5-6	20
Plug-in Center Jumper — 5-Pole		1492-CJK6-5	20	1492-CJK5-5	20
Plug-in Center Jumper — 4-Pole		1492-CJK6-4	60	1492-CJK5-4	60
Plug-in Center Jumper — 3-Pole		1492-CJK6-3	60	1492-CJK5-3	60
Plug-in Center Jumper — 2-Pole		1492-CJK6-2	60	1492-CJK5-2	60
Vertical Cross Connector*		—	—	1492-CJL5D	20
Other Accessories					
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²)		—	—	1492-PSLTF3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²)		—	—	1492-PSLTF3-5	100
Test Plug		1492-TP23	20	—	—
Electrical Warning Plate		1492-EWPL6	20	—	—
Marking Systems					
Snap-In Marker Cards		1492-M6X10 (120/card)	5	1492-SM5X10 (144/card)	5
Snap-In Marker Cards		1492-M6X5 (200/card)	5	1492-M5X5 (200/card)	5

* Used to electrically connect 2 levels of 1492-LTF3

Spring-Clamp Connection Terminal Blocks

Specialty Feed-Through Blocks

	1492-LD2C			1492-LD3C				1492-LD4C		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
Specifications	Two-level feed-through terminal block with commoning bar			Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar		
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	22 A	25 A	30 A	32 A
Wire Range (Rated Cross Section)	#28...16 AWG		1.5 mm ²	#30...12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)	#26...10 AWG		4 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color: Grey	1492-LD2C	50		1492-LD3C	25			1492-LD4C	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2			1492-DR7	2	
End Barriers Grey	1492-EBLD2	50		1492-EBLD3	20			1492-EBLD4	20	
End Anchors and Retainers Screwless End Retainer	1492-ERL35	20		1492-ERL35	20			1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50			1492-EAHJ35	50	
Jumpers:										
Plug-in Center Jumper — 50-Pole	—	—		1492-CJK5-50	10			—	—	
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20		1492-CJK5-10	20			1492-CJK6-10	20	
Plug-in Center Jumper — 9-Pole	—	—		1492-CJK5-9	20			1492-CJK6-9	20	
Plug-in Center Jumper — 8-Pole	—	—		1492-CJK5-8	20			1492-CJK6-8	20	
Plug-in Center Jumper — 7-Pole	—	—		1492-CJK5-7	20			1492-CJK6-7	20	
Plug-in Center Jumper — 6-Pole	—	—		1492-CJK5-6	20			1492-CJK6-6	20	
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60		1492-CJK5-5	20			1492-CJK6-5	20	
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60		1492-CJK5-4	60			1492-CJK6-4	60	
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60		1492-CJK5-3	60			1492-CJK6-3	60	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60		1492-CJK5-2	60			1492-CJK6-2	60	
Other Accessories:										
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100		1492-PSLS2-2	100			—	—	
Reducing Sleeves 22...20 AWG (0.13...0.2 mm ²) Grey	1492-PSL2-5	100		1492-PSLS2-5	100			—	—	
Test Plug	1492-TPL4	25		—	—			1492-TP23	20	
Electrical Warning Plate	1492-EWPL4	20		—	—			1492-EWPL6	20	
Marking Systems:										
Snap-In Marker Cards	1492-M3X12 (120/card)*	5		1492-M5X10 (144/card)	5			1492-M6X10 (120/card)	5	
Snap-In Marker Cards	1492-M3X5 (100/card)	5		1492-M5X5 (200/card)	5			1492-M6X5 (200/card)	5	

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Sensor Blocks — 3-Wire




1492-LS2-3*
1492-LS2-3L*

1492-LSG2-3*

1492-LS2-BR
1492-LS2-B
1492-LSG2

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	3 conductor sensor block base for plug in distribution blocks			3 conductor sensor ground block base for plug in distribution blocks			Plug in Distribution blocks — internally jumpered		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating (without LED)	300V AC/DC			300V AC/DC			300V AC/DC		
Voltage Rating (with LED)	5...30V AC/DC			—			5...30V AC/DC		
Maximum Current	10 A			10 A			10 A		
Wire Range (Rated Cross Section)	#26...14 AWG			#26...14 AWG			#26...14 AWG		
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey (Without LED)	1492-LS2-3	50		—	—		—	—	
Grey (With LED)	1492-LS2-3L	50		—	—		—	—	
Green/Yellow	—	—		1492-LSG2-3	20		1492-LSG2	100	
Brown	—	—		—	—		1492-LS2-BR	100	
Blue	—	—		—	—		1492-LS2-B	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		—	—	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		—	—	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		—	—	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		—	—	
End Barriers Grey	1492-EBLS2-3	50		1492-EBLS2-3	50		Not required	—	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		—	—	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		—	—	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		—	—	
Jumpers:									
Plug-in Center Jumper — 50-Pole	1492-CJK5-50	10		—	—		—	—	
Plug-in Center Jumper — 10-Pole	1492-CJK5-10	20		—	—		—	—	
Plug-in Center Jumper — 9-Pole	1492-CJK5-9	20		—	—		—	—	
Plug-in Center Jumper — 8-Pole	1492-CJK5-8	20		—	—		—	—	
Plug-in Center Jumper — 7-Pole	1492-CJK5-7	20		—	—		—	—	
Plug-in Center Jumper — 6-Pole	1492-CJK5-6	20		—	—		—	—	
Plug-in Center Jumper — 5-Pole	1492-CJK5-5	20		—	—		—	—	
Plug-in Center Jumper — 4-Pole	1492-CJK5-4	60		—	—		—	—	
Plug-in Center Jumper — 3-Pole	1492-CJK5-3	60		—	—		—	—	
Plug-in Center Jumper — 2-Pole	1492-CJK5-2	60		—	—		—	—	
Other Accessories:									
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSLS2-2	100		—	—		1492-PSLS2-2	100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSLS2-5	100		—	—		1492-PSLS2-5	100	
Marking Systems:									
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		—	—	

* A combination of two distribution blocks must be used with each base block.

Spring-Clamp Connection Terminal Blocks

Sensor Blocks — 4-Wire




1492-LS2-4*
1492-LS2-4L*

1492-LSG2-4*

1492-LS2-BR
1492-LS2-B
1492-LSG2

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.






Specifications	4 conductor sensor block base for plug in distribution blocks			4 conductor sensor ground block base for plug in distribution blocks			Plug In Distribution blocks — internally jumpered		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating (without LED)	300V AC/DC			300V AC/DC			300V AC/DC		
Voltage Rating (with LED)	5...30V AC/DC			—			5...30V AC/DC		
Maximum Current	10 A			10 A			10 A		
Wire Range (Rated Cross Section)	#26...14 AWG			#26...14 AWG			#26...14 AWG		
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.28 in. (7 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey (Without LED)	1492-LS2-4	50		—	—		—	—	
Grey (With LED)	1492-LS2-4L	50		—	—		—	—	
Green/Yellow	—	—		1492-LSG2-4	20		1492-LSG2	100	
Brown	—	—		—	—		1492-LS2-BR	100	
Blue	—	—		—	—		1492-LS2-B	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		—	—	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		—	—	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		—	—	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		—	—	
End Barriers Grey	1492-EBLS2-4	50		1492-EBLS2-4	50		Not required	—	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		—	—	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		—	—	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		—	—	
Jumpers:									
Plug-in Center Jumper — 50-Pole	1492-CJK5-50	10		—	—		—	—	
Plug-in Center Jumper — 10-Pole	1492-CJK5-10	20		—	—		—	—	
Plug-in Center Jumper — 9-Pole	1492-CJK5-9	20		—	—		—	—	
Plug-in Center Jumper — 8-Pole	1492-CJK5-8	20		—	—		—	—	
Plug-in Center Jumper — 7-Pole	1492-CJK5-7	20		—	—		—	—	
Plug-in Center Jumper — 6-Pole	1492-CJK5-6	20		—	—		—	—	
Plug-in Center Jumper — 5-Pole	1492-CJK5-5	20		—	—		—	—	
Plug-in Center Jumper — 4-Pole	1492-CJK5-4	60		—	—		—	—	
Plug-in Center Jumper — 3-Pole	1492-CJK5-3	60		—	—		—	—	
Plug-in Center Jumper — 2-Pole	1492-CJK5-2	60		—	—		—	—	
Other Accessories:									
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSLS2-2	100		—	—		1492-PSLS2-2	100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSLS2-5	100		—	—		1492-PSLS2-5	100	
Marking Systems:									
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		—	—	

* A combination of three distribution blocks must be used with each base block.




Spring-Clamp Connection Terminal Blocks

Grounding Blocks

	1492-LG2				1492-LG2T				1492-LG2Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block with 2 points on one side				Feed-through grounding terminal block with 2 points on each side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding			
Wire Range (Rated Cross Section)	#26...14 AWG	1.5 mm ²	1.5 mm ² (20...16 AWG)		#26...14 AWG	1.5 mm ²	1.5 mm ² (20...16 AWG)		#26...14 AWG	1.5 mm ²	1.5 mm ² (20...16 AWG)	
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		
Color: Green/Yellow	1492-LG2	50			1492-LG2T	50			1492-LG2Q	50		
Accessories	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1	10			199-DR1	10			199-DR1	10		
1 m Symmetrical DIN (Aluminum)	1492-DR5	10			1492-DR5	10			1492-DR5	10		
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2			1492-DR6	2			1492-DR6	2		
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2			1492-DR7	2			1492-DR7	2		
End Barrier Yellow	1492-EBL2-Y	50			1492-EBL2T-Y	50			1492-EBL2Q-Y	50		
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35	20			1492-ERL35	20			1492-ERL35	20		
DIN Rail — Normal Duty	1492-EAJ35	100			1492-EAJ35	100			1492-EAJ35	100		
DIN Rail — Heavy Duty	1492-EAHJ35	50			1492-EAHJ35	50			1492-EAHJ35	50		
Other Accessories:												
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100			1492-PSL2-2	100			1492-PSL2-2	100		
Reducing Sleeves 22...20 AWG (0.13...0.2 mm ²) Grey	1492-PSL2-5	100			1492-PSL2-5	100			1492-PSL2-5	100		
Test Plug (Stackable)	1492-TPL4	25			1492-TPL4	25			1492-TPL4	25		
Marking Systems:												
Snap-In Marker Cards	1492-M3X12 (120/card)	5			1492-M3X12 (120/card)	5			1492-M3X12 (120/card)	5		
Snap-In Marker Cards	1492-M3X5 (100/card)	5			1492-M3X5 (100/card)	5			1492-M3X5 (100/card)	5		




Spring-Clamp Connection Terminal Blocks

Grounding Blocks

	1492-LG3				1492-LG3T				1492-LG3Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block with 2 points on one side				Feed-through grounding terminal block with 2 points on each side			
Certifications	 CSA IEC ATEX				 CSA IEC ATEX				 CSA IEC ATEX			
Voltage Rating	—				—				—			
Maximum Current	Grounding				Grounding				Grounding			
Wire Range (Rated Cross Section)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20... 12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20... 12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20... 12 AWG)
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color: Green/Yellow	1492-LG3		50		1492-LG3T		50		1492-LG3Q		50	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Symmetrical Heavy Duty DIN (Steel)	199-DR9		5		199-DR9		5		199-DR9		5	
End Barrier Yellow	1492-EBL3-Y		50		1492-EBL3T-Y		50		1492-EBL3Q-Y		50	
End Anchors and Retainers: Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Other Accessories:												
Reducing Sleeves 30...24 AWG (0.13...0.2 mm ²) White	1492-PSL3-2		100		1492-PSL3-2		100		1492-PSL3-2		100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL3-5		100		1492-PSL3-5		100		1492-PSL3-5		100	
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL3-10		100		1492-PSL3-10		100		1492-PSL3-10		100	
Test Plug	1492-TP23		20		1492-TP23		20		1492-TP23		20	
Test Plug (Stackable)	1492-TPL5		25		1492-TPL5		25		1492-TPL5		25	
Marking Systems:												
Snap-In Marker Cards	1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5	
Snap-In Marker Cards	1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5	
Hinged Marker Cards	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5	
Hinged Marker Cards	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5	




Spring-Clamp Connection Terminal Blocks

Grounding Blocks

	1492-LG4				1492-LG4T				1492-LG4Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block with 2 points on one side				Feed-through grounding terminal block with 2 points on each side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding			
Wire Range (Rated Cross Section)	#26...10 AWG	4 mm ²	4 mm ² (20...10 AWG)		#26...10 AWG	4 mm ²	4 mm ² (20...12 AWG)		#26...10 AWG	4 mm ²	4 mm ² (20...12 AWG)	
Wire Strip Length	0.47 in. (12 mm)				0.47 in. (12 mm)				0.47 in. (12 mm)			
Density	49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color: Green/Yellow	1492-LG4		50		1492-LG4T		50		1492-LG4Q		50	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barrier Yellow	1492-EBL4-Y		50		1492-EBL4T-Y		50		1492-EBL4Q-Y		50	
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Other Accessories:												
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²) White	1492-PSL4-2		100		1492-PSL4-2		100		1492-PSL4-2		100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL4-5		100		1492-PSL4-5		100		1492-PSL4-5		100	
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL4-10		100		1492-PSL4-10		100		1492-PSL4-10		100	
Test Plug	1492-TP23		20		1492-TP23		20		1492-TP23		20	
Test Plug (Stackable)	1492-TPL6		25		1492-TPL6		25		1492-TPL6		25	
Marking Systems:												
Snap-In Marker Cards	1492-M6X10 (120/card)		5		1492-M6X10 (120/card)		5		1492-M6X10 (120/card)		5	
Snap-In Marker Cards	1492-M6X5 (200/card)		5		1492-M6X5 (200/card)		5		1492-M6X5 (200/card)		5	
Hinged Marker Cards	1492-MH6X12 (80/card)		5		1492-MH6X12 (80/card)		5		1492-MH6X12 (80/card)		5	

Spring-Clamp Connection Terminal Blocks




Grounding Blocks

	1492-LG6				1492-LG6T				1492-LG10			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block with 2 points on one side				Feed-through grounding terminal block			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding			
Wire Range (Rated Cross Section)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...8 AWG)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...10 AWG)	#16...6 AWG	10 mm ²	10 mm ² (16...8 AWG)	
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				0.70 in. (18 mm)			
Density	37 pcs/ft (123 pcs/m)				37 pcs/ft (123 pcs/m)				30 pcs/ft (99 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color: Green/Yellow	1492-LG6		50		1492-LG6T		50		1492-LG10		25	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barrier Yellow	1492-EBL6-Y		50		1492-EBL6T-Y		50		1492-EBL10-Y		20	
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Other Accessories:												
Test Plug	1492-TPL8		25		1492-TPL8		25		1492-TP23		20	
Marking Systems:												
Snap-In Marker Cards*	1492-MR8X12 (84/card)		5		1492-M6X12 (120/card)		5		1492-M6X12 (120/card)		5	
Snap-In Marker Cards	1492-M8X5 (160/card)		5		1492-M8X5 (160/card)		5		1492-M8X5 (160/card)		5	
Hinged Marker Cards	1492-MH6X12 (80/card)		5		1492-MH6X12 (80/card)		5		1492-MH5X15 (96/card)		5	

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks


Grounding Blocks

	1492-LG16				1492-LG35				1492-LDG2		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block				Two-circuit terminal block with 1 feed-through and 1 ground circuit		
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	—	—	—	—	—	—	—	—	300V AC/DC	500V AC/DC	—
Maximum Current	Grounding				Grounding				10 A	17.5 A	—
Wire Range (Rated Cross Section)	#14...6 AWG	#14...4 AWG	16 mm ²	16 mm ² (16...6 AWG)	#12...2 AWG	35 mm ²	35 mm ² (#14...2 AWG)	—	#28...16 AWG	1.5 mm ²	—
Wire Strip Length	0.70 in. (18 mm)				0.98 in. (25 mm)				0.31 in. (8 mm)		
Density	25 pcs/ft (82 pcs/m)				18 pcs/ft (62 pcs/m)				87 pcs/ft (285 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		
Color: Green/Yellow	1492-LG16			25	1492-LG35			10	—		
Grey	—			—	—			—	1492-LDG2		
50	—			—	—			—	—		
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1		
1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)	199-DR4			5	199-DR4			5	199-DR4		
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5		
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6		
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7		
1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	1492-DR8			5	1492-DR8			5	1492-DR8		
1 m Symmetrical Heavy Duty DIN (Steel)	1492-DR9			5	1492-DR9			5	1492-DR9		
End Barrier Yellow	1492-EBL16-Y			20	Integrated			—	—		
Grey	—			—	—			—	1492-EBLD2		
50	—			—	—			—	—		
End Anchors and Retainers	1492-ERL35			20	1492-ERL35			20	1492-ERL35		
Screwless End Retainer	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35		
DIN Rail — Normal Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35		
DIN Rail — Heavy Duty	—			—	—			—	1492-PSL2-2		
Other Accessories:											
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²) White	—			—	—			—	1492-PSL2-5		
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	—			—	—			—	—		
Test Plug	1492-TP23			20	1492-TP23			20	1492-TPL4		
Electrical Warning Plate	—			—	—			—	1492-EWPL4		
20	—			—	—			—	—		
Marking Systems:											
Snap-In Marker Cards*	1492-M7X12 (108/card)			5	1492-M7X12 (108/card)			5	1492-M3X12 (120/card)		
Snap-In Marker Cards	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5	1492-M3X5 (100/card)		
Hinged Marker Cards	1492-MH5X15 (96/card)			5	1492-MH5X10 (96/card)			—	—		

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Grounding Blocks

1492-LDG2C				1492-LDG3				1492-LDG3C			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
Specifications	Single-circuit, two-level grounding terminal block with 2 connection points on each side			Two-circuit grounding terminal block with 1 feed-through and 1 ground circuit			Single-circuit, two-level grounding terminal block with 2 connection points on each side				
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	600V AC/DC		800V AC/DC	550V AC/DC	—	—	—	—
Maximum Current	Grounding			20 A	25 A	24 A	20 A	Grounding			
Wire Range (Rated Cross Section)	#28...16 AWG		1.5 mm ²	#26...12 AWG	#30...12 AWG	2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)	#26...12 AWG	#30...12 AWG	2.5 mm ²	0.5...2.5 mm ² (20...14 AWG)
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)				
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			
Color: Green/Yellow	1492-LDG2C	50		—	—		1492-LDG3C	25			
Grey	—	—		1492-LDG3	25		—	—			
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10			
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10			
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2			
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2			
End Barrier Yellow	1492-EBLD2-Y	20		—	—		1492-EBLD3-Y	20			
Grey	—	—		1492-EBLD3	20		—	—			
End Anchors and Retainers											
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20			
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100			
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50			
Other Accessories:											
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100		1492-PSLS2-2	100		1492-PSLS2-2	100			
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL2-5	100		1492-PSLS2-5	100		1492-PSLS2-5	100			
Test Plug (Stackable)	1492-TPL4	25		—	—		—	—			
Marking Systems:											
Snap-In Marker Cards		1492-M3X12 (120/card)	5	1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5			
Snap-In Marker Cards	1492-M3X5 (100/card)		5	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5			

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks



Grounding Blocks

1492-LDG4

1492-LDG4C

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Two-circuit grounding terminal block with 1 feed-through and 1 ground circuit

Single-circuit, two-level grounding terminal block with 2 connection points on each side

Certifications	UL	CSA	IEC	UL	CSA	IEC
Voltage Rating	600V AC/DC		800V AC/DC	—	—	—
Maximum Current	25 A	30 A	32 A	Grounding		
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	#26...10 AWG		4 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		

Terminal Blocks




	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color: Green/Yellow	—	—	1492-LDG4C	20
Grey	1492-LDG4	20	—	—

Accessories

	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails:				
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2
End Barrier Yellow	—	—	1492-EBLD4-Y	20
Grey	1492-EBLD4	20	—	—
End Anchors and Retainers				
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50
Other Accessories:				
Test Plug	1492-TP23	20	—	—
Electrical Warning Plate	1492-EWPL6	20	—	—
Marking Systems:				
Snap-In Marker Cards	1492-M6X10 (120/card)	5	1492-M6X10 (120/card)	5
Snap-In Marker Cards	1492-M6X5 (200/card)	5	1492-M6X5 (200/card)	5

Spring-Clamp Connection Terminal Blocks

Plug-in Style Blocks

	1492-LD32P			1492-LG31P			1492-LG3T1P		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit terminal block with 1 fixed and 1 plug-in connection on each level. Plug-in connectors can be individual or grouped configurations.			Single-circuit grounding terminal block with 1 fixed and 1 plug-in connection.			Single-circuit grounding terminal block with 2 fixed and 1 plug-in connection.		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	—		—	—		—
Maximum Current	20 A		24 A	Grounding		—	Grounding		—
Limited Rating - Voltage*	600V AC/DC		—	—		—	—		—
Limited Rating - Current*	5 A		—	—		—	—		—
Wire Range (Rated Cross Section)	26... 12 AWG		0.5...2.5 mm ²	26... 12 AWG		0.5...2.5 mm ²	26... 12 AWG		0.5...2.5 mm ²
Wire Strip Length	0.394 in (10 mm)			0.394 in (10 mm)			0.394 in (10 mm)		
Density (Blocks per ft/m)	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pcs/ Pkg		Cat. No.	Pcs/ Pkg		Cat. No.	Pcs/ Pkg	
Color	Grey	1492-LD32P		50	—	—	—	—	
	Green/Yellow	—		—	1492-LG31P	50	1492-LG3T1P	50	
Accessories	Cat. No.	Pcs/ Pkg		Cat. No.	Pcs/ Pkg		Cat. No.	Pcs/ Pkg	
Mounting Rails									
1 m Symmetrical DIN (Steel)		199-DR1		10	199-DR1	10	199-DR1	10	
1 m Symmetrical DIN (Aluminum)		1492-DR5		10	1492-DR5	10	1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2	1492-DR6	2	1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2	1492-DR7	2	1492-DR7	2	
End Barrier	Grey	1492-EBLD32P		50	—	—	—	—	
	Yellow	—		—	1492-EBL31P-Y	50	1492-EBL3T1P-Y	50	
End Anchors									
Screwless End Retainer		1492-ERL35		20	1492-ERL35	20	1492-ERL35	20	
DIN Rail - Normal Duty		1492-EAJ35		100	1492-EAJ35	100	1492-EAJ35	100	
Din Rail - Heavy Duty		1492-EAHJ35		50	1492-EAHJ35	50	1492-EAHJ35	50	
Jumpers									
Plug-in Center Jumper — 50 Pole		1492-CJLJ5-50		10	—	—	—	—	
Plug-in Center Jumper — 10 Pole		1492-CJLJ5-10		20	—	—	—	—	
Plug-in Center Jumper — 9 Pole		1492-CJLJ5-9		20	—	—	—	—	
Plug-in Center Jumper — 8 Pole		1492-CJLJ5-8		20	—	—	—	—	
Plug-in Center Jumper — 7 Pole		1492-CJLJ5-7		20	—	—	—	—	
Plug-in Center Jumper — 6 Pole		1492-CJLJ5-6		20	—	—	—	—	
Plug-in Center Jumper — 5 Pole		1492-CJLJ5-5		20	—	—	—	—	
Plug-in Center Jumper — 4 Pole		1492-CJLJ5-4		60	—	—	—	—	
Plug-in Center Jumper — 3 Pole		1492-CJLJ5-3		60	—	—	—	—	
Plug-in Center Jumper — 2 Pole		1492-CJLJ5-2		60	—	—	—	—	
Individual Plug-in Connector	Grey	1492-STP		50	—	—	—	—	
	Green	1492-STP-G		50	1492-STP-G	50	1492-STP-G	50	
Ganged Connector - Start Plug	Grey	1492-SBSTP		50	—	—	—	—	
Ganged Connector - Middle Plug†	Grey	1492-GSTP		50	—	—	—	—	
Ganged Connector - End Plug	Grey	1492-EBSTP		50	—	—	—	—	
Plug-In Component Accessories									
Locking Element	Yellow	1492-STPLE		25	1492-STPLE	25	1492-STPLE	25	
Coding Element	Yellow	1492-STPCE		50	1492-STPCE	50	1492-STPCE	50	
Strain Relief	Yellow	1492-STPSR		25	1492-STPSR	25	1492-STPSR	25	
Group Marking									
Rail Mount Group Marking Carrier		1492-GM35		25	1492-GM35	25	1492-GM35	25	
End Anchor Top Marker Carrier*		1492-GMC		50	1492-GMC	50	1492-GMC	50	
Cat. No. 1492-GMC Top Marker Tag		1492-M5X30(20/card)		5	1492-M5X30(20/card)	5	1492-M5X30(20/card)	5	
Marking Systems									
Snap-in Marker Cards		1492-MR5X12 (120/card)		5	1492-MR5X12 (120/card)	5	1492-MR5X12 (120/card)	5	
Snap-In Marker Cards		1492-MR5X8 (120/card)		5	1492-MR5X8 (120/card)	5	1492-MR5X8 (120/card)	5	


* The Bulletin 1492-GMC marker carrier installs directly on the top of a 1492-EAJ35 end anchor or a 1492-ERL35 end retainer for group marking purposes.

* Blocks contain dual UL/CSA listings and can be used at 300V with a 20 A rating or 600V with a 5 A rating.

† For ganged configurations greater than 2, use multiple 1492-GSTP plug-in blocks.

1492-LKD3

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	<i>Knife disconnect feed-through terminal block</i>		
Certifications	UL	CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC
Maximum Current	20 A		24 A
Wire Range (Rated Cross Section)	#30...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		

Terminal Blocks		Cat. No.	Pkg Qty.
Color	Grey	1492-LKD3	25
Accessories		Cat. No.	Pkg Qty.
Mounting Rails			
1 m Symmetrical DIN (Steel)		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2
End Barriers	Grey	1492-EBL3	50
End Anchors and Retainers			
Screwless End Retainer		1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50
Jumpers			
Plug-in Center Jumper — 50-Pole		1492-CJK5-50	10
Plug-in Center Jumper — 10-Pole		1492-CJK5-10	20
Plug-in Center Jumper — 9-Pole		1492-CJK5-9	20
Plug-in Center Jumper — 8-Pole		1492-CJK5-8	20
Plug-in Center Jumper — 7-Pole		1492-CJK5-7	20
Plug-in Center Jumper — 6-Pole		1492-CJK5-6	20
Plug-in Center Jumper — 5-Pole		1492-CJK5-5	20
Plug-in Center Jumper — 4-Pole		1492-CJK5-4	60
Plug-in Center Jumper — 3-Pole		1492-CJK5-3	60
Plug-in Center Jumper — 2-Pole		1492-CJK5-2	60
Other Accessories			
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White		1492-PSL3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey		1492-PSL3-5	100
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey		1492-PSL3-10	100
Test Plug		1492-TP23	20
Test Plug (Stackable)		1492-TPL5	25
Electrical Warning Plate		1492-EWPL5	20
Marking Systems			
Snap-In Marker Cards		1492-M5X10 (144/card)	5
Snap-In Marker Cards		1492-M5X5 (200/card)	5

Spring-Clamp Connection Terminal Blocks

Plug-In Style Blocks & Analog Loop Control Block

	1492-L3P			1492-LDG3P			1492-LDAG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single circuit plug-in component block for a variety of components			Terminal block with slot for plug-in component, feed-through circuit and 1 ground connection			Analog Loop Control Terminal Block with 2 Feed-Through Circuits and 1 Ground Connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC			300V AC/DC			300V AC/DC		
Maximum Current	20 A			10 A			10 A		
Wire Range (Rated Cross Section)	#30...12 AWG			#26...12 AWG			#26...12 AWG		
Wire Strip Length	0.39 in. (10 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color Grey	1492-L3P	25		1492-LDG3P	25		1492-LDAG3	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Steel)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-EBL3	50		1492-EBLDAG3	20		1492-EBLDAG3	20	
End Barrier	1492-EBL35	20		1492-EBL35	20		1492-EBL35	20	
End Anchors and Retainers	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
Screwless End Retainer	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
DIN Rail — Normal Duty	1492-CJK5-50	10		1492-CJLJ5-50	10		1492-CJLJ5-50	10	
DIN Rail — Heavy Duty	1492-CJK5-10	20		1492-CJLJ5-10	20		1492-CJLJ5-10	20	
Jumpers	1492-CJK5-9	20		1492-CJLJ5-9	20		1492-CJLJ5-9	20	
Plug-In Center Jumper — 50-pole	1492-CJK5-8	20		1492-CJLJ5-8	20		1492-CJLJ5-8	20	
Plug-In Center Jumper — 10-pole	1492-CJK5-7	20		1492-CJLJ5-7	20		1492-CJLJ5-7	20	
Plug-In Center Jumper — 9-pole	1492-CJK5-6	20		1492-CJLJ5-6	20		1492-CJLJ5-6	20	
Plug-In Center Jumper — 8-pole	1492-CJK5-5	20		1492-CJLJ5-5	20		1492-CJLJ5-5	20	
Plug-In Center Jumper — 7-pole	1492-CJK5-4	60		1492-CJLJ5-4	60		1492-CJLJ5-4	60	
Plug-In Center Jumper — 6-pole	1492-CJK5-3	60		1492-CJLJ5-3	60		1492-CJLJ5-3	60	
Plug-In Center Jumper — 5-pole	1492-CJK5-2	60		1492-CJLJ5-2	60		1492-CJLJ5-2	60	
Plug-In Center Jumper — 4-pole	1492-DPL	50		1492-DPL	50		—	—	
Plug-In Center Jumper — 3-pole	1492-CPL	50		1492-CPL	50		—	—	
Plug-In Center Jumper — 2-pole	1492-FPK2	20		1492-FPK2	20		—	—	
Other Accessories	1492-FPK224	20		1492-FPK224	20		—	—	
Disconnect Plug	1492-FPK248	20		1492-FPK248	20		—	—	
Component Plug	1492-FPK2120	20		1492-FPK2120	20		—	—	
Fuse Plug	1492-FPK2250	20		1492-FPK2250	20		—	—	
Without Blown Fuse Indicator	1492-PSL3-2	100		—	—		—	—	
10...36V Blown Fuse Indicator	1492-PSL3-5	100		—	—		—	—	
35...70V Blown Fuse Indicator	1492-PSL3-10	100		—	—		—	—	
60...150V Blown Fuse Indicator	1492-TP5	25		1492-TP23	20		—	—	
140...250V Blown Fuse Indicator	1492-EWPL5	20		—	—		—	—	
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey									
Test Plug									
Electrical Warning Plate									
Marking Systems									
Snap-In Marker Cards									
Snap-In Marker Cards									

* When using Cat. No. 1492-LDG3P with a fuse plug, a center jumper cannot be used on the top level. The only jumper option to use in combination with a fuse plug is a 2-pole side jumper: Cat. No. 1492-SJLM5-2.

Spring-Clamp Connection Terminal Blocks

Flexible Plug-In Connection Blocks




	1492-L31P			1492-L3T1P			1492-L3Q2P		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single circuit terminal block with 1 fixed and 1 plug-in connection. Plug-in connectors can be individual or grouped configurations.			Single circuit terminal block with 2 fixed and 1 plug-in connection. Plug-in connectors can be individual or grouped configurations.			Single circuit terminal block with 2 fixed and 2 plug-in connections. Plug-in connectors can be individual or grouped configurations.		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC
Maximum Current	20 A		24 A	20 A		24 A	20 A		24 A
Limited Rating - Voltage*	600V AC/DC		—	600V AC/DC		—	600V AC/DC	—	—
Limited Rating - Current*	5 A		—	5 A		—	5 A	—	—
Wire Range (Rated Cross Section)	#26...12 AWG		0.5...2.5 mm ²	#26...12 AWG		0.5...2.5 mm ²	#26...12 AWG		0.5...2.5 mm ²
Wire Strip Length	0.394 in. (10 mm)			0.394 in. (10 mm)			0.394 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-L31P	50	1492-L3T1P	50	1492-L3Q2P	50		
Accessories		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.		
Mounting Rails		199-DR1	10	199-DR1	10	199-DR1	10		
1 m Symmetrical DIN (Steel)		1492-DR5	10	1492-DR5	10	1492-DR5	10		
1 m Symmetrical DIN (Aluminum)		1492-DR6	2	1492-DR6	2	1492-DR6	2		
1 m Hi-Rise Symmetrical DIN (Aluminum)		1492-DR7	2	1492-DR7	2	1492-DR7	2		
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2	1492-DR7	2	1492-DR7	2		
End Barrier	Grey	1492-EBL3Q2P	50	1492-EBL3T1P	50	1492-EBL3Q2P	50		
	Yellow	1492-EBL31P-Y	50	1492-EBL3T1P-Y	50	-	-		
End Anchors		1492-ERL35	20	1492-ERL35	20	1492-ERL35	20		
Screwless End Retainer		1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100		
DIN Rail — Normal Duty		1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50		
DIN Rail — Heavy Duty		1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50		
Jumpers		1492-CJLJ5-50	10	1492-CJLJ5-50	10	1492-CJLJ5-50	10		
Plug-In Center Jumper — 50-pole		1492-CJLJ5-10	20	1492-CJLJ5-10	20	1492-CJLJ5-10	20		
Plug-In Center Jumper — 10-pole		1492-CJLJ5-9	20	1492-CJLJ5-9	20	1492-CJLJ5-9	20		
Plug-In Center Jumper — 9-pole		1492-CJLJ5-8	20	1492-CJLJ5-8	20	1492-CJLJ5-8	20		
Plug-In Center Jumper — 8-pole		1492-CJLJ5-7	20	1492-CJLJ5-7	20	1492-CJLJ5-7	20		
Plug-In Center Jumper — 7-pole		1492-CJLJ5-6	20	1492-CJLJ5-6	20	1492-CJLJ5-6	20		
Plug-In Center Jumper — 6-pole		1492-CJLJ5-5	20	1492-CJLJ5-5	20	1492-CJLJ5-5	20		
Plug-In Center Jumper — 5-pole		1492-CJLJ5-4	60	1492-CJLJ5-4	60	1492-CJLJ5-4	60		
Plug-In Center Jumper — 4-pole		1492-CJLJ5-3	60	1492-CJLJ5-3	60	1492-CJLJ5-3	60		
Plug-In Center Jumper — 3-pole		1492-CJLJ5-2	60	1492-CJLJ5-2	60	1492-CJLJ5-2	60		
Plug-In Center Jumper — 2-pole									
Other Accessories		1492-TPL5P	25	1492-TPL5P	25	1492-TPL5P	25		
Test Adapter									
Individual Plug-in	Grey	1492-STP	50	1492-STP	50	1492-STP	50		
Connector	Green	1492-STP-G	50	1492-STP-G	50	1492-STP-G	50		
Ganged Connector Start Plug	Grey	1492-SBSTP	50	1492-SBSTP	50	1492-SBSTP	50		
Ganged Connector Middle Plug†	Grey	1492-GSTP	50	1492-GSTP	50	1492-GSTP	50		
Ganged Connector End Plug	Grey	1492-EBSTP	50	1492-EBSTP	50	1492-EBSTP	50		
Plug-in Component Accessories		1492-STPLE	25	1492-STPLE	25	1492-STPLE	25		
Locking Element - Yellow		1492-STPCE	50	1492-STPCE	50	1492-STPCE	50		
Coding Element - Yellow		1492-STPSR	25	1492-STPSR	25	1492-STPSR	25		
Strain Relief - Yellow		1492-MR5X12	5	1492-MR5X12	5	1492-MR5X12	5		
Marking Systems		(120/card)		(120/card)		(120/card)			
Snap-In Marker Cards		1492-M5X8 (120/card)	5	1492-M5X8 (120/card)	5	1492-M5X8 (120/card)	5		

* Terminal Blocks contain dual UL/CSA listings and can be used at 300V with a 20 A rating or 600V with a 5 A rating.

† For ganged configurations greater than 2, use multiple 1492-GSTP plug-in blocks.

Spring-Clamp Connection Terminal Blocks

Plug-in Connection Blocks

	1492-LD32P			1492-LG31P			1492-LG3T1P		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit terminal block with 1 fixed and 1 plug-in connection. Plug-in connectors can be individual or grouped configurations.			Single circuit grounding terminal block with 1 fixed and 1 plug-in connection.			Single circuit grounding terminal block with 2 fixed and 1 plug-in connection.		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	—		—	—		—
Maximum Current	20 A		24 A	Grounding		Grounding	Grounding		Grounding
Limited Rating - Voltage*	600V AC/DC		—	—		—	—		—
Limited Rating - Current*	5 A		—	—		—	—		—
Wire Range (Rated Cross Section)	#26...12 AWG		0.5...2.5 mm ²	#26...12 AWG		0.5...2.5 mm ²	#26...12 AWG		0.5...2.5 mm ²
Wire Strip Length	0.394 in. (10 mm)		0.394 in. (10 mm)	0.394 in. (10 mm)		0.394 in. (10 mm)	0.394 in. (10 mm)		0.394 in. (10 mm)
Density	59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)	59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)	59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)	-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)	-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-LD32P	50	—	—	—	—	—	—
	Green/ Yellow	—	—	1492-LG31P	50	1492-LG3T1P	50	50	50
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier	Grey	1492-EBLD32P	50	—	—	—	—	—	—
	Yellow	—	—	1492-EBL31P-Y	50	1492-EBL31P-Y	50	50	50
End Anchors									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-In Center Jumper — 50-pole	1492-CJLJ5-50	10		—	—		—	—	
Plug-In Center Jumper — 10-pole	1492-CJLJ5-10	20		—	—		—	—	
Plug-In Center Jumper — 9-pole	1492-CJLJ5-9	20		—	—		—	—	
Plug-In Center Jumper — 8-pole	1492-CJLJ5-8	20		—	—		—	—	
Plug-In Center Jumper — 7-pole	1492-CJLJ5-7	20		—	—		—	—	
Plug-In Center Jumper — 6-pole	1492-CJLJ5-6	20		—	—		—	—	
Plug-In Center Jumper — 5-pole	1492-CJLJ5-5	20		—	—		—	—	
Plug-In Center Jumper — 4-pole	1492-CJLJ5-4	60		—	—		—	—	
Plug-In Center Jumper — 3-pole	1492-CJLJ5-3	60		—	—		—	—	
Plug-In Center Jumper — 2-pole	1492-CJLJ5-2	60		—	—		—	—	
Other Accessories									
Test Adapter	1492-TPL5P	25		—	—		—	—	
Individual Plug-in Connector	Grey	1492-STP	50	—	—	—	—	—	—
	Green	1492-STP-G	50	1492-STP-G	50	1492-STP-G	50	50	50
Ganged Connector Start Plug	Grey	1492-SBSTP	50	—	—	—	—	—	—
Ganged Connector Middle Plug†	Grey	1492-GSTP	50	—	—	—	—	—	—
Ganged Connector End Plug	Grey	1492-EBSTP	50	—	—	—	—	—	—
Plug-in Component Accessories									
Locking Element - Yellow	1492-STPLE	25		1492-STPLE	25		1492-STPLE	25	
Coding Element - Yellow	1492-STPCE	50		1492-STPCE	50		1492-STPCE	50	
Strain Relief - Yellow	1492-STPSR	25		1492-STPSR	25		1492-STPSR	25	

* Terminal Blocks contain dual UL/CSA listings and can be used at 300V with a 20 A rating or 600V with a 5 A rating.

www.ab.com/catalogs Preferred availability cat. nos. are bold.




Publication A117-CA001A-EN-P



Allen-Bradley

Spring-Clamp Connection Terminal Blocks



Internal Component Blocks

	1492-LD4DF			1492-LD4DR			1492-LD4SS*		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-level terminal block with an IN4007 diode in forward bias between the 2 levels.			Two-level terminal block with an IN4007 diode in reverse bias between the 2 levels.			Two level terminal block with an MOV between the 2 levels.		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC			600V AC/DC			600V AC/DC		
Maximum Current	25 A	30 A	32 A	25 A	30 A	32 A	120V	—	140V AC/DC
Component Current/Wattage Rating*	1 A			1 A			25 A	30 A	32 A
Wire Range (Rated Cross Section)	#26...10 AWG			#26...10 AWG			#26...10 AWG	26...10 AWG	4mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color Black	1492-LD4DF	1		1492-LD4DR	1		1492-LD4SS	1	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier Grey	1492-EBLD4	20		1492-EBLD4	20		1492-EBLD4	20	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-in Center Jumper — 10-pole	1492-CJK6-10	20		1492-CJK6-10	20		1492-CJK6-10	20	
Plug-in Center Jumper — 9-pole	1492-CJK6-9	20		1492-CJK6-9	20		1492-CJK6-9	20	
Plug-in Center Jumper — 8-pole	1492-CJK6-8	20		1492-CJK6-8	20		1492-CJK6-8	20	
Plug-in Center Jumper — 7-pole	1492-CJK6-7	20		1492-CJK6-7	20		1492-CJK6-7	20	
Plug-in Center Jumper — 6-pole	1492-CJK6-6	20		1492-CJK6-6	20		1492-CJK6-6	20	
Plug-in Center Jumper — 5-pole	1492-CJK6-5	20		1492-CJK6-5	20		1492-CJK6-5	20	
Plug-in Center Jumper — 4-pole	1492-CJK6-4	60		1492-CJK6-4	60		1492-CJK6-4	60	
Plug-in Center Jumper — 3-pole	1492-CJK6-3	60		1492-CJK6-3	60		1492-CJK6-3	60	
Plug-in Center Jumper — 2-pole	1492-CJK6-2	60		1492-CJK6-2	60		1492-CJK6-2	60	
Other Accessories									
Test Plug	1492-TP23	20		1492-TP23	20		1492-TP23	20	
Marking Systems									
Snap-In Marker Cards	1492-M6X10 (120/card)	5		1492-M6X10 (120/card)	5		1492-M6X10 (120/card)	5	
Snap-In Marker Cards	1492-M6X5 (200/card)	5		1492-M6X5 (200/card)	5		1492-M6X5 (200/card)	5	

* For component specifications, see page 12-97

Spring-Clamp Connection Terminal Blocks

2-Level Neutral Disconnect and Installations

1492-LDG3ND				1492-LD3N			1492-LDG3N		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	3-Level terminal block with neutral disconnect and ground connection			2-Level feed-through terminal block for installation applications			3-Level terminal block with 2 feed-through and ground connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC	300V AC/DC	400V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC
Maximum Current	15 A	10 A	24 A	15 A	10 A	24 A	15 A	10 A	24 A
Wire Range (Rated Cross Section)	#26...12 AWG		2.5 mm²	#26...12 AWG		2.5 mm²	#26...12 AWG		2.5 mm²
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 per ft/196 per meter		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248°F (-50...+120°C)		
Short-Circuit Current Rating	See page 12-78								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey	1492-LDG3ND	50		1492-LD3N	50		1492-LDG3N	50	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers/ Grey	1492-BSPJLD3N	20		1492-BSPJLD3N	20		1492-BSPJLD3N	20	
Busbar Support Plates Blue	1492-BSPJLD3N-B	20		1492-BSPJLD3N-B	20		1492-BSPJLD3N-B	20	
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
End Anchor — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
End Anchor — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-10	20		1492-CJLJ5-10	20		1492-CJLJ5-10	20	
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-4	60		1492-CJLJ5-4	60		1492-CJLJ5-4	60	
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-3	60		1492-CJLJ5-3	60		1492-CJLJ5-3	60	
Plug-in Center Jumper — 2-Pole	1492-CJLJ5-2	60		1492-CJLJ5-2	60		1492-CJLJ5-2	60	
Other Accessories:									
Partition Plate									
Neutral Connection Block (4 mm) Blue	*	1492-JNC4-B	50	—	—	—	—	—	—
Neutral Connection Bloc (16 mm) Blue	*	1492-JNC16-B	50	—	—	—	—	—	—
Neutral Bus Bar (1 m)	1492-NBB3-1M		5	—	—	—	—	—	—
Marking Systems:									
Snap-in Marker Cards	1492-M5X5 (200/card)		5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5

* These terminals mount on Cat. No. 1492-NBB3-1M Neutral Busbar. They can accept Cat. No. 1492-M6X5 snap-in markers.

Spring-Clamp Connection Terminal Blocks



Fuse Blocks

1492-RFB4...

1492-RAFB4...

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications			Single-circuit fuse terminal block with or without blown fuse indicator			Single-circuit fuse terminal block with or without blown fuse indicator		
Certifications				cUR	IEC		cUR	IEC
Maximum Current			15 A*	15 A*	15 A*	12 A	12 A	12 A
Wire Range (Rated Cross Section)			#22...12 AWG	#22...12 AWG	0.5...4 mm ²	#22...12 AWG	#22...12 AWG	0.5...4 mm ²
Voltage Rating			RFB4/RAFB4	300V AC/DC	500V AC/DC	RFB4/RAFB4	300V AC/DC	500V AC/DC
			RFB424/RAFB424	10...57V AC/DC		RFB424/RAFB424	10...57V AC/DC	
			RFB4250/RAFB4250	85...264V AC		RFB4250/RAFB4250	85...264V AC	
Indicator Type			RFB4/RAFB4	Non-indicating		RFB4/RAFB4	Non-indicating	
			RFB424/RAFB424	LED		RFB424/RAFB424	LED	
			RFB4250/RAFB4250	Neon		RFB4250/RAFB4250	Neon	
Leakage Current			RFB4/RAFB4	—		RFB4/RAFB4	—	
			RFB424/RAFB424	2 mA @ 24V		RFB424/RAFB424	2 mA @ 24V	
			RFB4250/RAFB4250	1 mA @ 264V		RFB4250/RAFB4250	1 mA @ 264V	
Fuse Size (Not Supplied)				5 x 20 mm			1/4 x 1 -1/4 in.	
Wire Strip Length				0.47 in. (12 mm)			0.47 in. (12 mm)	
Density				37 pcs/ft (125 pcs/m)			30 pcs/ft (100 pcs/m)	
Insulation Temperature Range				-4...+140 °F (-20...+60 °C)			-4...+221 °F (-40...+105 °C)	
Terminal Blocks			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color			Black (Non-Indicating)	1492-RFB4	25	Black (Non-Indicating)	1492-RAFB4	25
			Black (10...57V LED)	1492-RFB424	25	Black (10...57V LED)	1492-RAFB424	25
			Black (85...264V Neon)	1492-RFB4250	25	Black (85...264V Neon)	1492-RAFB4250	25
Accessories			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails								
1 m Symmetrical DIN (Steel)			199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)			1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)			1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)			1492-DR7	2		1492-DR7	2	
End Barrier			Not Required	—		Not Required	—	
End Retainers/Anchors								
Screwless End Retainer			1492-ERL35	20		1492-ERL35	20	
DIN Rail — Heavy Duty			1492-EAHJ35	50		1492-EAHJ35	50	
Plug-in Center Jumper, 10-Pole			1492-CJR8-10	10		—	—	
Plug-in Center Jumper, 9-Pole			1492-CJR8-9	10		—	—	
Plug-in Center Jumper, 8-Pole			1492-CJR8-8	10		—	—	
Plug-in Center Jumper, 7-Pole			1492-CJR8-7	10		—	—	
Plug-in Center Jumper, 6-Pole			1492-CJR8-6	10		—	—	
Plug-in Center Jumper, 5-Pole			1492-CJR8-5	10		1492-CJRA10-5	10	
Plug-in Center Jumper, 4-Pole			1492-CJR8-4	10		1492-CJRA10-4	10	
Plug-in Center Jumper, 3-Pole			1492-CJR8-3	10		1492-CJRA10-3	10	
Plug-in Center Jumper, 2-Pole			1492-CJR8-2	10		1492-CJRA10-2	10	
Center Jumper Link			1492-CJRL6	10		1492-CJRL5	10	
Marking Systems								
Snap-in Marker for Block			1492-MS8X12 (56/card)	5		1492-MS8X12 (56/card)	5	
Snap-in Marker for Handle			1492-MS6X9 (80/card)	5		1492-MS6X9 (80/card)	5	


* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.

Spring-Clamp Connection Terminal Blocks

Single-Circuit Automotive Fuse Block

1492-LAFB6

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.





Single-circuit automotive style fuse terminal block with or without LED blown fuse indication

Specifications				
Certifications			CSA	IEC
Voltage Rating	-LAFB6	300V AC/DC		250V AC/DC
	-LAFB624	10...36V AC/DC		
Maximum Current		30 A	25 A	30 A
Wire Range (Rated Cross Section)		#22...12 AWG	#22...10 AWG	0.5...6 mm ²
Wire Strip Length		0.394 in. (10 mm)		
Density		37 pcs/ft (123 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)		
Terminal Blocks		Cat. No.		Pkg Qty.
Color	Black (without blown fuse indication)	1492-LAFB6		25
	Black (with blown fuse indication)	1492-LAFB624		25
Accessories		Cat. No.		Pkg Qty.
Mounting Rails				
1 m Symmetrical DIN (Steel)		199-DR1		10
1 m Symmetrical DIN (Aluminum)		1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2
End Barrier	Black	1492-EBLAFB6		50
End Anchors				
Screwless End Retainer		1492-ERL35		20
DIN Rail - Normal Duty		1492-EAJ35		100
Din Rail - Heavy Duty		1492-EAHJ35		50
Jumpers				
Plug-in Center Jumper — 32-Pole		1492-CJL8-32		10
Plug-in Center Jumper — 4-Pole		1492-CJL8-4		60
Plug-in Center Jumper — 3-Pole		1492-CJL8-3		60
Plug-in Center Jumper — 2-Pole		1492-CJL8-2		60
Test Adapter		1492-TPL8		25
Marking Systems				
Snap-in Marker Cards		1492-M5X8 (144/card)		5
Snap-In Marker Cards		1492-M6X5 (200/card)		5

Spring-Clamp Connection Terminal Blocks

Plug-in Connection Blocks

1492-LC3			1492-LDC3			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.						
Specifications	Feed-through terminal block with plug in comb connection on one side.		Two Circuit terminal block with plug in comb connection on one side of each circuit			
Certifications		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		250V AC/DC		300V AC/DC	
Maximum Current	10 A		16 A		10 A	
Wire Range (Rated Cross Section)	#26...12 AWG		2.5 mm²		#26...14 AWG	
Wire Strip Length	0.39 in. (10 mm)		0.39 in. (10 mm)			
Density	59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color	Grey	1492-LC3	50	1492-LDC3		50
Plug Connection Strips	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color/Quantity	Black/2-Pole	1492-QP5-2	100	1492-QP5-2		100
	Black/3-Pole	1492-QP5-3	100	1492-QP5-3		100
	Black/4-Pole	1492-QP5-4	100	1492-QP5-4		100
	Black/5-Pole	1492-QP5-5	50	1492-QP5-5		50
	Black/6-Pole	1492-QP5-6	50	1492-QP5-6		50
	Black/7-Pole	1492-QP5-7	50	1492-QP5-7		50
	Black/8-Pole	1492-QP5-8	50	1492-QP5-8		50
	Black/9-Pole	1492-QP5-9	50	1492-QP5-9		50
	Black/10-Pole	1492-QP5-10	50	1492-QP5-10		50
	Black/11-Pole	1492-QP5-11	50	1492-QP5-11		50
	Black/12-Pole	1492-QP5-12	50	1492-QP5-12		50
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails						
1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2
End Barriers	Grey	1492-EBLC3	20	1492-EBLDC3		20
End Anchors and Retainers:						
Screwless End Retainer	1492-ERL35		20	1492-ERL35		20
DIN Rail — Normal Duty	1492-EAJ35		100	1492-EAJ35		100
DIN Rail — Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50
Jumpers						
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-50		10	1492-CJLJ5-50		10
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-10		20	1492-CJLJ5-10		20
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-9		20	1492-CJLJ5-9		20
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-8		20	1492-CJLJ5-8		20
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-7		20	1492-CJLJ5-7		20
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-6		20	1492-CJLJ5-6		20
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-5		20	1492-CJLJ5-5		20
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-4		60	1492-CJLJ5-4		60
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-3		60	1492-CJLJ5-3		60
Plug-in Center Jumper — 2-Pole	1492-CJLJ5-2		60	1492-CJLJ5-2		60
Other Accessories						
Group Marking Carrier	1492-GM35		25	1492-GM35		25
Marking Systems						
Snap-In Marker Cards	1492-M5X10 (144/card)		5	1492-M5X10 (144/card)		5
Snap-In Marker Cards	1492-M5X5 (200/card)		5	1492-M5X5 (200/card)		5
Hinged Marker Card	1492-MH5X10 (96/card)		5	—		—

Spring-Clamp Connection Terminal Blocks









Short-Circuit Current Ratings

Short-Circuit Current Ratings — Fuse Ratings

Cat. No.	Wire Cu [AWG]		Overcurrent Protection Fuse Required Class/Max. Amp Rating						Maximum Voltage	SCCR, RMS SYM [A]
	Line	Load	J	T	RK1	RK5	G	CC		
1492-L3	14...12	14...12	30	30	—	—	30	30	600	100,000
1492-L3Q										
1492-L3T										
1492-LD3										
1492-L3QS										
1492-LMJ3										
1492-LMJG3										
1492-LKD3										
1492-L3P										
1492-LG3T										
1492-LG3Q										
1492-LG3										
1492-LD3C										
1492-LDG3C										
1492-LDG3										
1492-LC3	14...12	14...12	30	30	—	—	30	30	300	100,000
1492-LDC3										
1492-LDG3P										
1492-LDG3ND										
1492-LDG3N										
1492-LD3N										
1492-LD31P										
1492-LD3Q2P										
1492-LG31P										
1492-LG3T1P										
1492-L3T1P										
1492-LDG3FB										
1492-L4	14...10	14...10	60	60	30	—	30	30	600	100,000
1492-L4Q										
1492-L4T										
1492-LD4										
1492-LD4C										
1492-LG4										
1492-LG4T										
1492-LG4Q										
1492-LD4DFX2										
1492-L6	14...8	14...8	60	60	30	—	60	30	600	100,000
1492-L6T										
1492-LG6										
1492-LG6T	14...8	14...8	60	60	30	—	60	30	300	100,000
1492-LAFB6	14...8	14...8	60	60	30	—	60	30	300	100,000
1492-L10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-LG10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-L16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-LG16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-L35	12...2	12...2	200	200	100	30	60	30	600	100,000
1492-LG35	12...2	12...2	200	200	100	30	60	30	600	100,000



Mounting rails allow many blocks to be fastened in a panel with only a few screws to anchor the rail to the panel. Mounting rails allow easy installation and removal of a block in a row.

Cat. No.	Description	Pkg Qty.	Dimensions*
 199-DR1	Symmetrical Rail 35 mm x 7.5 mm 3.28 ft (1 m) long Zinc-Plated Clear Chromated Steel EN60715 DIN #3	10	 #10-32 or M5 Recommended Maximum Mounting Screw Size
199-DR2	Same as Cat. No. 199-DR1, but length = 2 m	20	
 199-DR4	Heavy Duty Symmetrical Rail 35 mm x 15 mm 3.28 ft (1 m) long Zinc-Plated Clear Chromated Steel EN60715 DIN #3	5	
 1492-DR3	Mini 15 mm x 5.5 mm Rail 3.28 ft (1 m) long Zinc-Plated Clear Chromated Steel EN60715 DIN #2	5	 #8-32 or M4 Recommended Maximum Mounting Screw Size
 1492-DR5	Symmetrical Rail 35 mm x 7.5 mm 3.28 ft (1 m) long Copper-Free Aluminum EN60715 For Bul. 1492 Terminal Blocks Only DIN #3	10	 #12-24 or M5 Recommended Maximum Mounting Screw Size
 1492-DR6	Symmetrical Rail 35 mm x 7.5 mm 2.26 in. (57.4 mm) high 3.28 ft (1 m) long Copper-Free Aluminum For Bul. 1492 Terminal Blocks Only DIN #3	2	 Wire insulator plug for wire access through rail — use Heyco UB875
 1492-DR7	Symmetrical Rail 35 mm x 7.5 mm 2.80 in. (71.0 mm) high 3.28 ft (1 m) long Angled 30° Zinc-Plated, Chromated Steel DIN #3	2	 For mounting rail details, see Cat. No. 199-DR1
 1492-DR8	Symmetrical Rail 35 mm x 15 mm 3.28 ft (1 m) long Copper EN60715 DIN #3	5	
 1492-DR9	Symmetrical Rail 35 mm x 15 mm 3.28 ft (1 m) long Zinc-Plated Clear Chromated Steel EN60715 DIN #3	5	

* Dimensions shown in inches (millimeters). Dimensions are not intended to be used for manufacturing purposes.

⊛ 0.218 x 0.50 in. (5.5 x 12.7 mm) slotted mounting holes every 3 in. (76.2 mm) starting 1.69 in. (42.9 mm) from end.

‡ Dimensions in millimeters.

End Barriers

End barriers are required to provide the necessary insulation for the last terminal block in a group.



Dimensions Width x Length x Height	For Use With	Color	Pkg Qty.	Cat. No.
0.08 x 1.14 x 2.03 in. (2 x 28.9 x 51.5 mm)	1492-L2, LG2	Grey	50	1492-EBL2
		Blue	50	1492-EBL2-B
		Yellow	50	1492-EBL2-Y
0.08 x 1.14 x 2.48 in. (2 x 28.9 x 63 mm)	1492-L2T, LG2T	Grey	50	1492-EBL2T
		Blue	50	1492-EBL2T-B
		Yellow	50	1492-EBL2T-Y
0.08 x 1.14 x 2.95 in. (2 x 28.9 x 75 mm)	1492-L2Q, LG2Q	Grey	50	1492-EBL2Q
		Blue	50	1492-EBL2Q-B
		Yellow	50	1492-EBL2Q-Y
0.08 x 1.15 x 2.34 in. (2 x 29.1 x 59.5 mm)	1492-L3, LG3, LK3, L3P	Grey	50	1492-EBL3
		Blue	50	1492-EBL3-B
		Yellow	50	1492-EBL3-Y
0.08 x 1.20 x 2.54 in. (2 x 30.6 x 64.5 mm)	1492-L3T, LG3T	Grey	50	1492-EBL3T
		Blue	50	1492-EBL3T-B
		Yellow	50	1492-EBL3T-Y
0.08 x 1.20 x 3.11 in. (2 x 30.6 x 79 mm)	1492-L3Q, L3QS, LG3Q	Grey	50	1492-EBL3Q
		Blue	50	1492-EBL3Q-B
		Yellow	50	1492-EBL3Q-Y
0.10 x 1.06 x 2.8 in. (2.5 x 27 x 71 mm)	1492-L31P, 1492-LG31P	Grey	50	1492-EBL31P
		Yellow	50	1492-EBL31P-Y
	1492-L3T1P, 1492-LG3T1P	Grey	50	1492-EBL3T1P
		Yellow	50	1492-EBL3T1P-Y
0.08 x 1.20 x 3.11 in. (2 x 30.6 x 79 mm)	1492-L3Q2P	Grey	50	1492-EBL3Q2P
0.10 x 1.76 x 3.17 in. (2.5 x 44.7 x 80.5)	1492-LD32P	Grey	50	1492-EBLD32P
0.08 x 1.37 x 2.44 in. (2 x 34.85 x 62 mm)	1492-L4, LG4	Grey	50	1492-EBL4
		Blue	50	1492-EBL4-B
		Yellow	50	1492-EBL4-Y
0.08 x 1.37 x 3.31 in. (2 x 34.85 x 84 mm)	1492-L4T, LG4T	Grey	50	1492-EBL4T
		Blue	50	1492-EBL4T-B
		Yellow	50	1492-EBL4T-Y
0.08 x 1.37 x 4.13 in. (2 x 34.85 x 105 mm)	1492-L4Q, LG4Q	Grey	50	1492-EBL4Q
		Blue	50	1492-EBL4Q-B
		Yellow	50	1492-EBL4Q-Y
0.08 x 1.45 x 2.56 in. (2 x 36.95 x 65 mm)	1492-L6, LG6	Grey	50	1492-EBL6
		Blue	50	1492-EBL6-B
		Yellow	50	1492-EBL6-Y
0.08 x 1.45 x 3.54 in. (2 x 36.95 x 90 mm)	1492-L6T, LG6T	Grey	50	1492-EBL6T
		Blue	50	1492-EBL6T-B
		Yellow	50	1492-EBL6T-Y
0.12 x 1.67 x 2.89 in. (3 x 42.5 x 73.5 mm)	1492-L10, LG10	Grey	20	1492-EBL10
		Blue	20	1492-EBL10-B
		Yellow	20	1492-EBL10-Y
0.12 x 1.71 x 3.25 in. (3 x 43.5 x 82.5 mm)	1492-L16, LG16	Grey	20	1492-EBL16
		Blue	20	1492-EBL16-B
		Yellow	20	1492-EBL16-Y
—	1492-LAFB6	Black	50	1492-EBLAFB6
0.08 x 1.65 x 2.95 in. (2 x 41.9 x 75 mm)	1492-LD2, LDG2, LD2C, LDG2C	Grey	50	1492-EBLD2
		Blue	20	1492-EBLD2-B
		Yellow	20	1492-EBLD2-Y
0.08 x 1.87 x 2.85 in. (2 x 47.5 x 72.5 mm)	1492-LD3, LD3C, LDG3, LDG3C	Grey	20	1492-EBLD3
		Blue	20	1492-EBLD3-B
		Yellow	20	1492-EBLD3-Y
0.08 x 2.05 x 2.99 in. (2 x 52 x 76 mm)	1492-LD4, LD4C, LDG4, LDG4C, LD4DF, LD4DR, LD4RB..., LD4SS	Grey	20	1492-EBLD4
		Blue	20	1492-EBLD4-B
		Yellow	20	1492-EBLD4-Y

End Barriers, continued

Dimensions Width x Length x Height	For Use With	Color	Pkg Qty.	Cat. No.
0.20 x 0.94 x 1.31 in. (5.1 x 23.8 x 33.3 mm)	1492-LMP3, LMP3Q	Grey	50	1492-EBLMP3
		Blue	50	1492-EBLMP3-B
0.20 x 0.94 x 1.31 in. (5.1 x 23.8 x 33.3 mm)	1492-LM3, LM3Q, LMG3, LMP3E, LMP3QE	Grey	50	1492-EBLM3
		Blue	50	1492-EBLM3-B
		Yellow	50	1492-EBLM3-Y
0.06 x 0.97 x 1.38 in. (1.5 x 24.65 x 35 mm)	1492-LMJ3, LMJG3	Grey	50	1492-EBLMJ3
		Blue	50	1492-EBLMJ3-B
		Yellow	50	1492-EBLMJ3-Y
0.06 x 2.32 x 4.35 in. (1.5 x 59 x 110.5 mm)	1492-LTF3	Grey	20	1492-EBLTF3
0.06 x 2.69 x 1.77 in. (5 x 68.5 x 45 mm)	1492-LS2-3, LS2-3L, LSG2-3		50	1492-EBLS2-3
0.20 x 3.2 x 1.77 in. (5 x 81.5 x 45 mm)	1492-LS2-4, LS2-4L, LSG2-4		50	1492-EBLS2-4
0.06 x 1.81 x 3.74 in. (1.5 x 46 x 95 mm)	1492-LDAG3, LDG3P		20	1492-EBLDAG3
0.10 x 1.04 x 1.81 in. (2.5 x 26.4 x 46 mm)	1492-LC3		20	1492-EBLC3
0.10 x 1.65 x 2.72 in. (2.5 x 41.85 x 69 mm)	1492-LDC3		20	1492-EBLDC3
—	1492-LDG3ND, LD3N, LDG3N	Grey	20	1492-BSPJLD3N
—	1492-LDG3ND, LD3N, LDG3N	Blue	20	1492-BSPJLD3N-B

End Anchor/End Retainers

End anchors and end retainers mount at both ends of a group of terminal blocks to add rigidity to the terminal assembly and prevent sliding along the rails.

Photo	Dimensions Width x Length x Height	Tightening Torque	Markers	For Use With	Color	Pkg Qty.	Cat. No.
	0.31 x 2.20 x 1.85 in. (8 x 56 x 47 mm)	4.4 lb•in. (0.5 N•m)	1492-M7X12 1492-M8X5	199-DR1, 199-DR2, 1492-DR4, 1492-DR5, 1492-DR6, 1492-DR7, 1492-DR8, 1492-DR9	Grey	100	1492-EAJ35
	0.48 x 2.20 x 2.48 in. (12.2 x 56 x 63 mm)	4.4 lb•in. (0.5 N•m)	1492-M7X12 1492-M5X5	199-DR1, 199-DR2, 1492-DR4, 1492-DR5, 1492-DR6, 1492-DR7, 1492-DR8, 1492-DR9	Grey	50	1492-EAHJ35
	0.31 x 1.06 x 1.06 in. (8 x 27 x 27 mm)	3.5 lb•in. (0.9 N•m)	1492-M5X5	1492-DR3	Grey	50	1492-EAJ15
	0.24 x 2.19 x 1.63 in. (6 x 55.6 x 41.5 mm)	—	1492-M5X10 1492-M5X5	199-DR1, 199-DR2, 1492-DR4, 1492-DR5, 1492-DR6, 1492-DR7, 1492-DR8, 1492-DR9	Grey	20	1492-ERL35
	0.20 x 0.96 x 0.75 in. (5 x 24.5 x 19 mm)	—	1492-M5X10 1492-M5X5	1492-DR3	Grey	20	1492-ERL15


IEC Terminal Block Accessories

Partition and Separation Plates

Partition Plates and Separation Plates

Partition plates allow visual and electrical separation of terminal groups and provide the necessary electrical spacing between adjacent insulated jumpers or between exposed ends of cut jumpers.

Separation plates consist of flexible thermoplastic material and are used between terminal blocks to isolate adjacent center jumpers both visually and electrically.



Dimensions Width x Length x Height	For Use With	Color	Pkg Qty.	Cat. No.
Partition Plates				
0.118 x 3.15 x 2.48 in. (3 x 80 x 63 mm)	1492-JD3, JD3C, JD3F, JD3DF, JD3DR, JD3RC..., JD3SS	Grey	20	1492-PPJD3
0.005 x 3.54 x 2.51 in. (0.13 x 90.1 x 63.8 mm)	1492-JD3P..., JDG3P...	Beige	20	1492-PPJD3P
0.08 x 1.57 x 1.20 in. (2 x 40 x 30.5 mm)	1492-WM3, WM4, WMG3, WMG4	Grey	50	1492-PPM3
0.014 x 2.28 x 1.51 in. (0.35 x 58 x 38.3 mm)	1492-WMD1	Grey	50	1492-PPMD1
0.06 x 1.85 x 1.57 in. (1.5 x 47 x 40 mm)	1492-W3, W4, WG4	Grey	50	1492-PP3
0.06 x 2.17 x 1.81 in. (1.5 x 55 x 46 mm)	1492-W6, W10, W16S, W4TW, WG6, WG10S, WG16S	Grey	50	1492-PP10
0.014 x 2.88 x 1.85 in. (0.35 x 73.2 x 47.1 mm)	1492-WTF3..., WTS3...	Beige	50	1492-PPTS3
0.06 x 1.93 x 2.36 in. (1.5 x 49 x 60 mm)	1492-J3, J4, J6, J10, J2Q, J3TW, J3F, JG2Q, JG3, JG3TW, JKD3, JKD3TP, J3P, J3PTP, JTC3	Grey	20	1492-EBJ16
		Blue	20	1492-EBJ16-B
		Yellow	20	1492-EBJ16-Y
Separation Plates				
.014 x 1.76 x 1.57 in. (0.35 x 44.8 x 40.0 mm)	1492-W3, W4	Beige	50	1492-SP3
	All 1492-FPK2 Fuse Plugs	Beige	50	1492-SPJ3