

Screw Connection Terminal Blocks



Fuse Blocks

1492-JD3FB

1492-JDG3FB

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Two-level terminal block with feed-through circuit and hinged-arm fuse circuit				Three-Level terminal block with feed-through circuit, hinged-arm fuse circuit, and ground point			
Certifications			CSA	IEC			CSA	IEC
Voltage Rating	300V AC/DC			500V AC/DC	300V AC/DC			500V AC/DC
Maximum Fuse Circuit Current	10 A	10 A/250V	6.3 A❄	10 A	10 A/250V	6.3 A❄		
Feed-through Circuit	20 A	25 A		20 A	25 A			
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	0.5...4 mm ²	#22...12 AWG	#26...12 AWG	0.5...4 mm ²		
Fuse Size (Not Supplied)	5 x 20 mm			5 x 20 mm				
Wire Strip Length	0.35 in. (9 mm)			0.35 in. (9 mm)				
Recommended Tightening Torque	5.5 lb•in (0.6 N•m)			5.5 lb•in (0.6 N•m)				
Density	38 pcs/ft (125 pcs/m)			38 pcs/ft (125 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating	See page 12-42							
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color: Grey	1492-JD3FB			50	1492-JDG3FB			50
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails:								
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2
End Barrier Grey	1492-EBJD3FB			20	1492-EBJD3FB			20
End Anchors:								
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20
DIN Rail - Normal Duty	1492-EAJ35			100	1492-EAJ35			100
DIN Rail - Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50
Jumpers:								
Side Jumper — 4-pole	1492-SJ8A-4			50	1492-SJ8A-4			50
Side Jumper — 3-pole	1492-SJ8A-3			50	1492-SJ8A-3			50
Side Jumper — 2-pole	1492-SJ8A-2			50	1492-SJ8A-2			50
End Anchor Top Marker Carrier❄	1492-GMC			50	1492-GMC			50
Cat. No. 1492-GMC Top Marker Tag	1492-M5X30 (20/card)			5	1492-M5X30 (20/card)			5
Marking Systems:								
Snap-in marker cards (Handle)	1492-M7X12 (108/card)			5	1492-M7X12 (108/card)			5
Snap-in marker cards (Handle)	1492-MR6X8 (120/card)			5	1492-MR6X8 (120/card)			5
Snap-in marker cards (Side)	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5

* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.

* The Bulletin 1492-GMC marker carrier installs directly on the top of a 1492-EAJ35 end anchor or a 1492-ERL35 end retainer for group marking purposes.