





	Jumbo Push-Pull Cap For use on Bul. 800T or 800H push-pull operators. Fits on illuminated and non-illuminated devices.		
	Bul. 800T 63 mm Red Anodized Aluminum Cap For use on Bul. 800T non-illuminated push-pull devices.		800T-N210R
	Bul. 800T 63 mm Red Anodized Aluminum Cap with "E-Stop" For use on Bul. 800T non-illuminated push-pull devices.		800T-N210RE
Cat. No. 800T-N209RE1	Bul. 800T 90 mm Gold Anodized Aluminum Cap For use on Bul. 800T non-illuminated push-pull devices.		800T-N211GL
	Bul. 800T Bonding Bracket The bonding bracket establishes an electrical circuit between the mounting surface and metal operator bushing for grounding purposes; recommended for installations which require CSA approval. Necessary mounting hardware is included. Order Cat. No. 800T-N300 for back-of-panel bracket. Order Cat. No. 800T-N300F for front-of-panel bracket.		800T-N300
	Cat. No. 800T-N300		* 800T-N300F
	Bul. 800T/H Lens/Bulb Removal Tool The small end of this tool provides quick and easy removal of any incandescent or LED lamp.		800F-ALR1
	Cat. No. 800F-ALR1		







* Must be ordered in multiples of 5 pieces.

			Description	Cat. No.	
	Cat. No. 800T-N323		Bul. 800T/H Finger-Safe Terminal Guards Snap-on accessories which provide IEC, IP2X and VGB finger-safe protection. Single terminal guards for single circuit contact blocks, full voltage modules, LED modules, etc. (800T-XD1, -XD2, -XD3, -XD4, -XD5, -XD6, -XAP, -XD1P, -XD2P, -PC..., and -QC...)* Note: Must be ordered in multiples of 100 pieces.	800T-N322	
Cat. No. 800T-N324		Cat. No. 800T-N322	Transformer covers for transformer only. Note: Must be ordered in multiples of 25 pieces.	800T-N324	
Finger-Safe Accessories			Multi-terminal side cover for use on single or double circuit contact blocks. (800T-XA, -XA1, -XA2, -XA4, -XA7, -XAR, -XA2R, -XA4R, -XD1R, and -XD2R) Note: Must be ordered in multiples of 25 pieces.	800T-N323	
			Potentiometer unit terminal cover Note: Must be ordered in multiples of 5	800T-N373	
			Grey Bul. 800T Trim Washer Used to mount the operator properly when a legend plate is not being used. Note: Must be ordered in multiples of 10 pieces.	800T-N292	
			Plastic Bul. 800H Trim Washer Used to mount the operator properly when a legend plate is not being used. Note: Must be ordered in multiples of 10 pieces.	800H-N148	
Cat. No. 800T-N292					
			Metal Bul. 800T Thrust Washer Used to prevent rotation of operators in a keyed or notched hole. Note: Must be ordered in multiples of 10 pieces.	800T-N293	
			Plastic Bul. 800H Thrust Washer Used to prevent rotation of operators in a keyed or notched hole. Note: Must be ordered in multiples of 10 pieces.	800H-N146	
Cat. No. 800T-N293					
			Bul. 800T/H Panel Gasket Used for dust, oil, and water ingress protection. Note: Must be ordered in multiples of 10 pieces.	800T-N19	
			Description	Color	Cat. No.
			Bul. 800T/H	Grey	800T-N1

	Closing Button Where an enclosure or flush plate with more than the required number of openings is used, this neat-appearing button can be supplied to close the unused openings.		
	Cat. No. 800T-N1	Black	800T-N1B

* Power modules excluding transformers and dual inputs

Locking Attachments

	Description	Cat. No.
 <p>Cat. No. 800T-N2 (Padlock not included)</p>	Bul. 800T Extended Head Push Button Padlocking Attachments Permits locking in the depressed position. Locks the normally closed contact in the open position. For extended head non-illuminated momentary push buttons.	800T-N2
 <p>Cat. No. 800H-N6 (Padlock not included)</p>	Bul. 800H Extended Head Push Button Padlocking Attachments Can be applied to either the momentary or maintained contact push button units. Padlocks an extended, non-illuminated STOP button in the depressed position. Kit includes padlocking attachment and STOP legend plate.	800H-N6
 <p>Cat. No. 800T-N10 (Padlock not included)</p>	Bul. 800T Flush Head Push Button Padlocking Attachments Permits locking in the depressed position. Locks the normally closed contact in the open position. For flush head push button.	800T-N10
 <p>Cat. No. 800T-N315 (Padlock not included)</p>	Bul. 800T Momentary Mushroom Padlocking Attachments For Bul. 800T non-illuminated momentary mushroom push button. Requires use of Cat. No. 800T-N311 mushroom cap. This device is used to lock the mushroom button in a depressed position.	800T-N315
 <p>Cat. No. 800T-N314 (Padlock not included)</p>	Bul. 800T/H Push-Pull Padlocking Attachment For 2-position push-pull and push-pull/twist release illuminated and non-illuminated operators. Use on standard head only (40 mm dia.). Locks the normally closed contacts open only. Conversion of normally closed late break contacts to standard normally closed contacts are recommended when using this accessory. Made of stainless steel.	800T-N314
	Bul. 800T/H Padlocking Cover Guards against unauthorized operation for non-illuminated, standard knob selector switches and potentiometers. Stainless steel and clear plastic construction.	800T-N163