





Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L3				1492-L3T				1492-L3Q					
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.														
Specifications	Feed-through terminal block				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 2 points on each side					
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX		
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC		
Maximum Current	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A		
Wire Range (Rated Cross Section)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)		
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)					
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating (SCCR)	See page 12-78													
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.			
Color	Grey		1492-L3		100		1492-L3T		100		1492-L3Q		100	
	Red		1492-L3-RE		100		1492-L3T-RE		100		1492-L3Q-RE		100	
	Blue		1492-L3-B		100		1492-L3T-B		100		1492-L3Q-B		100	
	Black		1492-L3-BL		100		1492-L3T-BL		100		1492-L3Q-BL		100	
	Green		1492-L3-G		100		1492-L3T-G		100		1492-L3Q-G		100	
	Yellow		1492-L3-Y		100		1492-L3T-Y		100		1492-L3Q-Y		100	
	Orange		1492-L3-OR		100		1492-L3T-OR		100		1492-L3Q-OR		100	
	Brown		1492-L3-BR		100		1492-L3T-BR		100		1492-L3Q-BR		100	
	White		1492-L3-W		100		1492-L3T-W		100		1492-L3Q-W		100	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.			
Mounting Rails	199-DR1		10		199-DR1		10		199-DR1		10			
1 m Symmetrical DIN (Steel)	1492-DR5		10		1492-DR5		10		1492-DR5		10			
1 m Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2			
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR7		2		1492-DR7		2		1492-DR7		2			
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-EBL3		50		1492-EBL3T		50		1492-EBL3Q		50			
End Barriers	Grey		50		Grey		50		Grey		50			
	Blue		50		Blue		50		Blue		50			
	Yellow		50		Yellow		50		Yellow		50			
End Anchors and Retainers	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20			
Screwless End Retainer	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100			
DIN Rail — Normal Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50			
DIN Rail — Heavy Duty	1492-CJK5-50		10		1492-CJK5-50		10		1492-CJK5-50		10			
Jumpers	1492-CJK5-10		20		1492-CJK5-10		20		1492-CJK5-10		20			
Plug-in Center Jumper — 50-Pole	1492-CJK5-9		20		1492-CJK5-9		20		1492-CJK5-9		20			
Plug-in Center Jumper — 10-Pole	1492-CJK5-8		20		1492-CJK5-8		20		1492-CJK5-8		20			
Plug-in Center Jumper — 9-Pole	1492-CJK5-7		20		1492-CJK5-7		20		1492-CJK5-7		20			
Plug-in Center Jumper — 8-Pole	1492-CJK5-6		20		1492-CJK5-6		20		1492-CJK5-6		20			
Plug-in Center Jumper — 7-Pole	1492-CJK5-5		20		1492-CJK5-5		20		1492-CJK5-5		20			
Plug-in Center Jumper — 6-Pole	1492-CJK5-4		60		1492-CJK5-4		60		1492-CJK5-4		60			
Plug-in Center Jumper — 5-Pole	1492-CJK5-3		60		1492-CJK5-3		60		1492-CJK5-3		60			
Plug-in Center Jumper — 4-Pole	1492-CJK5-2		60		1492-CJK5-2		60		1492-CJK5-2		60			
Plug-in Center Jumper — 3-Pole	1492-PSL3-2		100		1492-PSL3-2		100		1492-PSL3-2		100			
Plug-in Center Jumper — 2-Pole	1492-PSL3-5		100		1492-PSL3-5		100		1492-PSL3-5		100			
Other Accessories	1492-PSL3-10		100		1492-PSL3-10		100		1492-PSL3-10		100			
Reducing Sleeves #30...#24 AWG (0.13...0.2 mm ²) White	1492-TP23		20		1492-TP23		20		1492-TP23		20			
Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey	1492-TPL5		25		1492-TPL5		25		1492-TPL5		25			
Reducing Sleeves #18 AWG (0.75...1.0 mm ²) Dark Grey	1492-EWPL5		20		1492-EWPL5		20		1492-EWPL5		20			
Test Plug	1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5			
Test Plug (Stackable)	1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5			
Electrical Warning Plate	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5			
Marking Systems	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5			
Snap-In Marker Cards	1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5			
Snap-In Marker Cards	1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5			
Hinged Marker Cards	1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5			
Hinged Marker Cards	1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5			

1492-LKD3

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	<i>Knife disconnect feed-through terminal block</i>		
Certifications	UL	CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC
Maximum Current	20 A		24 A
Wire Range (Rated Cross Section)	#30...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		

Terminal Blocks		Cat. No.	Pkg Qty.
Color	Grey	1492-LKD3	25
Accessories		Cat. No.	Pkg Qty.
Mounting Rails			
1 m Symmetrical DIN (Steel)		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2
End Barriers	Grey	1492-EBL3	50
End Anchors and Retainers			
Screwless End Retainer		1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50
Jumpers			
Plug-in Center Jumper — 50-Pole		1492-CJK5-50	10
Plug-in Center Jumper — 10-Pole		1492-CJK5-10	20
Plug-in Center Jumper — 9-Pole		1492-CJK5-9	20
Plug-in Center Jumper — 8-Pole		1492-CJK5-8	20
Plug-in Center Jumper — 7-Pole		1492-CJK5-7	20
Plug-in Center Jumper — 6-Pole		1492-CJK5-6	20
Plug-in Center Jumper — 5-Pole		1492-CJK5-5	20
Plug-in Center Jumper — 4-Pole		1492-CJK5-4	60
Plug-in Center Jumper — 3-Pole		1492-CJK5-3	60
Plug-in Center Jumper — 2-Pole		1492-CJK5-2	60
Other Accessories			
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White		1492-PSL3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey		1492-PSL3-5	100
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey		1492-PSL3-10	100
Test Plug		1492-TP23	20
Test Plug (Stackable)		1492-TPL5	25
Electrical Warning Plate		1492-EWPL5	20
Marking Systems			
Snap-In Marker Cards		1492-M5X10 (144/card)	5
Snap-In Marker Cards		1492-M5X5 (200/card)	5

Spring-Clamp Connection Terminal Blocks

Plug-In Style Blocks & Analog Loop Control Block

	1492-L3P			1492-LDG3P			1492-LDAG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single circuit plug-in component block for a variety of components			Terminal block with slot for plug-in component, feed-through circuit and 1 ground connection			Analog Loop Control Terminal Block with 2 Feed-Through Circuits and 1 Ground Connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC			300V AC/DC			300V AC/DC		
Maximum Current	20 A			10 A			10 A		
Wire Range (Rated Cross Section)	#30...12 AWG			#26...12 AWG			#26...12 AWG		
Wire Strip Length	0.39 in. (10 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey								
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier	1492-EBL3	50		1492-EBLDAG3	20		1492-EBLDAG3	20	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-In Center Jumper — 50-pole	1492-CJK5-50	10		1492-CJLJ5-50	10		1492-CJLJ5-50	10	
Plug-In Center Jumper — 10-pole	1492-CJK5-10	20		1492-CJLJ5-10	20		1492-CJLJ5-10	20	
Plug-In Center Jumper — 9-pole	1492-CJK5-9	20		1492-CJLJ5-9	20		1492-CJLJ5-9	20	
Plug-In Center Jumper — 8-pole	1492-CJK5-8	20		1492-CJLJ5-8	20		1492-CJLJ5-8	20	
Plug-In Center Jumper — 7-pole	1492-CJK5-7	20		1492-CJLJ5-7	20		1492-CJLJ5-7	20	
Plug-In Center Jumper — 6-pole	1492-CJK5-6	20		1492-CJLJ5-6	20		1492-CJLJ5-6	20	
Plug-In Center Jumper — 5-pole	1492-CJK5-5	20		1492-CJLJ5-5	20		1492-CJLJ5-5	20	
Plug-In Center Jumper — 4-pole	1492-CJK5-4	60		1492-CJLJ5-4	60		1492-CJLJ5-4	60	
Plug-In Center Jumper — 3-pole	1492-CJK5-3	60		1492-CJLJ5-3	60		1492-CJLJ5-3	60	
Plug-In Center Jumper — 2-pole	1492-CJK5-2	60		1492-CJLJ5-2	60		1492-CJLJ5-2	60	
Other Accessories									
Disconnect Plug	1492-DPL	50		1492-DPL	50		—	—	
Component Plug	1492-CPL	50		1492-CPL	50		—	—	
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20		1492-FPK2	20		—	—	
10...36V Blown Fuse Indicator	1492-FPK224	20	*	1492-FPK224	20		—	—	
35...70V Blown Fuse Indicator	1492-FPK248	20	*	1492-FPK248	20		—	—	
60...150V Blown Fuse Indicator	1492-FPK2120	20	*	1492-FPK2120	20		—	—	
140...250V Blown Fuse Indicator	1492-FPK2250	20	*	1492-FPK2250	20		—	—	
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL3-2	100		—	—		—	—	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL3-5	100		—	—		—	—	
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL3-10	100		—	—		—	—	
Test Plug	1492-TPL5	25		1492-TP23	20		—	—	
Electrical Warning Plate	1492-EWPL5	20		—	—		—	—	
Marking Systems									
Snap-In Marker Cards	1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5	
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	

* When using Cat. No. 1492-LDG3P with a fuse plug, a center jumper cannot be used on the top level. The only jumper option to use in combination with a fuse plug is a 2-pole side jumper: Cat. No. 1492-SJLM5-2.

End Barriers

End barriers are required to provide the necessary insulation for the last terminal block in a group.



Dimensions Width x Length x Height	For Use With	Color	Pkg Qty.	Cat. No.
0.08 x 1.14 x 2.03 in. (2 x 28.9 x 51.5 mm)	1492-L2, LG2	Grey	50	1492-EBL2
		Blue	50	1492-EBL2-B
		Yellow	50	1492-EBL2-Y
0.08 x 1.14 x 2.48 in. (2 x 28.9 x 63 mm)	1492-L2T, LG2T	Grey	50	1492-EBL2T
		Blue	50	1492-EBL2T-B
		Yellow	50	1492-EBL2T-Y
0.08 x 1.14 x 2.95 in. (2 x 28.9 x 75 mm)	1492-L2Q, LG2Q	Grey	50	1492-EBL2Q
		Blue	50	1492-EBL2Q-B
		Yellow	50	1492-EBL2Q-Y
0.08 x 1.15 x 2.34 in. (2 x 29.1 x 59.5 mm)	1492-L3, LG3, LK3, L3P	Grey	50	1492-EBL3
		Blue	50	1492-EBL3-B
		Yellow	50	1492-EBL3-Y
0.08 x 1.20 x 2.54 in. (2 x 30.6 x 64.5 mm)	1492-L3T, LG3T	Grey	50	1492-EBL3T
		Blue	50	1492-EBL3T-B
		Yellow	50	1492-EBL3T-Y
0.08 x 1.20 x 3.11 in. (2 x 30.6 x 79 mm)	1492-L3Q, L3QS, LG3Q	Grey	50	1492-EBL3Q
		Blue	50	1492-EBL3Q-B
		Yellow	50	1492-EBL3Q-Y
0.10 x 1.06 x 2.8 in. (2.5 x 27 x 71 mm)	1492-L31P, 1492-LG31P	Grey	50	1492-EBL31P
		Yellow	50	1492-EBL31P-Y
	1492-L3T1P, 1492-LG3T1P	Grey	50	1492-EBL3T1P
		Yellow	50	1492-EBL3T1P-Y
0.08 x 1.20 x 3.11 in. (2 x 30.6 x 79 mm)	1492-L3Q2P	Grey	50	1492-EBL3Q2P
0.10 x 1.76 x 3.17 in. (2.5 x 44.7 x 80.5)	1492-LD32P	Grey	50	1492-EBLD32P
0.08 x 1.37 x 2.44 in. (2 x 34.85 x 62 mm)	1492-L4, LG4	Grey	50	1492-EBL4
		Blue	50	1492-EBL4-B
		Yellow	50	1492-EBL4-Y
0.08 x 1.37 x 3.31 in. (2 x 34.85 x 84 mm)	1492-L4T, LG4T	Grey	50	1492-EBL4T
		Blue	50	1492-EBL4T-B
		Yellow	50	1492-EBL4T-Y
0.08 x 1.37 x 4.13 in. (2 x 34.85 x 105 mm)	1492-L4Q, LG4Q	Grey	50	1492-EBL4Q
		Blue	50	1492-EBL4Q-B
		Yellow	50	1492-EBL4Q-Y
0.08 x 1.45 x 2.56 in. (2 x 36.95 x 65 mm)	1492-L6, LG6	Grey	50	1492-EBL6
		Blue	50	1492-EBL6-B
		Yellow	50	1492-EBL6-Y
0.08 x 1.45 x 3.54 in. (2 x 36.95 x 90 mm)	1492-L6T, LG6T	Grey	50	1492-EBL6T
		Blue	50	1492-EBL6T-B
		Yellow	50	1492-EBL6T-Y
0.12 x 1.67 x 2.89 in. (3 x 42.5 x 73.5 mm)	1492-L10, LG10	Grey	20	1492-EBL10
		Blue	20	1492-EBL10-B
		Yellow	20	1492-EBL10-Y
0.12 x 1.71 x 3.25 in. (3 x 43.5 x 82.5 mm)	1492-L16, LG16	Grey	20	1492-EBL16
		Blue	20	1492-EBL16-B
		Yellow	20	1492-EBL16-Y
—	1492-LAFB6	Black	50	1492-EBLAFB6
0.08 x 1.65 x 2.95 in. (2 x 41.9 x 75 mm)	1492-LD2, LDG2, LD2C, LDG2C	Grey	50	1492-EBLD2
		Blue	20	1492-EBLD2-B
		Yellow	20	1492-EBLD2-Y
0.08 x 1.87 x 2.85 in. (2 x 47.5 x 72.5 mm)	1492-LD3, LD3C, LDG3, LDG3C	Grey	20	1492-EBLD3
		Blue	20	1492-EBLD3-B
		Yellow	20	1492-EBLD3-Y
0.08 x 2.05 x 2.99 in. (2 x 52 x 76 mm)	1492-LD4, LD4C, LDG4, LDG4C, LD4DF, LD4DR, LD4RB..., LD4SS	Grey	20	1492-EBLD4
		Blue	20	1492-EBLD4-B
		Yellow	20	1492-EBLD4-Y