


1492-H...			1492-WFB4...		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block. 					
Specifications			Single-circuit fusible terminal block with or without fuse indication.		
Certifications			 CSA IEC		
Voltage Rating			Single-circuit fuse block with or without fuse indication.		
H6/WFB4			300V AC/DC		
H5/WFB424			10...57V AC/DC		
H4/WFB4250			100...300V AC		
Maximum Current			15 A		
Wire Range (Rated Cross Section)			#30...12 AWG		
Wire Strip Length			0.38 in. (9.7 mm)		
Recommended Tightening Torque			7.1 lb•in (0.8 N•m)		
Density			33 pcs/ft (109pcs /m)		
Housing Temperature Range			-40...+195 °F (-40...+90 °C)		
Indicator Type					
H6/WFB4			Non-Indicating		
H5/WFB424			Red LED		
H4/WFB4250			Neon		
Leakage Current					
H6/WFB4			—		
H5/WFB424			2 mA @ 24V		
H4/WFB4250			2 mA @ 300V		
Fuse Size (Not Supplied)			1/4 x 1-1/4 in.		
Short-Circuit Current Rating			See page 12-42		
Terminal Blocks			Cat. No.		
Black No-indication			1492-H6		
Color: Black w/LED			1492-H5		
Black w/Neon			1492-H4		
Accessories			Cat. No.		
Mounting Rails:			Pkg Qty.		
1 m Symmetrical DIN (Steel)			10		
1 m Symmetrical DIN (Aluminum)			10		
1 m Hi-Rise Sym. DIN (Aluminum)			2		
1 m Angled Hi-Rise Sym. DIN (Steel)			2		
3 ft Scored A-B Rail			20		
3 ft Rigid A-B Rail			20		
3 ft High Rise A-B Rail			2		
Standoff Brackets (Use Every 12 in.)			2		
End Barrier			50		
End Anchors and Retainers:			Cat. No.		
Screwless End Retainer			1492-ERL35		
DIN Rail — Normal Duty			1492-EAJ35		
DIN Rail — Heavy Duty			1492-EAHJ35		
A-B Rail — Heavy Duty			1492-N23		
10-Pole Side Jumper			1492-N49		
Side Jumper Insulating Sleeve			1492-SJS		
Other Accessories:			Cat. No.		
Partition Plate			1492-PPSL3		
Marking Systems:			Pkg Qty.		
Snap-In Marker Card — For Base Block			5		
For Handle			5		
Adhesive Labels			1		

* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.
 * Cat. No. 1492-N49 is uninsulated. Cat. No. 1492-SJFB8-10 is insulated.

IEC Terminal Block Accessories

Jumpers

Side Jumpers

For Use With	Pkg Qty.	Cat. No.
1492-WM4, W4	50	1492-N42
1492-H4, H5, H6, H7	10	1492-N49
	10	* 1492-SJS
1492-W3, WR3	10	1492-SJ5-10
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5A-10
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5A-24
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5B-24
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5B-10
1492-WM4, W4, W4TW	10	⚡ 1492-SJ6-10
1492-JT3M	5	1492-SJ6A-50
1492-W10	10	1492-SJ8-10
1492-JD3FB, JDG3FB	50	1492-SJ8A-4
1492-JD3FB, JDG3FB	50	1492-SJ8A-3
1492-JD3FB, JDG3FB	50	1492-SJ8A-2
1492-LMP3, LMP3Q, LMJ3, LM3, LM3Q, LMP3E, LMP3QE	50	1492-SJLM5-2
1492-WMD1	10	‡ 1492-SJMD5-12
1492-WFB4, WFB424, WFB4250	10	1492-SJFB8-10
1492-WM3	10	1492-SJM5-10
1492-WTF3, WTS3, WTF3LP, WTS3LP, WTF3LN, WTS3LN	10	1492-SJT5-20-R
1492-WTF3, WTS3, WTF3LP, WTS3LP, WTF3LN, WTS3LN	10	1492-SJT5-20-B

Note: Side jumpers carry the same current rating as the terminal block used with it

* Side jumper insulating sleeve only for use with Cat. No. 1492-N49

⚡ Use jumper on single side of terminal block only

‡ Uninsulated

Two-Level Jumper

For Use With	Pkg Qty.	Cat. No.
1492-LTF3 (Connects Two Levels within a 1492-LTF3 Terminal Block)	20	1492-CJL5D

