

Ethernet Switches

Introduction	Environmentals and Certifications	Stratix 8300 Modular Managed Switches	Stratix 8000 Modular Managed Switches	Stratix 6000 Fixed Managed Switches
Stratix 5700 Managed Switches	Stratix 2000 Unmanaged Switches	Embedded Switch Technology	Accessories	




Accessories

SFP (Small Form-factor Pluggable) Transceivers

Cat. No.	Description	Wavelength	Fiber Type	Core Size/Cladding Size (micron)	Modal Bandwidth (MHz/km) *	Cable Length	Compatible With
1783-SFP100FX	100Base-FX Multi-mode Fiber SFP	1310 nm	MMF	50/125 62.5/125	500	2 km (6562 ft)	Stratix 5700, 8000, 8300
1783-SFP100LX	100Base-LX Single-mode Fiber SFP	1310 nm	SMF	G.652	—	10 km (32.81 ft)	Stratix 5700, 8000, 8300
1783-SFP1GSX	1000Base-SX Multi-mode Fiber Transceiver	850 nm	MMF	62.5/125 62.5/125 50/125 50/125	160 200 400 500	220 m (722 ft) 275 m (902 ft) 500 m (1640 ft) 550 m (1804 ft)	Stratix 5700, 6000, 8000, 8300
1783-SFP1GLX	1000Base-LX/LH Single-mode Fiber SFP	1310 nm	SMF	G.652	—	10 km (32.81 ft)	Stratix 5700, 6000, 8000, 8300

* Modal bandwidth applies only to multi-mode fiber.

Ethernet Cable

Cat. No.	Description	
1585J-M8PBJM-2 *	RJ45 to RJ45 patchcord	
1585-C8PB-S100‡	Ethernet cable spool	
1585J-M8CC-H	Field attachable connector, IDC	

* Replace -2 (2 m) with 5 (5 m) or 10 (10 m) for additional standard cable lengths.

‡ Replace 100 (100 m) with 300 (300 m) or 600 (600 m) for additional standard cable lengths.