


DIN Fused Disconnect Switches



2

Ratings (AC23)							
Load Rating I_e [A]	With Fuse Links				Fuse	Dim. Ref.	Cat. No.
	3-Phase Maximum kW (50 Hz)						
	200/230V	380/400/415V	500V	660/690V			
75	22	37	45	55	DIN 00	C2	194R-ND072P3
138	37	75	90	110	DIN 0, 00❄	D2	194R-ND138P3
245	75	132	160	160	DIN 1	E2	194R-ND250P3
300	90	160	200	200	DIN 1, 2	F1	194R-ND300P3

* Series C only.

Operating Handles (Accepts 3 Padlocks)

	For Use With	Description	Color	Degree of Protection	Cat. No.
	C1, C2, D1, D2, E1, E2, F1	Standard orientation with defeater	Black/Grey	IP42 (Type 1)	194R-HM1
				IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4
			Red/Yellow	IP42 (Type 1)	194R-HM1E
				IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4E
		Standard orientation without defeater	Black/Grey	IP42 (Type 1)	194R-HM1-N2
				IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4-N2
			Red/Yellow	IP42 (Type 1)	194R-HM1E-N2
				IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4E-N2
 	90° rotated orientation with defeater	Black/Grey	IP42 (Type 1)	194R-HM1-N1	
			IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4-N1	
		Red/Yellow	IP42 (Type 1)	194R-HM1E-N1	
			IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4E-N1	
	90° rotated orientation without defeater	Black/Grey	IP42 (Type 1)	194R-HM1-N3	
			IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4-N3	
Red/Yellow		IP42 (Type 1)	194R-HM1E-N3		
		IP66 (Type 3R, 3, 12, 4, 4X)	194R-HM4E-N3		