


Bulletin 800F


22.5 mm Push Buttons

Product Selection

Single Turn Potentiometer Assembly*‡§



Series B



Series A

Resistive Element	Series B Cat. No.	Series A Cat. No.♣
None (Operator Only)*	800FP-POT	800FP-POTA
150 Ω	800FP-POT1	800FP-POT1A
500 Ω	800FP-POT2	800FP-POT2A
1000 Ω	800FP-POT3	800FP-POT3A
2500 Ω	800FP-POT4	800FP-POT4A
5000 Ω	800FP-POT5	800FP-POT5A
10000 Ω	800FP-POT6	800FP-POT6A

* The Cat. No. 800FP-POT is a complete operator assembly supplied without the resistive element, used with potentiometers having a shaft diameter of 6.0 mm (0.23 in.) and a shaft length of 50.0 mm (1.97 in.), or a shaft diameter of 6.4 mm (0.25 in.) and a shaft length of 22.5 mm (0.88 in.). This operator is used with Type "J" potentiometers only.

⌘ Rated 300V AC/DC, 2 W max.


‡ A latch is not needed.


§ Additional hole spacing required for potentiometers. See page 10-125 for panel hole spacing requirements.

♣ Not stocked. Longer lead-time.


Key Operated Selector Switch - SensEject™

Patented Spring-Loaded Key Ejection System







**2-Position
Switching Angle**



**3-Position
Switching Angle**

Operator Construction	Operator Type	Key Eject Position	Key Option§	Spare Keys	Contact Blocks	Cat. No.➤
Round Metal Operator — SensEject is IP6X (dust-tight) Type 1	2-Position Maintained	 Left with Key Eject	Zadi Key 06Z	800F-AKE006	None	800FM-KEM2106Z
					1 N.O.; 1 N.C.	800FM-KEM2106ZMX11
	3-Position Spring Return from Both	 Center with Key Eject	Zadi Key 01Z	800F-AKE001	None	800FM-KEB3401Z
					2 N.O.; 3 N.C.	800FM-KEB3401ZMX23

§ Not intended for high security applications. Interoperability is possible with certain key/cylinder lock combinations. Consult your local Rockwell Automation sales office or Allen-Bradley distributor for interoperability information.

➤ Includes latch and spacer block.