42EF RightSight, 42CA, 42CM, 42CS 18 mm Sensors

Approximate Dimensions [mm (in.)]	Product Description	Material	Cat. No.	
10° Adjustment in Each Direction (1.125) (2.25) (0.31) (0.31)	Swivel/ Tilt bracket ±10° vertical and 360° rotation	Valox®		60-2649
38.1 (1.50) 45.5 (1.79) (1.25)	Right angle mounting bracket 30° horizontal adjustment	Zinc- plated steel		60-2664
35.8 (1.41) 35.8 (1.41) 42.4 (1.67)	Right angle mounting bracket 30° horizontal adjustment	Zinc- plated steel		60-2657
70.0 (2.75) 42.0 (1.65)	Straight mounting bracket 30° vertical and 20° horizontal rotation	Stainless steel 304		60-2656
22.2 (1.88) H 152.4 (6.0)	Vertical adjustment bracket slotted for swivel/ tilt brackets	Stainless steel with powder coat	§	60-2721 (2 x 4 in.) 60-2722 (2 x 6 in.) 60-2723
				(2 x 8 in.) 60-2724 (2 x 10 in.)
	18 mm flush mount adaptor allows sensor to be flush mounted	Adaptor: plastic (Valox®); ring: steel		60-2590

