




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L4				1492-L4T				1492-L4Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 2 connection points on each side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	33 A	35 A	32 A	28 A	33 A	35 A	32 A	28 A	33 A	35 A	32 A	28 A
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)	#26...10 AWG		4 mm ²	4 mm ² (20...10 AWG)
Wire Strip Length	0.47 in. (12 mm)				0.47 in. (12 mm)				0.47 in. (12 mm)			
Density	49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-78											
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color	Grey	1492-L4		50	1492-L4T			50	1492-L4Q			50
	Red	1492-L4-RE		50	1492-L4T-RE			50	1492-L4Q-RE			50
	Blue	1492-L4-B		50	1492-L4T-B			50	1492-L4Q-B			50
	Black	1492-L4-BL		50	1492-L4T-BL			50	1492-L4Q-BL			50
	Green	1492-L4-G		50	1492-L4T-G			50	1492-L4Q-G			50
	Yellow	1492-L4-Y		50	1492-L4T-Y			50	1492-L4Q-Y			50
	Orange	1492-L4-OR		50	1492-L4T-OR			50	1492-L4Q-OR			50
	Brown	1492-L4-BR		50	1492-L4T-BR			50	1492-L4Q-BR			50
	White	1492-L4-W		50	1492-L4T-W			50	1492-L4Q-W			50
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails												
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2
End Barriers	Grey	1492-EBL4		50	1492-EBL4T			50	1492-EBL4Q			50
	Blue	1492-EBL4-B		50	1492-EBL4T-B			50	1492-EBL4Q-B			50
	Yellow	1492-EBL4-Y		50	1492-EBL4T-Y			50	1492-EBL4Q-Y			50
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50
Jumpers:												
Plug-in Center Jumper — 10-Pole	1492-CJK6-10			20	1492-CJK6-10			20	1492-CJK6-10			20
Plug-in Center Jumper — 9-Pole	1492-CJK6-9			20	1492-CJK6-9			20	1492-CJK6-9			20
Plug-in Center Jumper — 8-Pole	1492-CJK6-8			20	1492-CJK6-8			20	1492-CJK6-8			20
Plug-in Center Jumper — 7-Pole	1492-CJK6-7			20	1492-CJK6-7			20	1492-CJK6-7			20
Plug-in Center Jumper — 6-Pole	1492-CJK6-6			20	1492-CJK6-6			20	1492-CJK6-6			20
Plug-in Center Jumper — 5-Pole	1492-CJK6-5			20	1492-CJK6-5			20	1492-CJK6-5			20
Plug-in Center Jumper — 4-Pole	1492-CJK6-4			60	1492-CJK6-4			60	1492-CJK6-4			60
Plug-in Center Jumper — 3-Pole	1492-CJK6-3			60	1492-CJK6-3			60	1492-CJK6-3			60
Plug-in Center Jumper — 2-Pole	1492-CJK6-2			60	1492-CJK6-2			60	1492-CJK6-2			60
Other Accessories												
Reducing Sleeves #26...#24 AWG (0.13...0.2 mm ²) White	1492-PSL4-2			100	1492-PSL4-2			100	1492-PSL4-2			100
Reducing Sleeves #20...#22 AWG (0.25...0.5 mm ²) Grey	1492-PSL4-5			100	1492-PSL4-5			100	1492-PSL4-5			100
Reducing Sleeves #18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL4-10			100	1492-PSL4-10			100	1492-PSL4-10			100
Test Plug	1492-TP23			20	1492-TP23			20	1492-TP23			20
Test Plug (Stackable)	1492-TPL6			25	1492-TPL6			25	1492-TPL6			25
Electrical Warning Plate	1492-EWPL6			20	1492-EWPL6			20	1492-EWPL6			20
Marking Systems												
Snap-In Marker Cards	1492-M6X10 (120/card)			5	1492-M6X10 (120/card)			5	1492-M6X10 (120/card)			5
Snap-In Marker Cards	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5
Hinged Marker Cards	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5

Spring-Clamp Connection Terminal Blocks



Multi-Circuit Feed-Through Blocks

1492-LD4

1492-LTF3

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Two-circuit feed-through terminal block

Three-circuit feed-through terminal block with multiple cross connection points

	UL	CSA	IEC	UL	CSA	IEC
Certifications						
Voltage Rating	600V AC/DC		800V AC/DC	300V AC/DC		500V AC/DC
Maximum Current	25 A	30 A	32 A	15 A		20 A
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	#26...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		

Terminal Blocks

		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color	Grey	1492-LD4	20	1492-LTF3	25
	Red	1492-LD4-RE	20	—	—
	Blue	1492-LD4-B	20	—	—
	Black	1492-LD4-BL	20	—	—
	Green	1492-LD4-G	20	—	—
	Yellow	1492-LD4-Y	20	—	—
	Orange	1492-LD4-OR	20	—	—
	Brown	1492-LD4-BR	20	—	—
	White	1492-LD4-W	20	—	—




Accessories

		Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails					
1 m Symmetrical DIN (Steel)		199-DR1	10	199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2	1492-DR7	2
End Barriers	Grey	1492-EBLD4	20	1492-EBLTF3	20
	Blue	1492-EBLD4-B	20	—	—
	Yellow	1492-EBLD4-Y	20	—	—
End Anchors and Retainers					
Screwless End Retainer		1492-ERL35	20	1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100	1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50	1492-EAHJ35	50
Jumpers					
Plug-in Center Jumper — 50-Pole		—	—	1492-CJK5-50	10
Plug-in Center Jumper — 10-Pole		1492-CJK6-10	20	1492-CJK5-10	20
Plug-in Center Jumper — 9-Pole		1492-CJK6-9	20	1492-CJK5-9	20
Plug-in Center Jumper — 8-Pole		1492-CJK6-8	20	1492-CJK5-8	20
Plug-in Center Jumper — 7-Pole		1492-CJK6-7	20	1492-CJK5-7	20
Plug-in Center Jumper — 6-Pole		1492-CJK6-6	20	1492-CJK5-6	20
Plug-in Center Jumper — 5-Pole		1492-CJK6-5	20	1492-CJK5-5	20
Plug-in Center Jumper — 4-Pole		1492-CJK6-4	60	1492-CJK5-4	60
Plug-in Center Jumper — 3-Pole		1492-CJK6-3	60	1492-CJK5-3	60
Plug-in Center Jumper — 2-Pole		1492-CJK6-2	60	1492-CJK5-2	60
Vertical Cross Connector*		—	—	1492-CJL5D	20
Other Accessories					
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²)		—	—	1492-PSLTF3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²)		—	—	1492-PSLTF3-5	100
Test Plug		1492-TP23	20	—	—
Electrical Warning Plate		1492-EWPL6	20	—	—
Marking Systems					
Snap-In Marker Cards		1492-M6X10 (120/card)	5	1492-SM5X10 (144/card)	5
Snap-In Marker Cards		1492-M6X5 (200/card)	5	1492-M5X5 (200/card)	5

* Used to electrically connect 2 levels of 1492-LTF3

Spring-Clamp Connection Terminal Blocks




Specialty Feed-Through Blocks

	1492-LD2C			1492-LD3C				1492-LD4C		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
Specifications	Two-level feed-through terminal block with commoning bar			Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar		
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	22 A	25 A	30 A	32 A
Wire Range (Rated Cross Section)	#28...16 AWG		1.5 mm ²	#30...12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)	#26...10 AWG		4 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color: Grey	1492-LD2C	50		1492-LD3C	25			1492-LD4C	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2			1492-DR7	2	
End Barriers Grey	1492-EBLD2	50		1492-EBLD3	20			1492-EBLD4	20	
End Anchors and Retainers Screwless End Retainer	1492-ERL35	20		1492-ERL35	20			1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50			1492-EAHJ35	50	
Jumpers:										
Plug-in Center Jumper — 50-Pole	—	—		1492-CJK5-50	10			—	—	
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20		1492-CJK5-10	20			1492-CJK6-10	20	
Plug-in Center Jumper — 9-Pole	—	—		1492-CJK5-9	20			1492-CJK6-9	20	
Plug-in Center Jumper — 8-Pole	—	—		1492-CJK5-8	20			1492-CJK6-8	20	
Plug-in Center Jumper — 7-Pole	—	—		1492-CJK5-7	20			1492-CJK6-7	20	
Plug-in Center Jumper — 6-Pole	—	—		1492-CJK5-6	20			1492-CJK6-6	20	
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60		1492-CJK5-5	20			1492-CJK6-5	20	
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60		1492-CJK5-4	60			1492-CJK6-4	60	
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60		1492-CJK5-3	60			1492-CJK6-3	60	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60		1492-CJK5-2	60			1492-CJK6-2	60	
Other Accessories:										
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100		1492-PSLS2-2	100			—	—	
Reducing Sleeves 22...20 AWG (0.13...0.2 mm ²) Grey	1492-PSL2-5	100		1492-PSLS2-5	100			—	—	
Test Plug	1492-TPL4	25		—	—			1492-TP23	20	
Electrical Warning Plate	1492-EWPL4	20		—	—			1492-EWPL6	20	
Marking Systems:										
Snap-In Marker Cards	1492-M3X12 (120/card)*	5		1492-M5X10 (144/card)	5			1492-M6X10 (120/card)	5	
Snap-In Marker Cards	1492-M3X5 (100/card)	5		1492-M5X5 (200/card)	5			1492-M6X5 (200/card)	5	

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Internal Component Blocks

	1492-LD4DF			1492-LD4DR			1492-LD4SS*		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-level terminal block with an IN4007 diode in forward bias between the 2 levels.			Two-level terminal block with an IN4007 diode in reverse bias between the 2 levels.			Two level terminal block with an MOV between the 2 levels.		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC			600V AC/DC			600V AC/DC		
Maximum Current	25 A	30 A	32 A	25 A	30 A	32 A	120V	—	140V AC/DC
Component Current/Wattage Rating*	1 A			1 A			25 A	30 A	32 A
Wire Range (Rated Cross Section)	#26...10 AWG			#26...10 AWG			#26...10 AWG	26...10 AWG	4mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color Black	1492-LD4DF	1		1492-LD4DR	1		1492-LD4SS	1	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier Grey	1492-EBLD4	20		1492-EBLD4	20		1492-EBLD4	20	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-in Center Jumper — 10-pole	1492-CJK6-10	20		1492-CJK6-10	20		1492-CJK6-10	20	
Plug-in Center Jumper — 9-pole	1492-CJK6-9	20		1492-CJK6-9	20		1492-CJK6-9	20	
Plug-in Center Jumper — 8-pole	1492-CJK6-8	20		1492-CJK6-8	20		1492-CJK6-8	20	
Plug-in Center Jumper — 7-pole	1492-CJK6-7	20		1492-CJK6-7	20		1492-CJK6-7	20	
Plug-in Center Jumper — 6-pole	1492-CJK6-6	20		1492-CJK6-6	20		1492-CJK6-6	20	
Plug-in Center Jumper — 5-pole	1492-CJK6-5	20		1492-CJK6-5	20		1492-CJK6-5	20	
Plug-in Center Jumper — 4-pole	1492-CJK6-4	60		1492-CJK6-4	60		1492-CJK6-4	60	
Plug-in Center Jumper — 3-pole	1492-CJK6-3	60		1492-CJK6-3	60		1492-CJK6-3	60	
Plug-in Center Jumper — 2-pole	1492-CJK6-2	60		1492-CJK6-2	60		1492-CJK6-2	60	
Other Accessories									
Test Plug	1492-TP23	20		1492-TP23	20		1492-TP23	20	
Marking Systems									
Snap-In Marker Cards	1492-M6X10 (120/card)	5		1492-M6X10 (120/card)	5		1492-M6X10 (120/card)	5	
Snap-In Marker Cards	1492-M6X5 (200/card)	5		1492-M6X5 (200/card)	5		1492-M6X5 (200/card)	5	

* For component specifications, see page 12-97

Screwless Center Jumpers



For Use With	Color	Pkg Qty.	Cat. No.
1492-L2..., L2T, L2Q, LD2, LD2C	Yellow	60	1492-CJL4-2
		60	1492-CJL4-3
		60	1492-CJL4-4
		60	1492-CJL4-5
		20	1492-CJL4-10
1492-LM3, LC3, LDC3, LDAG3, LDG3P, JKD3..., J3P..., J3, J3TW (see Note)	Yellow	60	1492-CJLJ5-2
	Red	60	1492-CJLJ5-2-R
	Blue	60	1492-CJLJ5-2-B
	Black	60	1492-CJLJ5-2-BL
	Yellow	60	1492-CJLJ5-3
	Red	60	1492-CJLJ5-3-R
	Blue	60	1492-CJLJ5-3-B
	Black	60	1492-CJLJ5-3-BL
	Yellow	60	1492-CJLJ5-4
		20	1492-CJLJ5-5
		20	1492-CJLJ5-6
		20	1492-CJLJ5-7
		20	1492-CJLJ5-8
		20	1492-CJLJ5-9
		20	1492-CJLJ5-10
	Red	20	1492-CJLJ5-10-R
	Blue	20	1492-CJLJ5-10-B
	Black	20	1492-CJLJ5-10-BL
	White	20	1492-CJLJ5-10-W
	Yellow	10	1492-CJLJ5-50
	Red	10	1492-CJLJ5-50-R
	Blue	10	1492-CJLJ5-50-B
	Black	10	1492-CJLJ5-50-BL
	White	10	1492-CJLJ5-50-W

For Use With	Pkg Qty.	Cat. No.
1492-RFB4	10	1492-CJR8-2
	10	1492-CJR8-3
	10	1492-CJR8-4
	10	1492-CJR8-5
	10	1492-CJR8-6
	10	1492-CJR8-7
	10	1492-CJR8-8
	10	1492-CJR8-9
	10	1492-CJR8-10
	10	1492-CJRA10-2
1492-RAFB4	10	1492-CJRA10-3
	10	1492-CJRA10-4
	10	1492-CJRA10-5

For Use With	Color	Pkg Qty.	Cat. No.
1492-J4, J4M (see Note)	Yellow	60	1492-CJLJ6-2
	Red	60	1492-CJLJ6-2-R
	Blue	60	1492-CJLJ6-2-B
	Black	60	1492-CJLJ6-2-BL
	Yellow	60	1492-CJLJ6-3
	Red	60	1492-CJLJ6-3-R
	Blue	60	1492-CJLJ6-3-B
	Black	60	1492-CJLJ6-3-BL
	Yellow	60	1492-CJLJ6-4
	Yellow	20	1492-CJLJ6-10
	Red	20	1492-CJLJ6-10-R
	Blue	20	1492-CJLJ6-10-B
	Black	20	1492-CJLJ6-10-BL
	Yellow	10	1492-CJLJ6-41
	Red	10	1492-CJLJ6-41-R
	Blue	10	1492-CJLJ6-41-B
	Black	10	1492-CJLJ6-41-BL
1492-L6, L6T, L16D	Yellow	60	1492-CJL8-2
		60	1492-CJL8-3
		60	1492-CJL8-4
		10	1492-CJL8-32
1492-L10	Yellow	25	1492-CJL10-2
1492-L16	Yellow	25	1492-CJL12-2
1492-L35	Yellow	10	1492-CJL16-2
1492-L3, L3T, L3Q, L3P, LD3, LD3C, LKD3, LTF3, LS2..., L16D	Yellow	60	1492-CJK5-2
		60	1492-CJK5-3
		60	1492-CJK5-4
		20	1492-CJK5-5
		20	1492-CJK5-6
		20	1492-CJK5-7
		20	1492-CJK5-8
		20	1492-CJK5-9
		20	1492-CJK5-10
		10	1492-CJK5-50
		60	1492-CJK6-2
1492-L4, L4T, L4Q, LD4DF, LD4DR, LD4SS, LD4, LD4C, L16D	Yellow	60	1492-CJK6-3
		60	1492-CJK6-4
		20	1492-CJK6-5
		20	1492-CJK6-6
		20	1492-CJK6-7
		20	1492-CJK6-8
		20	1492-CJK6-9
		20	1492-CJK6-10
		20	1492-CJK6-20