




1492-JKD4TW

1492-JKD4Q

1492-H7

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Feed-through terminal block with knife disconnect; 3 connection points, 2 on one side			Feed-through terminal block with knife disconnect; 2 connection points on each side			Handle-style isolating terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC	600V AC/DC		500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	25 A		30 A	25 A		30 A	15 A	15 A	15 A
Wire Range (Rated Cross Section)	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4.0 mm ²
Fuse Size (Dummy Fuse Supplied)	—			—			1/4 x 1-1/4 in.		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.38 in. (9.7 mm)		
Recommended Tightening Torque	6.2 lb•in (0.7 N•m)			6.2 lb•in (0.7 N•m)			7.1 lb•in (0.8 N•m)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			33 pcs/ft (109 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-40...+221 °F (-40...+105 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Color:	Grey	1492-JKD4TW	50		1492-JKD4Q	50		—	—
With Test Points	Grey	1492-JKD4TWTP	50		1492-JKD4QTP	50		—	—
	Black	—	—		—	—		1492-H7	25
Accessories		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Mounting Rails:		—	—		—	—		1492-N1	20
3 ft Scored A-B Rail		—	—		—	—		1492-N22	20
3 ft Rigid A-B Rail		—	—		—	—		1492-N44	2
3 ft Rigid Rise A-B Rail		—	—		—	—		1492-N25	2
Standoff Brackets (use every 12 in.) 		—	—		—	—		1492-N25	2
1 m Symmetrical DIN (Steel)		199-DR1	10		199-DR1	10		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10		1492-DR5	10		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2		1492-DR6	2		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2		1492-DR7	2		1492-DR7	2
End Barrier	Grey	1492-EBJ4TW	50		1492-EBJ4Q	50		1492-N37	50
	Yellow	1492-EBJ4TW-Y	50		1492-EBJ4Q-Y	50		—	—
End Anchors and Retainers:		—	—		—	—		1492-N23	10
A-B Rail — Heavy Duty		—	—		—	—		1492-N47	50
A-B Rail — Normal Duty		—	—		—	—		1492-ERL35	20
Screwless End Retainer		1492-ERL35	20		1492-ERL35	20		1492-ERL35	20
DIN Rail - Normal Duty		1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100
DIN Rail - Heavy Duty		1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50
Jumpers:		1492-CJLJ6-41	10		1492-CJLJ6-41	10		—	—
Plug-in Center Jumper — 41-pole		1492-CJLJ6-10	20		1492-CJLJ6-10	20		—	—
Plug-in Center Jumper — 10-pole		1492-CJLJ6-4	60		1492-CJLJ6-4	60		—	—
Plug-in Center Jumper — 4-pole		1492-CJLJ6-3	60		1492-CJLJ6-3	60		—	—
Plug-in Center Jumper — 3-pole		1492-CJLJ6-2	60		1492-CJLJ6-2	60		—	—
Plug-in Center Jumper — 2-pole		—	—		—	—		1492-N49	10
Uninsulated Side Jumper — 10-Pole		—	—		—	—		1492-SJS	10
Side Jumper — Insulating Sleeve		—	—		—	—		—	—
Other Accessories:		—	—		—	—		—	—
Partition Plate		—	—		—	—		—	—
Marking Systems:		1492-MR6X12 (120/card)	5		1492-MR6X12 (120/card)	5		1492-MS8X12 (56/card)	5
Snap-in marker cards		1492-M6X12 (120/card)	5		1492-M6X12 (120/card)	5		1492-MS8X9 (56/card)	5
Snap-in marker cards		—	—		—	—		1492-ALHFB (50/sheet)	1
Adhesive Labels		—	—		—	—		—	—

* For use with 1492-N22 DIN rail only.