






	Bulletin 700S-CF • IEC Industrial Safety Relay • Positively Guided/Mechanically Linked Contacts as Per IEC 947-5-1 Annex L • Third Party Certification By SUVA • Red Cover and Mechanically Linked Contact Symbol on Front Face	Table Of Contents Product Selection 197 Specifications 199 Approximate Dimensions 200
---	---	--

Type CF Safety Control Relays — 8-Pole AC Voltage



AC-1			AC-11 and AC-15							Connection Diagrams		Contacts		Catalog Number ❶
<i>I</i> _e [A]			<i>I</i> _e [A]							Main Contacts	Auxiliary Contacts			
	40°C	60°C	24/48V	120V	240V	400V	500V	600V	690V			N.O.	N.C.	
Main Contacts	25	20	16	14	10	5	2.5	1.8	1			4	4	700S-CF440⊗C
												5	3	700S-CF530⊗C
Adder Deck Contacts	10	6	6	6	3	2	2	1.2	0.7			6	2	700S-CF620⊗C

❶ All Cat. Nos. are factory-stocked.

❷ AC Voltage Suffix Code

Voltage	12	24	32	36	42	48	100	100-110	110	120	127	200	200-220	208	208-240	220-230
50 Hz	R	K	V	W	X	Y	KP	—	D	P	S	KG	—	—	—	F
60 Hz	Q	J	—	V	—	X	—	KP	—	D	—	—	KG	H	L	—
50/60 Hz	—	KJ	—	—	—	KY	KP	—	KD	—	—	KG	—	—	—	—

Voltage	230	230-240	240	277	347	380	380-400	400	400-415	440	480	500	550	600
50 Hz	—	VA	T	—	—	—	N	—	G	B	—	M	C	—
60 Hz	—	—	A	T	I	E	—	—	—	N	B	—	—	C
50/60 Hz	KF	—	KA	—	—	—	—	KN	—	KB	—	—	—	—

❶ All Cat. Nos. are factory-stocked.

❷ See page 198 for coil voltage selection information.