

Pinout and Color Code

Color Code	Face View Pinout							
	3-Pin		4-Pin		5-Pin		6-Pin	
A	1 Green (GND) 2 Red/Black Tr. 3 Red/White Tr.		1 Red/Black Tr. 3 Red 2 Red/White Tr. 4 Green (GND)		1 Red/White Tr. 2 Red 3 Green	4 Red/Yellow Tr. 5 Red/Black Tr.	1 Red/White Tr. 2 Red 3 Green	4 Red/Yellow Tr. 5 Red/Black Tr. 6 Red/Blue Tr.

Product Selection

Cordsets

Pin Count	Assembly Rating	Color Code	Cat. No.			
			Straight Female	Right Angle Female	Straight Male	Right Angle Male
3-Pin	Braided 22 AWG, 250V, 4 A	A	889R-F3ECA*	889R-R3ECA*	889R-M3ECA*	889R-E3ECA*
	18 AWG, 250V, 4 A		889R-F3AEA*	889R-R3AEA*	889R-M3AEA*	889R-E3AEA*
4-Pin	Braided 22 AWG, 250V, 4 A		889R-F4ECA*	889R-R4ECA*	889R-M4ECA*	889R-E4ECA*
	18 AWG, 250V, 4 A		889R-F4AEA*	889R-R4AEA*	889R-M4AEA*	889R-E4AEA*
5-Pin	Braided 22 AWG, 250V, 4 A		889R-F5ECA*	889R-R5ECA*	889R-M5ECA*	889R-E5ECA*
	18 AWG, 250V, 4 A		889R-F5AEA*	889R-R5AEA*	889R-M5AEA*	889R-E5AEA*
6-Pin	Braided 22 AWG, 250V, 4 A		889R-F6ECA*	889R-R6ECA*	889R-M6ECA*	889R-E6ECA*

Patchcords

Pin Count	Assembly Rating	Color Code	Cat. No.			
			Straight Female Straight Male	Straight Female Right Angle Male	Right Angle Female Straight Male	Right Angle Female Right Angle Male
3-Pin	Braided 22 AWG, 250V, 4 A	A	889R-F3ECRM‡	889R-F3ECRE‡	889R-R3ECRM‡	889R-R3ECRE‡
	18 AWG, 250V, 4 A		889R-F3AERM‡	889R-F3AERE‡	889R-R3AERM‡	889R-R3AERE‡
4-Pin	Braided 22 AWG, 250V, 4 A		889R-F4ECRM‡	889R-F4ECRE‡	889R-R4ECRM‡	889R-R4ECRE‡
	18 AWG, 250V, 4 A		889R-F4AERM‡	889R-F4AERE‡	889R-R4AERM‡	889R-R4AERE‡
5-Pin	Braided 22 AWG, 250V, 4 A		889R-F5ECRM‡	889R-F5ECRE‡	889R-R5ECRM‡	889R-R5ECRE‡
	18 AWG, 300V, 4 A		889R-F5AERM‡	889R-F5AERE‡	889R-R5AERM‡	889R-R5AERE‡
6-Pin	Braided 22 AWG, 250V, 4 A		889R-F6ECRM‡	889R-F6ECRE‡	889R-R6ECRM‡	889R-R6ECRE‡

* Replace symbol with 2 (2 m), 5 (5 m) or 10 (10 m) for standard cable lengths.

‡ Replace symbol with 0M3 (0.3 m), 1 (1 m), 2 (2 m), 3 (3 m), 5 (5 m) or 10 (10 m) for standard lengths.