

Accessories — Field Installed

	Description		Cat. No.	
			Cat. No.	
 Cat. No. 500LG-1PCK	Pole conversion kit	1-Pole N.O.	500LG-1PCK	
		2-Pole N.O.	500LG-2PCK	
 Cat. No. 500LG-141C	One Form C (SPST) Auxiliary contact rated 10 A at 277V AC to indicate status of main contacts.		500LG-141C	
 Cat. No. 500LG-142C	Two Form C (SPDT) Auxiliary contact rated 10 A at 277V AC to indicate status of main contacts.		500LG-142C	
 Cat. No. 500LC-CCKA1	Coil replacement kit	115...120V AC (60 Hz) 110V AC (50 Hz)	500LG-CCKA1	
		230...240V AC (60 Hz) 220V AC (50 Hz)	500LG-CCKA2	
		277V AC (60 Hz) 240V AC (50 Hz)	500LG-CCKA3	
		347V AC (60 Hz)	500LG-CCKA4	
		460...480V AC (60 Hz) 440V AC (50 Hz)	500LG-CCKA5	
		575...600V AC (60 Hz)	500LG-CCKA6	
 Cat. No. 500LC-E4SM	Enclosure	Type 12 surface mount	500LC-E12SM	
		Type 4/4X stainless steel surface mount	500LC-E4SM	
		Type 3R surface mount	500LC-E3RSM	
 Cat. No. 500LG-47CM120	Control module, 2-wire	12...24V DC	500LG-47CM12	
		24V AC	500LG-47CM24	
		120V AC	500LG-47CM120	
		277V AC	500LG-47CM277	
	Control module, 3-wire	12...24V DC	500LG-48CM12	
		24V AC	500LG-48CM24	
		120V AC	500LG-48CM120	
		277V AC	500LG-48CM277	
 Cat. No. 598-DF14126	Description	Enclosure Type	Enclosures Subpanel†	
			Cat. No.	
	Enclosure	Type 1 flush cover	598-QA1210F	—
		Type 1 lift off	598-BA12105	—
		Type 1 flush mount	598-QA12106	—
		Type 1 hinged	598-DA12106	598-PA1210
			* 598-DA14126	598-PA1412
			* 598-DA16166	598-PA1616
		Type 12 hinged	598-DF12106	598-PC1210
			* 598-DF14126	598-PC1412
			* 598-DF16146	598-PC1614
		Type 4/12 hinged	598-DJ12106	598-PC1210
			* 598-DJ14126	598-PC1412
			* 598-DJ16146	598-PC1614
		Type 4/4X hinged	598-DC12106	598-PC1210
			* 598-DC14126	598-PC1412
			* 598-DC16146	598-PC1614

* Three 22.5 mm pre-punched pilot holes are available as standard enclosure. Cat. No. 800F-N2 hole plug, sold separately.
† Subpanel sold separately.