




Shunt Trip Units

Description	Connection Diagram ⁽¹⁾	Trip Rating	For Use With	Cat. No.
 Shunt Trip - Left-side mounted - Adds 18 mm to the width of the device - Provides remote tripping of the MPCB/MCP - Maximum on time for DC operated devices: 5 sec.		24V, 50 Hz/24...28V, 60 Hz	140MT-C, D 140UT-D (UL 489 applications up to 30 A)	140MT-C-SNK
		110V, 50 Hz/120V, 60 Hz		140MT-C-SND
		220...230V, 50 Hz		140MT-C-SNF
		240...260V, 60 Hz		140MT-C-SNA
		240V, 50 Hz; 277V, 60 Hz		140MT-C-SNT
		380...400V, 50 Hz		140MT-C-SNN
		480V, 60 Hz/415V, 50 Hz		140MT-C-SNB
		24V DC		140MT-C-SNZJ

(1) Connection Diagram Reference:



Additional Accessories

	Description	For Use With	Cat. No.
	Anti-Tamper Shield - Provides protection against inadvertent adjustment of the current setting - Must be ordered in multiples of 10 (10 pieces/package)	140MT-C, D	140MT-C-CA
	Lockable Twist Knob - For one padlock 5 mm (3/16 in.) diameter shackle - Can be locked in OFF position	Blue	140MT-C-KB
		Black	140MT-C-KN
		Red/Yellow	140MT-C-KRY
	Locking Tag - Padlock attachment to the lockable handles - Up to three padlocks 4...8 mm (5/16 in.) diameter shackle	140MT-C-KN1 140MT-C-KRY1	140MT-C-M3
	Door Coupling Handle - For 3 padlocks 4...8 mm (5/16 in.) in diameter - IP66 Protection/Type 1, 4, 4X, 12 Interlock override capability - Can be modified for locking in ON position - Ships with coupling — order extension shaft and legend plate separately	Black	140MT-C, D 140UT-D
		Red/Yellow	140MT-C, D 140UT-D