


	<p><b>Bulletin 194R/140U Next Generation Disconnect Handles</b></p> <ul style="list-style-type: none"> <li>• Available in matte black for ON-OFF switching and red/yellow for Emergency OFF requirements</li> <li>• One-hand operation to open the door</li> <li>• Operating handle environmental ratings:               <ul style="list-style-type: none"> <li>- Type 3R, 3, 12, 4, 4X</li> </ul> </li> <li>• Handle with or without test mode; Trip indication on Bul 140U handle</li> <li>• Padlockable handle for up to three padlocks</li> <li>• Defeater mechanism</li> <li>• NFPA 79 internal operating handle with shaft (option)</li> <li>• Option for either vertical or 45° mount holes</li> </ul> <p>Bulletin 194R/140U Next Generation Disconnect Handles have been redesigned with a unique form and contemporary styling to improve both comfort and performance in the field. These handles are designed to be used with Bulletin 194R fused and non-fused disconnect switches up to 60 A, Bulletin 140U/UE Molded Case Circuit Breakers, Bulletin 140M Motor Protection Circuit Breakers, and Bulletin 140M Motor Circuit Protectors.</p>	<p><b>Table of Contents</b></p> <p>Product Selection ..... this page</p> <p>Specifications..... 4</p> <p>Approximate Dimensions..... 5</p> <p><b>Standards Compliance</b></p> <p>IEC/EN 60947-3</p> <p>UL 98</p> <p>UL 489</p> <p>UL 508</p> <p>CSA, C22.2 Nos. 4, 5, 14</p> <p>VDE 0660</p> <p><b>Certifications</b></p> <p>CE Marked</p> <p>cULus Recognized (File No. E3125 Vol 2)</p>
---	--	---

**Product Selection**  
**Operating Handles (Accepts 3 Padlocks)**

	Description	Shaft Type	For Use With	Color	Environmental Rating	Cat. No.
	Padlockable handle, standard	194R-S, 194R-N operating shafts	Bul. 194R disconnect switches up to 60 A	Black	Type 3R, 3, 12, 4, 4X	194R-PB
				Padlockable handle, test mode	Red/Yellow	Type 3R, 3, 12, 4, 4X
				Padlockable handle, standard, with trip indication	Black	Type 3R, 3, 12, 4, 4X
	Red/Yellow				Type 3R, 3, 12, 4, 4X	194R-PYT
			Bul. 140U/UE Molded Case Circuit Breakers, 140M Motor Protection Circuit Breakers & Motor Circuit Protectors; 100, 125, and 250A devices	Black	Type 3R, 3, 12, 4, 4X	140U-PB
				Red/Yellow	Type 3R, 3, 12, 4, 4X	140U-PY

**OSHA Lockout/Tag Out Compliance (LOTO)**

OSHA CFR36 Section 1910 mandates that disconnects be able to be locked out while in the OFF position during servicing. All Bulletin 194R/140U handles comply with this important safety requirement.



(Please see NFPA Article 430 for disconnect requirements of motor applications)