


22.5 mm Push Buttons

Quick Selection


Complete Devices, Continued*

Non-Illuminated Emergency Stop Operators, Ø 40 mm, Red (Screw Terminal Connections)

	Description	Type of Contact*		Construction	Pkg. Quantity	Cat. No.
		N.O.	N.C.			
 Cat. No. 800FP-MT44PX01S	Twist-to-Release	—	1	Plastic operator/plastic latch	1	800FP-MT44PX01S
		—	1	Metal operator/metal latch		800FM-MT44MX01S
		1	1	Plastic operator/plastic latch		800FP-MT44PX11S
		1	1	Metal operator/metal latch		800FM-MT44MX11S

* Self-monitoring contact block included when N.C. is specified.

Pilot Lights with Integrated LED Modules (Screw Terminal Connections)

	Voltage	Style	Construction	Pkg. Quantity	Cat. No.
 Cat. No. 800FP-P7PN3W	24V AC/DC	Green	Plastic operator/plastic latch	1	800FP-P3PN3G
		Red			800FP-P4PN3R
		Yellow			800FP-P5PN3Y
		Blue			800FP-P6PN3B
		White			800FP-P7PN3W
	120V AC	Green			800FP-P3PN5G
		Red			800FP-P4PN5R
		Yellow			800FP-P5PN5Y
		Blue			800FP-P6PN5B
		White			800FP-P7PN5W
	240V AC	Green			800FP-P3PN7G
		Red			800FP-P4PN7R
		Yellow			800FP-P5PN7Y
		Blue			800FP-P6PN7B
		White			800FP-P7PN7W
		White			800FP-P7PN7W

* For complete devices not listed and configuration assistance, see RAISE product selection software (<http://www.ab.com/raise>).