




Screw Connection Terminal Blocks

Specialty Feed-Through Blocks

1492-J2Q				1492-J3TW				1492-J4TW				
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications		Feed-through terminal block with 2 connection points on each side		Feed-through terminal block with 3 connection points, 2 on one side		Feed-through terminal block with 3 connection points, 2 on one side						
Certifications			CSA	IEC		CSA	IEC		CSA	IEC		
Voltage Rating		300V AC/DC		300V AC/DC		800V AC/DC		550V AC/DC		500V AC/DC		
Maximum Current		25 A	10 A	17.5 A	—		30 A		32 A			
Maximum Current		Single Side		10 A		15 A		17.5 A		15 A		
		Twin Side		20 A		24 A		21 A		—		
Wire Range (Rated Cross Section)		Single Side		#22...12 AWG	#26...12 AWG	1.5 mm ²		#22...14 AWG		2.5 mm ² (#20...14 AWG)		
		Twin Side		—		#22...14 AWG		26...14 AWG		1.5 mm ² (#20...16 AWG)		
Wire Strip Length		0.28 in. (7 mm)		Single Side: 0.39 in. (10 mm)		Twin Side: 0.26 in. (7 mm)		0.39 in. (10 mm)				
Recommended Tightening Torque		4.5 lb•in (0.5 N•m)		Single Side: 7.0 lb•in (0.8 N•m)		Twin Side: 4.5 lb•in (0.5 N•m)		6.2 lb•in (0.7 N•m)				
Density		59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)		59 pcs/ft (196 pcs/m)				
Housing Temperature Range		-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)		-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating		See page 12-42										
Terminal Blocks		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.	Pkg Qty.	
Color:		Grey		1492-J2Q		100		1492-J3TW		100		
		Red		1492-J2Q-RE		100		1492-J3TW-RE		100		
		Blue		1492-J2Q-B		100		1492-J3TW-B		100		
		Black		1492-J2Q-BL		100		1492-J3TW-BL		100		
		Green		1492-J2Q-G		100		1492-J3TW-G		100		
		Yellow		1492-J2Q-Y		100		1492-J3TW-Y		100		
		Orange		1492-J2Q-OR		100		1492-J3TW-OR		100		
		Brown		1492-J2Q-BR		100		1492-J3TW-BR		100		
		White		1492-J2Q-W		100		1492-J3TW-W		100		
Accessories		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.
Mounting Rails:		199-DR1		10		199-DR1		10		199-DR1		10
1 m Symmetrical DIN (Steel)		1492-DR5		10		1492-DR5		10		1492-DR5		10
1 m Symmetrical DIN (Aluminum)		1492-DR6		2		1492-DR6		2		1492-DR6		2
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR7		2		1492-DR7		2		1492-DR7		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-EBJ3		50		1492-EBJ3		50		1492-EBJ4TW		50
End Barriers		Grey		1492-EBJ3-B		50		1492-EBJ3-B		50		—
		Blue		1492-EBJ3-Y		50		1492-EBJ3-Y		1492-EBJ4TW-Y		50
		Yellow		1492-ERL35		20		1492-ERL35		1492-ERL35		20
End Anchors and Retainers:		1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100
Screwless End Retainer		1492-EAH35		10		1492-EAH35		10		1492-EAH35		10
DIN Rail — Normal Duty		1492-CJJ5-10		20		1492-CJJ5-10		20		—		—
Jumpers:		1492-CJJ5-4		50		1492-CJJ5-4		50		—		—
Screw Center Jumper — 10-pole		1492-CJJ5-3		50		1492-CJJ5-3		50		—		—
Screw Center Jumper — 4-pole		1492-CJJ5-2		50		1492-CJJ5-2		50		—		—
Screw Center Jumper — 3-pole		1492-CJLJ5-50		10		1492-CJLJ5-50		10		1492-CJLJ6-41		10
Screw Center Jumper — 2-pole		1492-CJLJ5-5, -6, -7, -8, -9, -10		20		1492-CJLJ5-5, -6, -7, -8, -9, -10		20		1492-CJLJ6-10		20
Plug-in Center Jumper — 50-Pole (1492-J3TW)/ 41-Pole (1492-J4TW)		1492-CJLJ5-2, -3, -4		60		1492-CJLJ5-2, -3, -4		60		1492-CJLJ6-2, -3, -4		60
Plug-in Center Jumper — 5-, 6-, 7-, 8-, 9-, 10-Pole		1492-SJ5B-24		50		1492-SJ5B-24		50		—		—
Insulated Side Jumper — 24-Pole		1492-SJ5B-10		50		1492-SJ5B-10		50		—		—
Insulated Side Jumper — 10-Pole		1492-T1		1		1492-T1		1		—		—
Screw Type Jumper Notching Tool		1492-EBJ16		20		1492-EBJ16		20		—		—
Other Accessories:		1492-TPS23L		50		1492-TPS23L		50		1492-TPS23L		50
Partition Plate		1492-TP23		20		1492-TP23		20		1492-TP23		20
Test Plug Socket		1492-TPJ5		25		1492-TPJ5		25		—		—
Test Plug		1492-M5X12 (144/card)		5		1492-M5X12 (144/card)		5		1492-MR6X12 (120/card)		5
Test Plug (Stackable)		1492-M6X12 (200/card)		5		1492-M6X12 (200/card)		5		1492-M6X12 (120/card)		5
Marking Systems:		1492-M5X12 (144/card)		5		1492-M5X12 (144/card)		5		1492-MR6X12 (120/card)		5
Snap-in marker card		1492-M6X12 (200/card)		5		1492-M6X12 (200/card)		5		1492-M6X12 (120/card)		5

* Use of center jumpers may affect spacings, requiring derating of terminal blocks.