
Bulletin	1492-J, -W	1492-L
Type	<b>Screw Type Terminal Blocks</b>	<b>Spring-Clamp Terminal Blocks</b>
Technology	Screw terminations are a time-proven method of wire connection. Their greatest advantage is the ability to land multiple wires to a single terminal, potentially saving panel space. Screw type blocks can often accept up to five solid or stranded wires per terminal. They also typically provide the best visual indication of the wire connection.	Compared to screw type terminations, spring clamp terminations can be a significantly faster method of connection and can often reduce wire connection time by 30...50%. Because the wire is under constant tension from the spring clamp, spring type terminations also produce very favorable results in high vibration applications.
Certifications	UR, CSA	UR, CSA
Standards Compliance	IEC, CE	IEC, CE
Product Types	<ul style="list-style-type: none"> <li>• Mini blocks</li> <li>• Feed-through blocks</li> <li>• Multi-conductor blocks</li> <li>• Plug-in style blocks</li> <li>• Grounding blocks</li> <li>• Fuse blocks</li> <li>• Two level terminal blocks</li> <li>• Three-Level Sensor blocks</li> <li>• Electrical Component blocks</li> <li>• Isolation blocks</li> </ul>	<ul style="list-style-type: none"> <li>• Mini blocks</li> <li>• Fuse blocks</li> <li>• Feed-through blocks</li> <li>• Grounding blocks</li> <li>• Multi-circuit blocks</li> <li>• Plug-in style blocks</li> <li>• Isolation blocks</li> <li>• Sensor blocks</li> <li>• Electrical component blocks</li> </ul>
Product Selection	Page 12-6	Page 12-47

## Certifications

Allen-Bradley terminal blocks generally have been designed to meet the requirements of one or more regulatory bodies. Most products have also been tested per additional standards. The following is a listing of some of the regulatory bodies and standards which apply to Allen-Bradley terminal block products. See the particular product description for information on specific certifications and ratings.



(Underwriters Laboratories) — Devices in this catalog with one of these ratings have been tested by Underwriters Laboratories and meet the requirements of one or more of the following United States Standards:

- UL 467 — Grounding and Bonding Equipment
- UL 486E — Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors
- UL 1059 — Standard for Terminal Blocks

Reference UL files E34648, E40735, E160646



(Underwriters Laboratories) — Devices in this catalog with this rating have been tested by Underwriters Laboratories and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference UL file E40735



(Canadian Standards Association) — Devices in this catalog with this rating have been tested by the Canadian Standards Association and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference CSA files LR67896



Terminal blocks listed in this catalog meet the requirements of the Low Voltage Directive put forth by the European Union. Devices have been tested and comply with one or more of the following European Norms:

- EN 60947-1 — Low Voltage Switchgear and Controlgear: General Rules
- EN 60947-7-1 — Low Voltage Switchgear and Controlgear: Terminal Blocks for Copper Conductors
- EN 60947-7-2 — Low Voltage Switchgear and Controlgear: Protective Conductor Terminal Blocks for Copper Conductors
- EN 60947-7-3 — Low Voltage Switchgear and Controlgear: Safety Requirements for Fuse Terminal Blocks



**ATEX** — Devices listed in this catalog with “ATEX” ratings meet the following European Norms per DEMKO or KEMA, Approval Certification Bodies for the European Union:

- EN 60079-7 — Electrical Apparatus for Potentially Explosive Atmospheres — General Requirements
- EN 60079-0 — Electrical Apparatus for Potentially Explosive Atmospheres — Increased Safety “e”

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.



## Screw Connection Terminal Blocks

### Certifications/Introduction

**Ex e II** — Many 1492-J, 1492-K, 1492-L, and 1492-W terminal blocks in this catalog meet the following Canadian Standards per Underwriters Laboratories:

CAN/CSA E 60079-7 — Electrical Apparatus for Explosive Atmospheres — Part 0 — General Requirements

CAN/CSA E 60079-0 — Electrical Apparatus for Explosive Atmospheres — Part 7 — Increased Safety “e”

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

**AEx e II** — Devices listed in this catalog with an “AEx e II” rating meet the following United States Standard per Underwriters Laboratories:

- ANSI/UL 60079-0 and 60079-7 — Standard for Electrical Equipment for Use in Class I, Zone 0, 1, and 2 Hazardous (Classified) Locations

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Rockwell Automation sales office or Allen-Bradley distributor for more information.

**Lloyd's Register** — Many 1492-H, 1492-J, 1492-L, and 1492-W terminal blocks in this catalog have been certified for use in marine, off-shore, and industrial installations per the following standard:

- Lloyd's Register Test Specification No. 1:1996

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.

### The Allen-Bradley Line of IEC Terminal Blocks... International Products for a Worldwide Marketplace

The Allen-Bradley Bulletin 1492-J line of internationally approved IEC style terminal blocks offers a wide range of features and benefits ideally suited for many industrial applications. The 1492-J line has been designed to meet the tough requirements of almost every industrial application. Functional, internationally approved, finger-safe, and cost-effective — the Allen-Bradley Bulletin 1492-J line.

### Products Available in the Bulletin 1492 Screw Terminal Block Line

Our family of IEC terminal blocks consists of many different types of blocks, from general feed-through terminal blocks for control wiring to specialty blocks for grounding and isolating. We even offer thermocouple terminal blocks, specifically designed for temperature-dependent process control applications.

Products offered within the Bulletin 1492 Screw Terminal Block line include:

- **Feed-Through Blocks**, capable of accommodating #30...2/0 AWG (0.2...70 mm<sup>2</sup>) wire
- **Grounding Blocks** for grounding a given circuit to the DIN Rail
- **Mini Blocks** for applications where panel space is at a premium
- **Two-Level Blocks** that double circuit wiring density
- **Multi-Conductor Blocks** that allow splitting or joining of control circuits
- **Three-Level Sensor Blocks** for coordination of three-wire sensor groups
- **Isolation Blocks** for circuit isolation during testing and troubleshooting
- **Fuse Blocks**, with and without blown fuse indication, for easily integrated overcurrent protection
- **Electrical Component Blocks** that allow the insertion of fixed components into control circuits. Available components include resistors, diodes, surge suppression circuits, and shunt bars.

# Screw Connection Terminal Blocks

## Specialty Feed-Through Blocks

	1492-J4Q				1492-JD3C				1492-JD4C			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Single-level feed-through terminal block with 2 connection points on each side				Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar			
Certifications		CSA	IEC			CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC			500V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	275V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC	550V AC/DC
Maximum Current	30 A			32 A	20 A	10 A	24 A	21 A	35 A	30 A	32 A	28 A
Wire Range (Rated Cross Section)	#30...10 AWG			0.5...4 mm <sup>2</sup>	#22...12 AWG	#26...12 AWG	2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup> (20...14 AWG)	#26...10 AWG		0.5...4 mm <sup>2</sup>	4 mm <sup>2</sup> (20...12 AWG)
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.28 in. (7 mm)			
Recommended Tightening Torque	6.2 lb•in (0.7 N•m)				4.5...7.1 lb•in (0.5...0.8 N•m)				4.5 lb•in (0.5 N•m)			
Density	49 pcs/ft (163 pcs/m)				59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating (SCCR)	See page 12-42											
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color: Grey	1492-J4Q		50		1492-JD3C		100		1492-JD4C		100	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barriers												
Grey	1492-EBJ4Q		50		1492-EBJD3		20		1492-EBJD4		20	
Blue	—		—		1492-EBJD3-B		20		—		—	
Yellow	1492-EBJ4Q-Y		50		1492-EBJD3-Y		20		—		—	
End Anchors and Retainers:												
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		—		—	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		—		—	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Jumpers:*												
Screw Center Jumper — 41-pole	—		—		—		—		—		—	
Screw Center Jumper — 10-pole	—		—		1492-CJJ5-10		20		—		—	
Screw Center Jumper — 4-pole	—		—		1492-CJJ5-4		50		—		—	
Screw Center Jumper — 3-pole	—		—		1492-CJJ5-3		50		—		—	
Screw Center Jumper — 2-pole	—		—		1492-CJJ5-2		50		—		—	
Plug-in Center Jumper — 41-Pole	1492-CJLJ6-41		10		—		—		1492-CJLJ6-41		10	
Plug-in Center Jumper — 5-, 6-, 7-, 8-, 9-, 10-Pole	1492-CJLJ6-10		20		—		—		1492-CJLJ6-10		20	
Plug-in Center Jumper — 2-, 3-, 4-Pole	1492-CJLJ6-2, -3, -4		60		—		—		1492-CJLJ6-2, -3, -4		60	
Insulated Side Jumper — 24-Pole	—		—		1492-SJ5A-24		50		—		—	
Insulated Side Jumper — 10-Pole	—		—		1492-SJ5A-10		50		—		—	
Screw Type Jumper Notching Tool	—		—		1492-T1		1		—		—	
Other Accessories:												
Partition Plate	—		—		1492-PPJD3		20		1492-PPJD3		20	
Test Plug Socket	—		—		1492-TPS23		20		—		—	
Test Plug	—		—		1492-TP23		20		—		—	
Test Plug (Stackable)	—		—		—		—		—		—	
Marking Systems:	1492-MR6X12 (120/card)		5		1492-M5X8 (144/card)		5		1492-MR6X8 (120/card)		5	
Snap-in marker card	1492-M6X12 (120/card)		5		1492-M5X5 (200/card)		5		1492-M6X5 (200/card)		5	




\* Use of center jumpers may affect spacings, requiring derating of terminal blocks; see page 12-83 for details.





1492-JKD4TW

1492-JKD4Q

1492-H7

Dimensions are not intended to be used for manufacturing purposes.  
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications		Feed-through terminal block with knife disconnect; 3 connection points, 2 on one side			Feed-through terminal block with knife disconnect; 2 connection points on each side			Handle-style isolating terminal block		
Certifications			CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating		600V AC/DC			600V AC/DC			300V AC/DC		
Maximum Current		25 A			25 A			15 A		
Wire Range (Rated Cross Section)		#30...10 AWG			#30...10 AWG			#30...10 AWG		
Fuse Size (Dummy Fuse Supplied)		—			—			1/4 x 1-1/4 in.		
Wire Strip Length		0.39 in. (10 mm)			0.39 in. (10 mm)			0.38 in. (9.7 mm)		
Recommended Tightening Torque		6.2 lb•in (0.7 N•m)			6.2 lb•in (0.7 N•m)			7.1 lb•in (0.8 N•m)		
Density		49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			33 pcs/ft (109 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-40...+221 °F (-40...+105 °C)		
Short-Circuit Current Rating		See page 12-42								
Terminal Blocks		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color:	Grey	1492-JKD4TW		50	1492-JKD4Q		50	—		—
With Test Points	Grey	1492-JKD4TWTP		50	1492-JKD4QTP		50	—		—
	Black	—		—	—		—	1492-H7		25
Accessories		Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:		—		—	—		—	1492-N1		20
3 ft Scored A-B Rail		—		—	—		—	1492-N22		20
3 ft Rigid A-B Rail		—		—	—		—	1492-N44		2
3 ft Rigid Rise A-B Rail		—		—	—		—	1492-N25		2
Standoff Brackets (use every 12 in.) 		—		—	—		—	199-DR1		10
1 m Symmetrical DIN (Steel)		1492-DR5		10	1492-DR5		10	1492-DR5		10
1 m Symmetrical DIN (Aluminum)		1492-DR6		2	1492-DR6		2	1492-DR6		2
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR7		2	1492-DR7		2	1492-DR7		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-EBJ4TW		50	1492-EBJ4Q		50	1492-N37		50
End Barrier	Grey	1492-EBJ4TW-Y		50	1492-EBJ4Q-Y		50	—		—
	Yellow	—		—	—		—	1492-N23		10
End Anchors and Retainers:		—		—	—		—	1492-N47		50
A-B Rail — Heavy Duty		—		—	—		—	1492-ERL35		20
A-B Rail — Normal Duty		1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100
Screwless End Retainer		1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50
DIN Rail - Normal Duty		1492-CJLJ6-41		10	1492-CJLJ6-41		10	—		—
DIN Rail - Heavy Duty		1492-CJLJ6-10		20	1492-CJLJ6-10		20	—		—
Jumpers:		1492-CJLJ6-4		60	1492-CJLJ6-4		60	—		—
Plug-in Center Jumper — 41-pole		1492-CJLJ6-3		60	1492-CJLJ6-3		60	—		—
Plug-in Center Jumper — 10-pole		1492-CJLJ6-2		60	1492-CJLJ6-2		60	—		—
Plug-in Center Jumper — 4-pole		—		—	—		—	1492-N49		10
Plug-in Center Jumper — 3-pole		—		—	—		—	1492-SJS		10
Plug-in Center Jumper — 2-pole		—		—	—		—	—		—
Uninsulated Side Jumper — 10-Pole		—		—	—		—	—		—
Side Jumper — Insulating Sleeve		—		—	—		—	—		—
Other Accessories:		—		—	—		—	—		—
Partition Plate		—		—	—		—	—		—
Marking Systems:		1492-MR6X12 (120/card)		5	1492-MR6X12 (120/card)		5	1492-MS8X12 (56/card)		5
Snap-in marker cards		1492-M6X12 (120/card)		5	1492-M6X12 (120/card)		5	1492-MS8X9 (56/card)		5
Snap-in marker cards		—		—	—		—	1492-ALHFB (50/sheet)		1
Adhesive Labels		—		—	—		—	—		—

\* For use with 1492-N22 DIN rail only.