

Screw Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-J3				1492-J4				1492-J6			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block				Feed-through terminal block			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	690V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	25 A	20 A	24 A	21 A	35 A	25 A	32 A	28 A	50 A	41 A	36 A	
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (#20...14 AWG)	#22...10 AWG	#26...10 AWG	4 mm ²	4 mm ² (#20...12 AWG)	#22...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)				9.0 lb•in (1.0 N•m)				14.2 lb•in (1.6 N•m)			
Density	59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				37 pcs/ft (123 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color:	Grey	1492-J3	100		1492-J4	100		1492-J6	100			
	Red	1492-J3-RE	100		1492-J4-RE	100		1492-J6-RE	100			
	Blue	1492-J3-B	100		1492-J4-B	100		1492-J6-B	100			
	Black	1492-J3-BL	100		1492-J4-BL	100		1492-J6-BL	100			
	Green	1492-J3-G	100		1492-J4-G	100		1492-J6-G	100			
	Yellow	1492-J3-Y	100		1492-J4-Y	100		1492-J6-Y	100			
	Orange	1492-J3-OR	100		1492-J4-OR	100		1492-J6-OR	100			
	Brown	1492-J3-BR	100		1492-J4-BR	100		1492-J6-BR	100			
	White	1492-J3-W	100		1492-J4-W	100		1492-J6-W	100			
	Violet	1492-J3-V	100		1492-J4-V	100		—	—			
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1	10		199-DR1	10			
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5	10		1492-DR5	10			
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2		1492-DR6	2		1492-DR6	2			
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7	2		1492-DR7	2			
End Barriers	Grey	1492-EBJ3	50		1492-EBJ3	50		1492-EBJ3	50			
	Blue	1492-EBJ3-B	50		1492-EBJ3-B	50		1492-EBJ3-B	50			
	Yellow	1492-EBJ3-Y	50		1492-EBJ3-Y	50		1492-EBJ3-Y	50			
End Anchors and Retainers:												
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35	100		1492-EAJ35	100			
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35	50		1492-EAHJ35	50			
Screwless End Retainer	1492-ERL35		20		1492-ERL35	20		1492-ERL35	20			
Jumpers:*												
Screw Center Jumper — 10-pole	1492-CJJ5-10		20		1492-CJJ6-10	20		1492-CJJ8-10	20			
Screw Center Jumper — 4-pole	1492-CJJ5-4		50		1492-CJJ6-4	50		1492-CJJ8-4	50			
Screw Center Jumper — 3-pole	1492-CJJ5-3		50		1492-CJJ6-3	50		1492-CJJ8-3	50			
Screw Center Jumper — 2-pole	1492-CJJ5-2		50		1492-CJJ6-2	50		1492-CJJ8-2	50			
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-50		10		1492-CJLJ6-41 (41-pole)	10		—	—			
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-10		20		1492-CJLJ6-10	20		—	—			
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-9		20		—	—		—	—			
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-8		20		—	—		—	—			
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-7		20		—	—		—	—			
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-6		20		—	—		—	—			
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-5		20		—	—		—	—			
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-4		60		1492-CJLJ6-4	60		—	—			
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-3		60		1492-CJLJ6-3	60		—	—			
Plug-in Center Jumper — 2-Pole	1492-CJLJ5-2		60		1492-CJLJ6-2	60		—	—			
Insulated Side Jumper — 24-Pole	1492-SJ5B-24		50		—	—		—	—			
Insulated Side Jumper — 10-Pole	1492-SJ5B-10		50		—	—		—	—			
Screw Type Jumper Notching Tool	1492-T1		1		1492-T1	1		1492-T1	1			
Other Accessories:												
Partition Plate	1492-EBJ16		20		1492-EBJ16	20		1492-EBJ16	20			
Test Plug Socket	1492-TPS23		20		1492-TPS23L	50		1492-TPS23L	50			
Test Plug	1492-TP23		20		1492-TP23	20		1492-TP23	20			
Test Plug (Stackable)	1492-TPJ5		25		1492-TPJ6	25		—	—			
Electrical Warning Plate	1492-EWPJ5		25		1492-EWPJ5	25		1492-EWPJ8	50			
Marking Systems:												
Snap-in Marker Cards	1492-M5X12 (144/card)		5		1492-M6X12 (120/card)	5		1492-MR8X12 (84/card)	5			
	1492-M5X5 (200/card)		5		1492-M6X5 (200/card)	5		1492-M8X5 (160/card)	5			

* Use of center jumpers may affect spacings, requiring derating of terminal blocks. See page 12-83 for details.