



- Bulletin 700-HP — (PCB) "Pin Style" Relay
- 8 A contact ratings
- DPDT/ (2 c/o) contacts
- Plug-in PIN style (PCB) terminals (5 mm pinning)
- Choice of standard silver nickel contacts, or silver nickel with gold-plated contacts

Table of Contents

Product Selection this page

Accessories..... 9-59



Specifications..... 9-60

Approximate Dimensions..... 9-61

Standards Compliance and Certifications

See Specification table in this section, page 9-60.

Product Selection
Slim Line Relay with "PIN Style" Terminations

	Description	Contact Rating	Wiring Diagrams		Coil Voltage	Package Quantity	Cat. No.
			U.S./Canada	International			
	DPDT 2-Pole 2 Form C AgNi + Au Gold Plated Contacts	8 A			6V AC	10	700-HPX2A06
	Sockets				12V AC	10	700-HPX2A12
24V AC					10	700-HPX2A24	
120V AC					10	700-HPX2A1	
240V AC					10	700-HPX2A2	
6V DC					10	700-HPX2Z06	
12V DC					10	700-HPX2Z12	
24V DC					10	700-HPX2Z24	
48V DC					10	700-HPX2Z48	
110V DC					10	700-HPX2Z1	
6V AC					10	700-HP32A06	
12V AC					10	700-HP32A12	
24V AC					10	700-HP32A24	
120V AC	10				700-HP32A1		
Sockets	240V AC	10	700-HP32A2				
	6V DC	10	700-HP32Z06				
	12V DC	10	700-HP32Z12				
	24V DC	10	700-HP32Z24				
	48V DC	10	700-HP32Z48				
	110V DC	10	700-HP32Z1				
	Bulletin 700-HP DPDT		700-HN123	700-HN123			