




	Description			Connection Diagrams	For Use With	Pkg. Qty.	Cat. No.
	Mechanical Interlock - For interlocking of two adjacent contactors - No added width to contactor assembly - Front mount plug-in type - Optional auxiliary contact blocks and suppressor modules mount onto the interlock				100/104-K/-KR, 700-K/-KR	1	100-KMCH
	Surge Suppressor - Plug-in type - Limits surge voltage on coil drop-off	RC Suppressor	24...48V AC		100/104-K/-KR, 700-K/-KR	1 *	100-KFSC50
			110...280V AC			1 *	100-KFSC280
			380...480V AC			1 *	100-KFSC480
		MOV Suppressor	12...55V AC, 12...77V DC		100/104-K/-KR, 700-K/-KR	1 *	100-KFSV55
			56...136V AC, 78...180V DC			1 *	100-KFSV136
			137...277V AC, 181...250V DC			1 *	100-KFSV277
		Diode Suppressor	12...250V DC		100/104-K/-KR, 700-K/-KR	1 *	100-KFSD250

* May be ordered in package quantities of 10. Add letter M to the end of the cat. no. Example: **100-KFSC50M**.

Timers

	Description		Connection Diagrams	For Use With	Pkg. Qty.	Cat. No.
	Solid-State Timing Element 110...250V AC or DC - Includes 35 mm Hat Rail adapter	On-Delay, 0.1...3 s		100/104-K, 700-K	10	100-KT3S
		On-Delay, 1...30 s				100-KT30S


Connecting Components

	Description		For Use With	Pkg. Qty.	Cat. No.
	ECO Connecting Module — 12 A - For DOL and reversing starters - Eco-starters mount on single DIN Rail (140M on DIN Rail) - Electrical and mechanical interconnection of 140M and 100-K contactors	Connects: 140M-C circuit breakers with 100-K contactors	140M-C to 100-K	1 ★	140M-C-PEK12
	Power Wiring Kit For Reversing and Star/Delta combinations. Star-point bridge not included. Min. interruption time 50 ms		100-K	1	100-KPR
	Feeder Terminal for Compact Bus Bars Max. current 34 A	Supply of compact bus bars	100-K	1	100-KWT
	Three-Phase Compact Bus Bars Max. current 34 A	For 100-K, 5...12 A contactors 45 mm spacing (3 connections)‡	100-K	1	100-KW453
		For 100-K, 5...12 A contactors 45 mm spacing (4 connections)‡	100-K	1	100-KW454

* May be ordered in package quantities of 10. Add letter M to the end of the cat. no. Example: **140M-C-PEK12M**.

‡ Combinations possible. Example: For 6 contactor connections use one cat. no. 100-KW453 and one cat. no. 100-KW454.

Marking Systems

	Description	Pkg. Qty.	Cat. No.
	Label Sheet 105 self-adhesive paper labels each, 6 x 17 mm	10	100-FMS
	Snap-In Marker Card	5	1492-M6X12