



|                                                                                   | Description                                                                                                                                    |                                                                                                                                                                                                                                                                                                         | Pkg. Qty. | Cat. No.    |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------------|
|   | <b>Diode Surge Suppressor</b><br>Voltage Range: 6...220V DC used with 700-HN221, 700-HN222 sockets                                             |                                                                                                                                                                                                                                                                                                         | 10        | 700-ADR     |
|                                                                                   | <b>Diode with LED Surge Suppressor</b><br>Voltage Range: 6...24V DC used with 700-HN221, 700-HN222 sockets                                     |                                                                                                                                                                                                                                                                                                         | 10        | 700-ADL1R   |
|                                                                                   | <b>Diode with LED Surge Suppressor</b><br>Voltage Range: 28...60V DC used with 700-HN221, 700-HN222 sockets                                    |                                                                                                                                                                                                                                                                                                         | 10        | 700-ADL2R   |
|                                                                                   | <b>Diode with LED Surge Suppressor</b><br>Voltage Range: 110...220V DC used with 700-HN221, 700-HN222 sockets                                  |                                                                                                                                                                                                                                                                                                         | 10        | 700-ADL3R   |
|                                                                                   | <b>Varistor with LED Surge Suppressor</b><br>Voltage Range: 6...24V AC used with 700-HN221, 700-HN222 sockets                                  |                                                                                                                                                                                                                                                                                                         | 10        | 700-AV1R    |
|                                                                                   | <b>Varistor with LED Surge Suppressor</b><br>Voltage Range: 110...240V AC used with 700-HN221, 700-HN222 sockets                               |                                                                                                                                                                                                                                                                                                         | 10        | 700-AV3R    |
|                                                                                   | <b>RC Surge Suppressor</b><br>Voltage Range: 6...24V AC/DC used with 700-HN221, 700-HN222 sockets                                              |                                                                                                                                                                                                                                                                                                         | 10        | 700-AR1     |
|                                                                                   | <b>RC Surge Suppressor</b><br>Voltage Range: 110...240V AC/DC used with 700-HN221, 700-HN222 sockets                                           |                                                                                                                                                                                                                                                                                                         | 10        | 700-AR2     |
|   | <b>Timing Module</b><br>On-Delay or One-Shot selectable voltage range: 12...24V AC/DC used with sockets that accept plug-in accessory modules. | <div>On-Delay</div> <div>U (A1/A2) </div> <div>LED &amp; R</div> <div>One-Shot</div> <div>U (A1/A2) </div> <div>LED &amp; R</div> | 1         | 700-AT3     |
|                                                                                   | <b>Timing Module</b><br>On-Delay or One-Shot selectable voltage range: 110...125V AC used with sockets that accept plug-in accessory modules.  |                                                                                                                                                                                                                                                                                                         |           | 700-AT3A1   |
|                                                                                   | <b>Timing Module</b><br>On-Delay or One-Shot selectable voltage range: 230...240V AC used with sockets that accept plug-in accessory modules.  |                                                                                                                                                                                                                                                                                                         |           | 700-AT3A2   |
|   | 8-Way Jumper can be cut to required length. Rated 10 A - 250V. Used with 700-HN221, 700-HN222 sockets.                                         | Red                                                                                                                                                                                                                                                                                                     | 1         | 700-HN180R  |
| Cat. No. 700-HN180                                                                |                                                                                                                                                | Grey                                                                                                                                                                                                                                                                                                    |           | 700-HN180G  |
|                                                                                   |                                                                                                                                                | Blue                                                                                                                                                                                                                                                                                                    |           | 700-HN180B  |
|  | <b>DIN (#3) symmetrical hat rail</b><br>35 x 7.5 x 1 m                                                                                         |                                                                                                                                                                                                                                                                                                         | 10        | 199-DR1     |
| Cat. No. 199-DR1                                                                  |                                                                                                                                                |                                                                                                                                                                                                                                                                                                         |           |             |
|                                                                                   | <b>Relay Identification Snap-in Markers</b><br>Snap-in markers fit on top of product covers. The following are blank cards.                    |                                                                                                                                                                                                                                                                                                         | 100       | 1492-MS6X9  |
|                                                                                   |                                                                                                                                                |                                                                                                                                                                                                                                                                                                         |           | 1492-MS6X12 |
|                                                                                   |                                                                                                                                                |                                                                                                                                                                                                                                                                                                         |           | 1492-MS8X12 |

**Note:**Spring clamp sockets are also available. Cat. No. 700-HN223 for Cat. No. 700-HK36 and Cat. No. 700-HN224 for 700-HK32.

**Bulletin 700-HK Slim Line Relay, Socket, and Retainer Clip Reference Chart**

| Relay Type | Socket Cat. No.                 | Retainer Clip Cat. No. |
|------------|---------------------------------|------------------------|
| 700-HK32   | 700-HN122, 700-HN222, 700-HN224 | Provided               |
| 700-HK36   | 700-HN121, 700-HN221, 700-HN223 |                        |

|                                    |                | Cat. No. 700-HK...        |                                                                                        |                          |                                                                     |
|------------------------------------|----------------|---------------------------|----------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------|
| Electrical Ratings                 |                |                           |                                                                                        |                          |                                                                     |
| Rated Thermal Current ( $I_{th}$ ) |                | 1-Pole, 1 CO, SPDT — 16 A |                                                                                        | 2-Pole, 2 CO, DPDT — 8 A |                                                                     |
| Rated Insulation Voltage ( $U_i$ ) |                | 250V IEC, 300V UL/CSA     |                                                                                        |                          |                                                                     |
| Contacts                           | Inductive V AC | 120V AC                   | AC-15, 6.2 A<br>B300 Pilot Duty, 3 A<br>A300 (700-HKM_)<br>1/3 Hp (0.24 kW) 1-phase    | 120V AC                  | AC-15, 2.9 A<br>B300 Pilot Duty, 3.0 A<br>1/4 Hp (0.18 kW), 1-phase |
|                                    |                | 240V AC                   | AC-15, 3.1 A<br>B300 Pilot Duty, 1.5 A<br>A300 (700-HKM_)<br>3/4 Hp (0.55 kW), 1-phase | 240V AC                  | AC-15, 1.4 A<br>B300 Pilot Duty, 1.5 A<br>1/2 Hp (0.37 kW), 1-phase |
|                                    |                | 230V AC                   | 0.55 kW, 1-phase                                                                       | 230V AC                  | 0.37 kW, 1-phase                                                    |
|                                    | Inductive V DC | 24V DC                    | DC-13, 5.0 A                                                                           | 24V DC                   | DC-13, 3.0 A                                                        |
|                                    |                | 125V DC                   | DC-13, 0.2 A<br>R300 Pilot Duty, 0.22 A                                                | 125V DC                  | DC-13, 0.2 A<br>R300 Pilot Duty, 0.22 A                             |
|                                    |                |                           |                                                                                        |                          |                                                                     |